

Type 6014 3/2-way solenoid valve

Address

Bürkert Fluid Control Systems
Christian-Bürkert-Str. 13-17
D-74653 Ingelfingen
Tel. +49 (0)7940 10-91 111
E-mail: info@burkert.com
International: country.burkert.com

Manuals on the Internet: country.burkert.com



Important information for devices with UL approval

Operating conditions:

Fluidic data

Temperature-/fluid ratings General Purpose Valve							
	Seal designation	Seal material	Fluid temperature		Ambient temperature		Fluids
			[°F]	[°C]	[°F]	[°C]	
6014	EG, EF	PTFE + Graphite, PTFE + FKM	-40...+266 °F	-40...+130 °C	-40...+131 °F	-40...+55 °C	Air, Inert gas, Steam
6014 with manual override			+14...+248 °F	-10...+120 °C	+14...+131 °F	-10...+55 °C	
6014			+32...+212 °F	0...+100 °C	+32...+131 °F	0...+55 °C	Water
6014	FF with IB46	FKM	-40...+212 °F	-40...+100 °C	-40...+131 °F	-40...+55 °C	Air, Inert gas
6014	FF	FKM	+14...+212 °F	-10...+100 °C	+14...+131 °F	-10...+55 °C	Air, Inert gas
			+32...+212 °F	0...+100 °C	+32...+131 °F	0...+55 °C	Water
6014 with manual override	AA	EPDM	-22...+212 °F	-30...+100 °C	-22...+131 °F	-30...+55 °C	Air, Inert gas, Steam
			+14...+212 °F	-10...+100 °C	+14...+131 °F	-10...+55 °C	
6014			+32...+212 °F	0...+100 °C	+32...+131 °F	0...+55 °C	Water
6014	BB	NBR	+14...+194 °F	-10...+90 °C	+14...+131 °F	-10...+55 °C	No. 2 Fuel Oil
	FF	FKM	+14...+248 °F	-10...+120 °C	+14...+131 °F	-10...+55 °C	

Direction of flow

from 1(P) → 2(A) (Circuit function C) or
from 1(P) → 2(B) (Circuit function D)