



Pneumatically operated 2-way Globe Control Valve

- Excellent control characteristics
- High cycle life and maintenance-free operation
- Flow optimised body in stainless steel
- Several K_{VS} value per port size due to removable valve seats
- Control units can be mounted directly without external tubing

Product variants described in the data sheet may differ from the product presentation and description.

Can be combined with

	Type 8692 Digital electropneumatic positioner for integrated mounting on process control valves	▶
	Type 8694 Digital electropneumatic positioner for integrated mounting on process control valves	▶
	Type 8696 Digital electropneumatic positioner for integrated mounting on process control valves	▶
	Type 8693 Digital electropneumatic process controller for integrated mounting on process control valves	▶
	Type 8792 Digital electropneumatic positioner SideCONTROL	▶
	Type 8791 Digital electropneumatic positioner SideCONTROL	▶
	Type 8793 Digital electropneumatic Process Controller SideCONTROL	▶
	Type 8802 Continuous control valve systems ELEMENT – overview	▶

Type description

In line with Bürkert's philosophy the construction of the Type 2301 globe valve fulfils tough criteria for process environments. Unrivalled cycle life and sealing integrity is guaranteed by the proven self adjusting spindle packing with exchangeable V-seals. Each globe valve body can be fitted with up to five sizes of trim sets. These parabolic trims provide a reliable and repeatable characteristic to vary the flow. The control cones are available in either stainless steel or with a durable PTFE seal or PEEK seal for tight shut-off. Leakage class III, IV or VI are available. The design enables the easy integration of automation modules whether they are digital electropneumatic positioner or process controller. The fully integrated system has a compact and smooth design, integrated pneumatic lines, IP65/67 protection class and superior chemical resistance.

Table of contents

1. General technical data	4
2. Product variants	5
2.1. ELEMENT	5
2.2. Stainless steel drive guide for higher drive forces.....	5
3. Control functions	5
4. Approvals and conformities	6
4.1. General notes	6
4.2. Conformity	6
4.3. Standards.....	6
4.4. Explosion protection.....	6
4.5. Drinking water	6
4.6. Foods and beverages/Hygiene.....	7
4.7. Others	7
DNV GL classification.....	7
Oxygen	7
Fuel gases	7
Hydrogen.....	7
TA Luft.....	7
5. Materials	8
5.1. Bürkert resistApp.....	8
5.2. Material specifications.....	8
ELEMENT	8
Stainless steel for higher drive forces.....	9
6. Dimensions	10
6.1. Actuator.....	10
Continuous ELEMENT Type 2301 valve	10
Valve system Continuous ELEMENT.....	11
6.2. Body with flange connection.....	13
6.3. Body with threaded connection.....	14
6.4. Body with welded connection.....	15
6.5. Body with clamp connection	16
7. Performance specifications	17
7.1. Fluidic data.....	17
Flow characteristics	17
Overview of fluidic data for flow below seat (for liquids, steam and gases)	17
Pilot pressure diagrams with flow direction below seat (control function B).....	21
7.2. Operating limits.....	22
Operating limits for medium temperature and operating pressure	22
Operating limits for ambient and medium temperature.....	23
Operating limits for seat seal	23
Operating limits for optional variants	24
8. Product accessories	24
9. Networking and combination with other Bürkert products	28

10. Ordering information	30
10.1. Bürkert eShop	30
10.2. Bürkert product filter	30
10.3. Bürkert Product Enquiry Form	30
10.4. Ordering chart flange connection.....	31
Valves with flow direction below seat.....	31
10.5. Ordering chart threaded connection	34
Valves with flow direction below seat.....	34
10.6. Ordering chart welded connection.....	37
Valves with flow direction below seat.....	37
10.7. Ordering chart clamp connection.....	40
Valves with flow direction below seat.....	40

DTS 1000112932 EN Version: - Status: RL (released | freigegeben | valide) printed: 06.10.2026

valvesgo.com

1. General technical data

Product properties	
Dimensions	Further information can be found in chapter "6. Dimensions" on page 10.
Material	Further information can be found in chapter "5. Materials" on page 8.
Design	Globe control valve
Nominal diameter (port connection)	DN 10...DN 100, NPS 3/8...NPS 4
Safety setting in case of power failure	Normally closed (control function A), normally open (control function B)
Flow direction	Flow to open (below seat)
Performance data	
Operating pressure	0...25 bar(g), 40 bar(g) on request (see "7.1. Fluidic data" on page 17) Vacuum variant... - 0.9 bar(g) (option)
Nominal pressure	PN 25/PN 40 (DIN EN 1333), Class 150 (DIN EN 1759)
Seat leakage	Leakage class III and IV (DIN EN 60534 - 4:2006) for stainless steel Leakage class VI for PTFE and PEEK (see "7.1. Fluidic data" on page 17)
K _v value	0.1 m³/h...140 m³/h (see "7.1. Fluidic data" on page 17)
Operating characteristic	Equal percentage, linear (others on request)
Theoretical rangeability	50:1
Medium data	
Medium	Steam, water, neutral gases, alcohols, oils, fuels, hydraulic fluids, salt solutions, organic solvents, oxygen and fuel gases of families I, II and III in accordance with the Gas Appliances Regulation (EU) 2016/426, Hydrogen (optional), lyes (optional)
Medium temperature	- 40 °C...+ 230 °C (see "7.2. Operating limits" on page 22)
Viscosity	Max. 600 mm²/s
Control medium	Air, neutral gases
Product connections	
Port connection ^{2,)}	
Flange connection	DIN EN 1092 - 1 ANSI B 16.5 JIS 10K
Threaded connection	G (DIN ISO 228 - 1) NPT (ASME B1.20.1) RC (ISO 7 - 1)
Welded connection	DIN EN ISO 1127 / ISO 4200 / DIN 11866 series B DIN 11850 - 2 / DIN 11866 series A ASME BPE / DIN 11866 series C SMS 3008
Clamp connection	DIN 32676 series B (pipe: ISO 4200) DIN 32676 series A (pipe: DIN 11850 - 2) ASME BPE
Approvals and conformities	
Further information can be found in chapter "4. Approvals and conformities" on page 6	
Environment and installation	
Environmental factors	Protect the device from electromagnetic interference, UV radiation and, when used outdoors, from weather conditions.
Ambient temperature	- 10 °C...+ 80 °C (with positioner or process controller Type 8791/8792/8793) - 10 °C...+ 55 °C (with positioner or process controller Type 8692/8693/8694) (see "7.2. Operating limits" on page 22)
Degree of protection	IP65/67
Installation position	As required, preferably with actuator upright

1.) Others are available on request.

2. Product variants





2.1. ELEMENT

Product properties	
Nominal diameter (port connection)	DN 10...DN 100
Actuator size	50 mm (D), 70 mm (M), 90 mm (N), 130 mm (P)
Performance data	
Pilot pressure (CF A)	5.6...7 bar(g) for control function B (see "Pilot pressure diagrams with flow direction below seat (control function B)" on page 21)

2.2. Stainless steel drive guide for higher drive forces

Product properties	
Nominal diameter (port connection)	DN 65...DN 100
Actuator size	225 mm (L)
Performance data	
Pilot pressure (CF A)	DN 65, 3.7 bar(g)...7 bar(g) DN 80, DN 100, 5.5 bar(g)...7 bar(g) 5 bar(g) for control function B (see "Pilot pressure diagrams with flow direction below seat (control function B)" on page 21)

3. Control functions

Symbol	Description	
Flow direction below seat for fluids, steam and gases		
	Control function A (CF A) Pneumatically operated 2/2-way control valve Flow direction below seat Normally closed by spring force	
	Control function B (CF B) Pneumatically operated 2/2-way control valve Flow direction below seat Normally opened by spring force	

DTS 1000112932 EN Version: - Status: RL (released | freigegeben | valide) printed: 06.10.2026

4. Approvals and conformities

4.1. General notes

- The approvals and conformities listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available variants can be supplied with the below mentioned approvals or conformities.

4.2. Conformity

In accordance with the Declaration of Conformity, the product is compliant with the EU Directives. This includes the following directives:

- Pressure Equipment Directive 2014/68/EU
- Machinery Directive 2006/42/EC

4.3. Standards

The applied standards which are used to demonstrate compliance with the EU Directives are listed in the EU-Type Examination Certificate and/or the EU Declaration of Conformity.

4.4. Explosion protection

Approval	Description																
 	Optional: Explosion protection (valid for the variable code PX51) As a category 2 device suitable for zone 1/21 and zone 2/22. ATEX: EPS 18 ATEX 2 008 X II 2G Ex h IIC T4...T2 Gb II 2D Ex h IIIC T135 °C...T300 °C Db IECEx: IECEx EPS 18.0007X Ex h IIC T4...T2 Gb Ex h IIIC T135 °C...T300 °C Db <table><tr><th>Temperature class</th><th>T2</th><th>T3</th><th>T4</th></tr><tr><td>Maximum surface temperature</td><td>+ 300 °C</td><td>+ 200 °C</td><td>+ 135 °C</td></tr><tr><td>Ambient temperature</td><td>- 40 °C...+ 130 °C</td><td>- 40 °C...+ 130 °C</td><td>- 40 °C...+ 100 °C</td></tr><tr><td>Maximum medium temperature</td><td>+ 285 °C</td><td>+ 185 °C</td><td>+ 125 °C</td></tr></table> Note: The ambient and medium temperature range may be limited by non-ex-relevant specifications. Observe the Operating Instructions.	Temperature class	T2	T3	T4	Maximum surface temperature	+ 300 °C	+ 200 °C	+ 135 °C	Ambient temperature	- 40 °C...+ 130 °C	- 40 °C...+ 130 °C	- 40 °C...+ 100 °C	Maximum medium temperature	+ 285 °C	+ 185 °C	+ 125 °C
Temperature class	T2	T3	T4														
Maximum surface temperature	+ 300 °C	+ 200 °C	+ 135 °C														
Ambient temperature	- 40 °C...+ 130 °C	- 40 °C...+ 130 °C	- 40 °C...+ 100 °C														
Maximum medium temperature	+ 285 °C	+ 185 °C	+ 125 °C														

4.5. Drinking water

Conformity	Description
	Suitable for use in drinking water applications The materials comply with the assessment principles (UBA) for materials in contact with drinking water (TrinkwasserV). Stainless steel body PF39: Suitable for products with medium temperature up to 85 °C (hot water)

4.6. Foods and beverages/Hygiene

Conformity	Description
FDA	FDA – Code of Federal Regulations (valid for the variable code PL02, PL03) All wetted materials are compliant with the Code of Federal Regulations published by the FDA (Food and Drug Administration, USA) according to the manufacturer's declaration.
USP	United States Pharmacopeial Convention (USP) (valid for the variable code PL04) All wetted materials are biocompatible according to the manufacturer's declaration.
	EC Regulation 1935/2004 of the European Parliament and of the Council (valid for the variable code PL01, PL02) All wetted materials are compliant with EC Regulation 1935/2004/EC according to the manufacturer's declaration.
	China food GB Standards of the People's Republic of China (valid for the variable code PL10) All wetted materials are compliant with the requirement of China food GB Standards according to the manufacturer's declaration.

4.7. Others

DNV GL classification

Approval	Description
	DNV GL classification – Ships, offshore units, and high speed and light craft The products are accepted for installation on all vessels classed by DNV GL.

Oxygen

Conformity	Description
O ₂	Optional: Suitability for oxygen (valid for the variable code NL02) The products are suitable for use with gaseous oxygen, according to the manufacturer's declaration.

Fuel gases

Conformity	Description
CE	Fuel gases (valid for the variable code PO19, PO20) The products comply with: - Regulation (EU) 2016/426 – Appliances burning gaseous fuels and - DVGW DIN EN 161 (Automatic shut-off valves for gas burners and gas appliances) and - DIN EN 16678, Class A or Class D (Safety and control devices for gas burners and gas burning appliances – Automatic shut-off valves for operating pressure of above 500 kPa up to and including 6 300 kPa)

Hydrogen


Conformity	Description
H ₂	Optional: Suitability for hydrogen (valid for the variable code NG18) The products are suitable for use with gaseous hydrogen, according to the manufacturer's declaration.

TA Luft

Conformity	Description
TA Luft	Technical instruction on air quality control (valid for the variable code PM01)

5. Materials

5.1. Bürkert resistApp



Bürkert resistApp – Chemical resistance chart


You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.

[Start chemical resistance check](#)

5.2. Material specifications


ELEMENT

Note:
The Type 2301 globe control valve is supplied with different port connections (flange, thread, welded connection and clamp). These connections are not shown. They correspond to the valve body material.



No.	Element	Material
1	Pilot air ports	Push-in connector PP
2	Actuator cover	PPS
3	Actuator casing	Stainless steel 1.4561 (316Ti)
4	Piston seal	FKM
5	Spring	Stainless steel 1.4310
6	Pipe	Stainless steel CF3M
7	Packing gland	PTFE V-Rings (filled), with spring compensation
8	Spindle	Stainless steel 1.4401 (316)/1.4404 (316L)
9	Spindle guide	Stainless steel 1.4404 (316L), PTFE filled
10	Body seal	Graphite or PTFE
11	Control cone	Stainless steel 1.4571 (optionally hardened)
12	Spring straight pin	Stainless steel 1.4310
13	Seat seal	Stainless steel 1.4571 (optionally hardened), PTFE or PEEK
14	Valve seat with o-Ring	Stainless steel 1.4571, EPDM
15	Valve body	Stainless steel 316L / CF3M

Stainless steel for higher drive forces




No.	Element	Material
1	Actuator cover	Stainless steel 1.4308
2	Actuator	Stainless steel 1.4404
3	Piston seal	FKM
4	Nut	Stainless steel 1.4301
5	Spring	Stainless steel 1.4310
6	Pipe	Stainless steel CF3M
7	Packing gland	PTFE V-rings (filled), with spring compensation
8	Spindle	Stainless steel 1.4021
9	Spindle guide	Stainless steel 1.4404 (316L) / PTFE filled
10	Body seal	Graphite or PTFE
11	Control cone	Stainless steel 1.4571 (optionally hardened)
12	Spring straight pin	Stainless steel 1.4310
13	Seat seal	Stainless steel 1.4571 (optionally hardened), PTFE or PEEK
14	Valve seat with o-ring	Stainless steel 1.4571, EPDM
15	Valve body	Stainless steel 316L / CF3M

6. Dimensions

6.1. Actuator

Continuous ELEMENT Type 2301 valve

Note:
Dimensions in mm, unless otherwise stated







Nominal diameter (port connection)		Actuator size Ø	Ø A	H
DN	NPS			
10	3/8	50 (D)	64.5	226
		70 (M)	91	239
15	1/2	50 (D)	64.5	226
		70 (M)	91	239
20	3/4	50 (D)	64.5	232
		70 (M)	91	245
		90 (N)	120	307
25	1	50 (D)	64.5	235
		70 (M)	91	248
		90 (N)	120	301
32	1 1/4	90 (N)	120	329
		130 (P)	159	381
40	1 1/2	90 (N)	120	334
		130 (P)	159	386
50	2	90 (N)	120	340
		130 (P)	159	392
65	2 1/2	130 (P)	159	446
		225 (L)	245	460
80	3	130 (P)	159	454
		225 (L)	245	467
100	4	130 (P)	159	464
		225 (L)	245	477

DTS 1000112932 EN Version: - Status: RL (released | freigegeben | valide) printed: 06.10.2026

Valve system Continuous ELEMENT


Note:

- Dimensions in mm, unless otherwise stated
- Please note actuator size A in table “6.1. Actuator” on page 10

With positioner TopControl			With remote positioner Side-CONTROL
Type 8692 or with process controller TopControl	Type 8694	Type 8696	Type 8792 or with remote process controller SideCONTROL
Type 8693			Type 8793
			

DTS 1000112932 EN Version: - Status: RL (released | freigegeben | valide) printed: 06.10.2026

Nominal diameter (port connection)		Actuator size Ø	HS with		
DN	NPS		Type 8692 or Type 8693	Type 8694 or Type 8696	Type 8792 or Type 8793
10	3/8	50 (D)	–	329	–
		70 (M)	383	342	342
15	1/2	50 (D)	–	329	–
		70 (M)	383	342	342
20	3/4	50 (D)	–	335	–
		70 (M)	389	348	348
		90 (N)	449	405	413
25	1	50 (D)	–	342	–
		70 (M)	392	351	351
		90 (N)	445	404	404
32	1 1/4	90 (N)	473	432	432
		130 (P)	525	484	484
40	1 1/2	90 (N)	478	437	437
		130 (P)	530	489	489
50	2	90 (N)	484	443	443
		130 (P)	536	495	495
65	2 1/2	130 (P)	590	549	549
		225 (L)	603	564	564
80	3	130 (P)	598	557	557
		225 (L)	611	572	572
100	4	130 (P)	608	567	567
		225 (L)	621	582	582




DTS 1000112932 EN Version: - Status: RL (released | freigegeben | valide) printed: 06.10.2026

6.2. Body with flange connection

Note:

Dimensions in mm, unless otherwise stated




Nominal diameter (pipe)	DIN EN 1092 PN 25 FTF 1 according to DIN EN 558 - 1							JIS 10K FTF 10 according to DIN EN 558 - 2						
DN	Ø DF	LF	Ø BF	AF	Ø D	A x α	Ø MF	Ø DF	LF	Ø BF	AF	Ø D	A x α	Ø MF
10	90	130	60	16	14	4 × 90°	13.6	—	—	—	—	—	—	—
15	95	130	65	16	14	4 × 90°	18.1	95	108	70	12	15	4 × 90°	18.1
20	105	150	75	18	14	4 × 90°	23.7	100	117	75	14	15	4 × 90°	23.7
25	115	160	85	18	14	4 × 90°	29.7	125	127	90	14	19	4 × 90°	29.7
32	140	180	100	18	18	4 × 90°	38.4	135	140	100	16	19	4 × 90°	38.4
40	150	200	110	18	18	4 × 90°	44.3	140	165	105	16	19	4 × 90°	44.3
50	165	230	125	20	18	4 × 90°	56.3	155	203	120	16	19	4 × 90°	56.3
65	185	290	145	22	18	8 × 45°	66.0	175	216	140	18	19	4 × 90°	71.5
80	200	310	160	24	18	8 × 45°	81.0	185	241	150	18	19	8 × 45°	84.3
100	235	350	190	24	22	8 × 45°	100.0	210	292	175	18	19	8 × 45°	109.1

Nominal diameter (pipe)	ANSI B 16.5 Class 150 FTF 37 according to DIN EN 558 - 2						
NPS	Ø DF	LF	Ø BF	AF	Ø D	A x α	Ø MF
½	89	184	60.5	11.2	15.7	4 × 90°	15.7
¾	99	184	69.9	12.7	15.7	4 × 90°	20.8
1	108	184	79.2	14.2	15.7	4 × 90°	26.7
1½	127	222	98.6	17.5	15.7	4 × 90°	40.9
2	152	254	120.7	19.1	19.1	4 × 90°	52.6
2½	178	276	139.7	22.3	19.1	4 × 90°	62.7
3	190	298	152.5	23.9	19.1	4 × 90°	78.0
4	229	352	190.5	23.9	19.1	8 × 45°	102.4

6.3. Body with threaded connection


Note:
Dimensions in mm, unless otherwise stated



Nominal diameter (port connection)		G (DIN ISO 228 - 1) NPT (ASME B1.20.1) RC (ISO 7 - 1)				
		E			LM	AF
DN	NPS	G	NPT	RC		
10	3/8	12	10.3	10.1	65	27
15	1/2	14	13.7	13.2	65	27
20	3/4	16	14	14.5	75	34
25	1	18	16.8	16.8	90	41
32	1 1/4	20	17.3	19.1	110	50
40	1 1/2	22	17.3	19.1	120	55
50	2	24	17.6	23.4	150	70
65	2 1/2	26	23.7	26.7	185	85
80	3	28	30.5	29.8	205	100
100	4	32	33	35.8	240	125

6.4. Body with welded connection

Note:
Dimensions in mm, unless otherwise stated




Nominal diameter (port connection) DN	ES	LS	DIN EN ISO 1127 - 1 / ISO 4200 / DIN 11866 series B		DIN 11850 - 2 / DIN 11866 series A / DIN EN 10357 series A	
			Ø DS	WS	Ø DS	WS
10	20	90	17.2	1.6	13	1.5
15	20	90	21.3	1.6	19	1.5
20	20	100	26.9	1.6	23	1.5
25	26	130	33.7	2.0	29	1.5
32	26	140	42.4	2.0	35	1.5
40	26	150	48.3	2.0	41	1.5
50	26	175	60.3	2.0	53	1.5
65	26	210	76.1	2.3	70	2.0
80	26	230	88.9	2.3	85	2.0
100	26	260	114.3	2.6	104	2.0

Nominal diameter (port connection) NPS	ES	LS	ASME BPE / DIN 11866 series C	
			Ø DS	WS
½	20	90	12.7	1.65
¾	20	90	19.05	1.65
1	20	100	25.4	1.65
1½	26	140	38.1	1.65
2	26	150	50.8	1.65
2½	26	175	63.5	1.65
3	26	210	76.2	1.65
4	26	260	101.6	2.11

Nominal diameter (port connection) NPS	ES	LS	SMS 3008	
			Ø DS	WS
20	20	100	25	1.2
32	26	140	38	1.2
40	26	175	51	1.2
50	26	175	63.5	1.6
65	26	210	76.1	1.6
100	26	260	101.5	2

6.5. Body with clamp connection

Note:
Dimensions in mm, unless otherwise stated



Nominal diameter (port connection)		Clamp: DIN 32676 series A Pipe: DIN 11850 - 2 / DIN 11866 series A / DIN EN 10357 series A			Clamp: DIN 32676 series B Pipe: DIN EN ISO 1127 / ISO 4200 / DIN 11866 series B			
DN	LC	Ø D2 C	Ø D1 C	SC	LC	Ø D2 C	Ø D1 C	SC
15	126	19	34	1.5	146	21.3	50.5	1.6
20	136	23	34	1.5	136	26.9	50.5	1.6
25	173	29	50.5	1.5	164	33.7	50.5	2.0
40	193	41	50.5	1.5	193	48.3	64.0	2.0
50	218	53	64	1.5	218	60.3	77.5	2.0


Nominal diameter (port connection)		Clamp: ASME BPE / DIN 11866 series C Pipe: ASME BPE / DIN 11866 series C		
NPS	LC	Ø D2 C	Ø D1 C	SC
½	122	12.7	25.0	1.65
¾	126	19.05	25.0	1.65
1	126	25.4	50.5	1.65
1½	172	38.1	50.5	1.65
2	182	50.8	64.0	1.65
2½	231	63.5	77.5	1.65
3	265	76.2	91.0	1.65
4	315	101.6	119.0	2.11

7. Performance specifications

7.1. Fluidic data

Flow characteristics

- Equal-percentage flow characteristic according to DIN EN 60534 - 2 - 4 (linear characteristic curve on request)
- K_{VR} value at 5 % of the stroke for seat size > 10 mm
 K_{VR} value at 10 % of the stroke for seat size ≤ 10 mm
- Actuator size 70 offers a better control quality compared to actuator size 50 and is therefore preferred (K_{VR} value = smallest K_V value, at which the tilt tolerance according to DIN EN 60534 - 2 - 4 is still maintained).



Equal percentage flow curve - detailed values please see below

Overview of fluidic data for flow below seat (for liquids, steam and gases)

Note:

- K_V value [m^3/h]: measurement with water according to DIN EN 60534 - 2 - 4
- Operating limits (see "7.2. Operating limits" on page 22)

Nominal diameter (port connection)		Seat size	Actuator size Ø	Operating pressure max. (Seat leakage class)			Theoretical rangeability	K _v value water at stroke [m³/h]											K _{vs} value
				Seat seal				5 %	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	90 %	100 %	
				CF A															
				Stainless steel	PTFE	PEEK													
DN	NPS		[mm]	[bar(g)]			[m³/h]												
10	¾ ²⁾	3	50 (D)	16 (IV)	–	–	20:1	–	0.005	0.009	0.013	0.019	0.026	0.034	0.044	0.060	0.077	0.1	
			70 (M)	25 (IV) 40 (IV) ⁴⁾															
		3	50 (D)	16 (IV)			20:1	–	0.009	0.015	0.023	0.033	0.046	0.063	0.085	0.11	0.16	0.2	
			70 (M)	25 (IV) 40 (IV) ⁴⁾															
		4	50 (D)	16 (IV)			30:1	–	0.023	0.033	0.049	0.070	0.097	0.14	0.18	0.26	0.35	0.5	
			70 (M)	25 (IV) 40 (IV) ⁴⁾															
		6	50 (D)	16 (IV)	16 (VI)	10 (VI)	50:1	0.019	0.026	0.046	0.072	0.11	0.17	0.25	0.39	0.57	0.85	1.25	
			70 (M)	25 (IV) 40 (IV) ⁴⁾	25 (IV) 40 (IV) ⁴⁾	25 (VI)													
		8	50 (D)	16 (IV)	16 (VI)	10 (VI)		0.060	0.070	0.090	0.12	0.18	0.26	0.42	0.61	0.92	1.5	2.0	
			70 (M)	25 (IV) 40 (IV) ⁴⁾	25 (IV) 40 (IV) ⁴⁾	25 (VI)													
		10	50 (D)	16 (IV)	16 (VI)	10 (VI)		0.090	0.11	0.13	0.19	0.30	0.48	0.73	1.0	1.6	2.3	2.7	
			70 (M)	25 (IV) 40 (IV) ⁴⁾	25 (IV) 40 (IV) ⁴⁾	25 (VI)													

Nominal diameter (port connection)		Seat size	Actuator size Ø	Operating pressure max. (Seat leakage class)			Theoretical rangeability	K _v value water at stroke [m³/h]											K _{vs} value
				Seat seal															
				CF A															
				Stainless steel	PTFE	PEEK		5 %	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	90 %	100 %	
DN	NPS		[mm]	[bar(g)]				[m³/h]											
15	½ ^{2.)}	3	50 (D)	16 (IV)	–	–	20:1	–	0.005	0.009	0.013	0.019	0.026	0.034	0.044	0.060	0.077	0.1	
			70 (M)	25 (IV) 40 (IV) ^{4.)}															
		3	50 (D)	16 (IV)			20:1	–	0.009	0.015	0.023	0.033	0.046	0.063	0.085	0.11	0.16	0.2	
			70 (M)	25 (IV) 40 (IV) ^{4.)}															
		4	50 (D)	16 (IV)			30:1	–	0.023	0.033	0.049	0.070	0.097	0.14	0.18	0.26	0.35	0.5	
			70 (M)	25 (IV) 40 (IV) ^{4.)}															
		6	50 (D)	16 (IV)			50:1	0.019	0.026	0.046	0.072	0.11	0.17	0.25	0.39	0.57	0.85	1.25	
			70 (M)	25 (IV) 40 (IV) ^{4.)}															
		8	50 (D)	16 (IV)				0.070	0.080	0.11	0.13	0.19	0.27	0.43	0.63	0.95	1.6	2.1	
			70 (M)	25 (IV) 40 (IV) ^{4.)}															
		10	50 (D)	16 (IV)				0.090	0.11	0.15	0.19	0.31	0.49	0.75	1.1	1.7	2.5	3.1	
			70 (M)	25 (IV) 40 (IV) ^{4.)}															
		15	50 (D)	16 (IV)				0.14	0.17	0.22	0.35	0.52	0.80	1.2	1.8	2.7	3.7	4.3	
			70 (M)	25 (IV) 40 (IV) ^{4.)}															
20	¾ ^{2.)}	10	50 (D)	16 (IV)	16 (VI)	10 (VI)		0.11	0.12	0.16	0.20	0.33	0.52	0.77	1.2	1.8	2.6	3.2	
			70 (M)	25 (IV) 40 (IV) ^{4.)}	25 (VI) 40 (VI) ^{4.)}	10 (VI)													
		15	50 (D)	16 (IV)	16 (VI)	10 (VI)		0.14	0.17	0.22	0.35	0.52	0.80	1.2	1.8	2.9	4.0	5.2	
			70 (M)	25 (IV) 40 (IV) ^{4.)}	25 (VI) 40 (VI) ^{4.)}	25 (VI)													
		20	70 (M)	16 (IV)	16 (VI)	10 (VI)		0.20	0.25	0.30	0.45	0.70	1.1	1.6	2.4	3.5	5.2	7.1	
			90 (N)	25 (IV) 40 (IV) ^{4.)}	25 (VI) 40 (VI) ^{4.)}	25 (VI)													

Nominal diameter (port connection)		Seat size	Actuator size Ø	Operating pressure max. (Seat leakage class)			Theoretical range-ability	K _v value water at stroke [m³/h]											K _{vs} value
				Seat seal															
				CF A															
				Stainless steel	PTFE	PEEK		5 %	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	90 %	100 %	
DN	NPS		[mm]		[bar(g)]			[m³/h]											
25	1	3	50 (D)	16 (IV)	–	–	20:1	–	0.005	0.009	0.013	0.019	0.026	0.034	0.044	0.060	0.077	0.1	
			70 (M)	25 (IV) 40 (IV) ⁴⁾															
		3	50 (D)	16 (IV)	20:1	–	0.009	0.015	0.023	0.033	0.046	0.063	0.085	0.11	0.16	0.2			
			70 (M)	25 (IV) 40 (IV) ⁴⁾															
		4	50 (D)	16 (IV)	30:1	–	0.023	0.033	0.049	0.070	0.097	0.14	0.18	0.26	0.35	0.5			
			70 (M)	25 (IV) 40 (IV) ⁴⁾															
		6	50 (D)	16 (IV)	50:1	0.019	0.026	0.046	0.072	0.11	0.17	0.25	0.39	0.57	0.85	1.25			
			70 (M)	25 (IV) 40 (IV) ⁴⁾													25 (VI) 40 (VI) ⁴⁾	25 (VI)	
		8	50 (D)	16 (IV)	0.070	0.080	0.11	0.13	0.19	0.27	0.43	0.63	0.95	1.6	2.1				
			70 (M)	25 (IV) 40 (IV) ⁴⁾												25 (VI) 40 (VI) ⁴⁾	25 (VI)		
		10	50 (D)	16 (IV)	0.11	0.12	0.16	0.20	0.33	0.52	0.77	1.2	1.8	2.6	3.2				
			70 (M)	25 (IV) 40 (IV) ⁴⁾												25 (VI) 40 (VI) ⁴⁾	25 (VI)		
		15	50 (D)	16 (IV)	0.14	0.17	0.22	0.35	0.52	0.80	1.2	1.8	2.9	4.1	5.3				
			70 (M)	25 (IV) 40 (IV) ⁴⁾												25 (VI) 40 (VI) ⁴⁾	25 (VI)		
		20	70 (M)	16 (IV)	0.20	0.25	0.31	0.47	0.70	1.1	1.6	2.5	3.8	5.4	7.2				
			90 (N)	25 (IV) 40 (IV) ⁴⁾												25 (VI) 40 (VI) ⁴⁾	25 (VI)		
		25	70 (M)	12 (IV)	0.35	0.38	0.65	1.0	1.5	2.2	3.4	5.1	7.0	9.4	12.0				
			90 (N)	25 (IV)												25 (VI)	20 (VI)		
32	1¼ ²⁾	20	90 (N)	25 (IV)	25 (VI)	25 (VI)	0.21	0.24	0.32	0.43	0.60	0.85	1.2	1.6	2.3	3.3	4.8		
			130 (P)				0.22	0.25	0.35	0.50	0.70	1.1	1.6	2.5	3.8	5.8	8.0		
		25	90 (N)	20 (VI)	0.38	0.45	0.65	0.93	1.3	1.8	2.6	3.7	5.1	6.7	8.9				
			130 (P)		0.40	0.47	0.73	1.1	1.6	2.5	3.7	5.4	7.5	10.3	13.0				
		32	90 (N)	16 (IV)	16 (VI)	10 (VI)	0.45	0.58	0.80	1.1	1.7	2.5	3.5	4.9	7.0	10.1	13.4		
			130 (P)				0.48	0.60	0.85	1.3	2.1	3.1	4.5	6.8	10.2	14.0	17.8		
40	1½ ²⁾	25	90 (N)	25 (IV)	25 (VI)	10 (VI)	0.38	0.47	0.68	0.95	1.4	1.9	2.7	3.7	5.2	7.2	9.4		
			130 (P)				0.40	0.50	0.75	1.1	1.7	2.6	3.8	5.6	8.0	10.7	13.6		
		32	90 (N)	16 (IV)	16 (VI)	10 (VI)	0.45	0.55	0.80	1.1	1.7	2.5	3.6	5.0	7.2	10.8	14.4		
			130 (P)				0.48	0.60	0.85	1.3	2.1	3.2	4.6	6.9	11.0	15.0	20.0		
		40	90 (N)	12 (IV)	12 (VI)	7 (VI)	0.55	0.67	1.0	1.5	2.3	3.2	4.5	6.5	9.5	13.7	17.5		
			130 (P)				0.60	0.70	1.1	1.7	2.7	4.0	6.0	9.2	13.8	18.2	24.0		

Nominal diameter (port connection)		Seat size	Actuator size Ø	Operating pressure max. (Seat leakage class)			Theoretical range-ability	K _v value water at stroke [m³/h]											K _{vs} value	
				Seat seal																
				CF A																
				Stainless steel	PTFE	PEEK		5 %	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	90 %	100 %		
DN	NPS		[mm]		[bar(g)]		[m³/h]													
50	2 ^{2 1}	20	90 (N)	25 (20 ^{1 1}) (IV)	–	–	50:1	–	0.12	0.23	0.33	0.47	0.67	0.96	1.4	1.9	2.7	3.8		
			130 (P)	25 (20 ^{1 1}) (IV)					0.14	0.25	0.38	0.57	0.85	1.3	1.9	2.8	4.1	6.3		
		32	90 (N)	16 (IV)					0.29	0.46	0.66	0.95	1.3	1.9	2.7	3.7	5.2	7.4		
			130 (P)	25 (20 ^{1 1}) (IV)	0.31	0.51			0.76	1.1	1.7	2.5	3.6	5.3	7.9	12.0				
		32	90 (N)	16 (IV)	16 (VI)	10 (VI)		0.45	0.56	0.80	1.1	1.7	2.5	3.6	5.0	7.2	11.4	15.3		
			130 (P)	25 (20 ^{1 1}) (IV)	25 (20 ^{1 1}) (VI)	20 (VI)		0.48	0.60	0.90	1.3	2.1	3.2	4.6	6.9	11.6	16.0	21.0		
		40	90 (N)	12 (IV)	12 (VI)	7 (VI)		0.57	0.68	0.90	1.5	2.1	3.2	4.5	6.4	9.5	13.8	18.0		
			130 (P)	25 (20 ^{1 1}) (IV)	25 (20 ^{1 1}) (VI)	20 (VI)		0.60	0.70	1.0	1.7	2.6	4.0	5.9	9.2	14.0	18.9	24.5		
		50	90 (N)	7 (III)	7 (VI)	–		0.85	1.1	1.7	2.6	3.8	5.4	7.7	11.4	16.0	21.5	28.0		
			130 (P)	25 (20 ^{1 1}) (IV)	25 (20 ^{1 1}) (VI)	20 (VI)		0.90	1.1	1.9	2.9	4.5	6.8	10.5	15.5	22.0	29.5	37.0		
		65	2 1/2 ^{2 2}	40	130 (P)	25 (15 ^{1 1}) (IV)		25 (15 ^{1 1}) (VI)	20 (15 ^{1 1}) (VI)	0.65	0.75	1.1	1.8	2.8	4.3	6.5	10.4	16.0	22.0	29.0
				50	130 (P)	16 (15 ^{1 1}) (IV)		16 (15 ^{1 1}) (VI)	10 (VI)	1.0	1.2	2.0	3.1	4.8	6.7	9.7	16.0	24.0	35.0	45.0
65	130 (P)			16 (15 ^{1 1}) (IV)	16 (15 ^{1 1}) (VI)	12 (VI)	1.6	2.0	3.0	5.0	8.0	13.5	22.0	33.0	45.0	56	65			
	225 (L) ^{3 3}			20 (15 ^{1 1}) (IV)	20 (15 ^{1 1}) (VI)	12 (VI)	1.1	1.4	2.1	3.2	4.9	8.0	12.0	18.5	31.5	46.5	62			
	225 (L)			25 (15 ^{1 1}) (IV)	25 (15 ^{1 1}) (VI)	16 (15 ^{1 1}) (VI)														
80	3 ^{2 2}			50	130 (P)	25 (12.5 ^{1 1}) (IV)	25 (12.5 ^{1 1}) (VI)	20 (12.5 ^{1 1}) (VI)	1.0	1.2	2.0	3.4	5.3	8.3	13.0	19.0	26.0	35.0	45.0	
		65	130 (P)		16 (12.5 ^{1 1}) (IV)	16 (12.5 ^{1 1}) (VI)	10 (VI)	1.6	2.0	2.9	5.0	8.2	13.0	22.0	35.0	48.0	61	73		
		225 (L) ^{3 3}	25 (12.5 ^{1 1}) (IV)	25 (12.5 ^{1 1}) (VI)	16 (12.5 ^{1 1}) (VI)	1.4	1.7	2.5	3.8	5.7	8.2	12.2	19.5	32.5	50	70				
			225 (L)	25 (12.5 ^{1 1}) (IV)	25 (12.5 ^{1 1}) (VI)	20 (12.5 ^{1 1}) (VI)														
		80	130 (P)	10 (IV)	10 (VI)	10 (VI)	2.5	3.4	6.3	10.7	16.0	27.0	42.5	58	73	87	100			
			225 (L) ^{3 3}	16 (12.5 ^{1 1}) (IV)	16 (12.5 ^{1 1}) (VI)	10 (VI)	2.1	2.6	4.2	7.0	10.5	16.0	25.0	40.0	60	83	100			
			225 (L)	25 (12.5 ^{1 1}) (IV)	25 (12.5 ^{1 1}) (VI)	15 (12.5 ^{1 1}) (VI)														
		100	4	65	130 (P)	16 (10 ^{1 1}) (IV)	16 (10 ^{1 1}) (VI)	10 (VI)	50:1	1.4	1.8	2.8	5.0	8.8	15.0	25.0	37.0	50	64	77
225 (L) ^{3 3}	25 (10 ^{1 1}) (IV)				25 (10 ^{1 1}) (VI)	16 (10 ^{1 1}) (VI)	1.4	1.7	2.6	3.8	5.7	8.3	12.6	20.0	32.0	51	75			
225 (L)	25 (10 ^{1 1}) (IV)				25 (10 ^{1 1}) (VI)	20 (10 ^{1 1}) (VI)														
80	130 (P)			10 (IV)	10 (VI)	10 (VI)	2.2	3.1	5.9	10.3	17.5	30.0	48.0	66	82	97	110			
	225 (L) ^{3 3}			16 (10 ^{1 1}) (IV)	16 (10 ^{1 1}) (VI)	10 (VI)	2.1	2.6	4.3	7.0	11.0	17.0	26.5	44.0	65	89	115			
	225 (L)			25 (10 ^{1 1}) (IV)	25 (10 ^{1 1}) (VI)	15 (10 ^{1 1}) (VI)														
100	130 (P)			6 (IV)	6 (VI)	–	3.8	5.2	9.5	15.0	26.0	46.5	68	90	111	128	140			
	225 (L) ^{3 3}			10 (IV)	10 (VI)	6 (VI)	3.2	3.9	5.7	9.0	13.5	20.5	32.0	51	83	118	140			
	225 (L)			16 (10 ^{1 1}) (IV)	16 (10 ^{1 1}) (VI)	10 (VI)														


- 1.) According to the Pressure Equipment Directive 97/23/EC for compressible fluids of Group 1 (hazardous gases and vapours according to Article 3 No. 1.3 letter a first dash)
- 2.) Deviation for port connections according to ASME BPE: the next largest nominal diameter is used, e.g. NPS 1 instead of NPS ¾.
- 3.) Reduced spring force
- 4.) Only for housing variants with nominal pressure PN 40 (optional)

Pilot pressure diagrams with flow direction below seat (control function B)
Note:


d = Seat size

Actuator size Ø 50 mm


Maximum control pressure 7 bar(g)


Actuator size Ø 70 mm


Maximum control pressure 7 bar(g)


Actuator size Ø 90 mm


Maximum control pressure 7 bar(g)


Actuator size Ø 130 mm

Maximum control pressure 7 bar(g)


Actuator size Ø 225 mm


Maximum control pressure 5 bar(g)




7.2. Operating limits

Operating limits for medium temperature and operating pressure

In addition to the maximum operating pressures, the operating range of Bürkert process valves is limited by the nominal pressure according to the relevant standard.



Operating limits for ambient and medium temperature



Operating limits for seat seal

Tight sealing required	Leakage class (DIN EN 60534 - 4)	Medium temperature	Seat seal
No An additional shut-off valve is recommended	III/IV (metal seals) Metal-sealed valves have larger leakages (0.1% or 0.01% of the nominal flow rate are permissible). Metallic seals are impervious even under demanding process conditions.	- 40...+ 230 °C	Stainless steel
	For particularly demanding process conditions such as cavitation, erosion by wet steam or abrasive media, hardened cones and seats can be used to significantly increase the service life.		Hardened stainless steel
Yes An additional shut-off valve is often unnecessary.	VI (soft seals) By using plastics as sealing material, the control valves can close tightly. Their use is not recommended in cases of increased erosion due to demanding process conditions.	- 40...+ 130 °C (recommended for ≤ + 130 °C)	PTFE
		- 10...+ 230 °C (recommended for > + 130 °C)	PEEK

DTS 1000112932 EN Version: - Status: RL (released | freigegeben | valide) printed: 06.10.2026

Operating limits for optional variants

High-temperature variant

Thanks to an adaption of the spindle seal, this variant is suitable for applications with steam, neutral gases and other heat transfer mediums up to + 230 °C.

Water variant

For applications with water up to + 200 °C, a special configuration of the spindle seal increases service life significantly. It is recommended for water temperatures starting at + 85 °C.

Drinking water variant

Wetted materials are tested in contact with the medium are tested for suitability with drinking water up to + 85 °C.

Vacuum variant

Without leakage bore, this design is suitable for pressures down to - 0.9 bar(g).

Low-temperature variant

Suitable for minimum medium temperatures down to - 40 °C

Oxygen variant

Non-metallic wetted materials are tested for suitability with oxygen and are suitable for operating pressures up to 25 bar(g) and medium temperatures up to + 60 °C. Optional variant for operating pressures up to 40 bar(g) and medium temperatures up to + 100 °C on request.

Hydrogen variant

Wetted materials are tested for suitability with hydrogen and are suitable for operating pressures up to 40 bar(g) and medium temperatures up to + 100 °C.

The hydrogen variant of Type 2301 is tested for an external tightness (stem seal and body seal) totalling 10^{-6} mbar*l/s at 40 bar, + 20 °C helium and 2.78×10^{-3} mbar*l/s at 40 bar, - 10 °C/+ 100 °C hydrogen. An external leak-tightness of 10^{-4} mbar*l/s is ensured when delivered.

8. Product accessories

Process controller TopControl

Type 8693 ▶ Actuator size Ø 70/90/130/225 mm



The intelligent process controller Type 8693 is designed for integrated mounting on pneumatic actuators from the process control valve series Type 23xx/2103 and especially for the requirements of hygienic process conditions. Using the TUNE functions, the positioner and process controller can be initialised automatically. Easy operation and selection of additional software functions as well as parameterisation are carried out via the large graphic display and a touch keypad. Device configuration and parameterisation can also be conveniently carried out by the Bürkert Communicator software via a PC interface.

Features

- Contactless position sensor
- Universal control system for single and double acting actuators
- Highly dynamic actuating system without internal pilot air consumption in the balanced state
- Integrated diagnostic functions for valve monitoring
- Automatic initialisation of the positioner and process controller using the TUNE function
- Safeguarding in the event of failure of the electrical or pneumatic auxiliary power
- PROFIBUS DPV1, EtherNet/IP, PROFINET, Modbus TCP, Bürkert system bus (bÜS)
- Compact and robust hygienic stainless steel design

Customer benefits

- Quick and easy commissioning
- Intuitive and simple operation via a graphic display with backlight and touch keypad
- High system availability due to increased drive service life by means of spring chamber ventilation
- Guaranteed reliability and predictable maintenance through valve monitoring and diagnostics
- Easy maintenance and process monitoring

Positioner TopControl
Type 8692 ▶ Actuator size Ø 70/90/130/225 mm


The intelligent electropneumatic positioner Type 8692 is designed for integrated attachment to pneumatic actuators of the process control valve series Type 23xx/2103 and especially for the requirements of hygienic process conditions. The positioner can be initialised automatically using the TUNE function. Easy operation and the selection of the extensive additional software functions as well as parameterisation are carried out via the large graphic display and the touch keypad. The device configuration and parameterisation can also be conveniently carried out using the Bürkert Communicator software via a PC interface.

Features

- Contactless position sensor
- Universal positioning system for single and double-acting actuators in the balanced state
- Highly dynamic positioning system without internal pilot air consumption
- Integrated diagnostic functions for valve monitoring
- Automatic initialisation of the positioner by using the TUNE function
- Safeguard in the event of failure of the electrical or pneumatic auxiliary power
- PROFIBUS DPV1, EtherNet/IP, PROFINET, Modbus TCP, Bürkert system bus (bÜS)
- Compact and robust hygienic stainless steel design

Customer benefits

- Quick and easy commissioning
- Intuitive and simple operation via graphic display with backlight and touch keypad
- High system availability due to increased drive service life by means of spring chamber ventilation
- Guaranteed reliability and predictable maintenance through valve monitoring and diagnostics

Positioner TopControl BASIC
Type 8694 ▶ Actuator size Ø 70/90/130/225 mm


The compact positioner Type 8694/8696 is designed for integrated attachment to pneumatic actuators of the Type 23xx/2103 process control valve series and especially for the requirements of hygienic process conditions. Operation and parameterisation are performed via push buttons and DIP switches. The device configuration and parameterisation can also be conveniently carried out using the Bürkert Communicator software via a PC interface.

Features

- Contactless position sensor
- Universal positioning system for single and double-acting actuators
- Ultra dynamic positioning system without internal pilot air consumption
- AS-Interface, IO-Link, Bürkert system bus (bÜS) (only 8694)
- Compact and robust hygienic stainless steel design

**Type 8696 ▶
Actuator size Ø 50 mm**

Customer benefits

- Simple and safe commissioning using the teach function
- Minimum space requirement in the plant pipework for more flexibility in plant design
- High system availability due to increased drive service life by means of spring chamber ventilation

Process controller SideCONTROL Remote
Type 8793 ▶ with remote sensor 8798 ▶ Actuator size Ø 70/90/130/225 mm


The intelligent digital positioner and process controller Type 8793 is designed for mounting on lift or swivel drives with standardisation in accordance with IEC 534 - 6 or VDI/VDE 3845 for demanding control tasks. The variant with remote position sensor Type 8798 is used to control Bürkert process control valves. It is operated via a graphic display with backlight. The initialisation of the positioner and process controller can be done automatically using the TUNE function. The type of controlled system is automatically recognised and the appropriate controller structure with the corresponding optimum parameter set is determined.

Features

- Universal control system for single and double acting actuators
- Integrated diagnostic functions for valve monitoring
- Automatic initialisation of the position and process controller using the TUNE function
- Ultra-dynamic actuating system without internal pilot air consumption
- Illuminated graphic display with backlight and touch keypad
- PROFIBUS DPV1, EtherNet/IP, PROFINET, Modbus TCP, Bürkert system bus (bÜS)
- Compact and robust design
- Adaptation according to IEC 534 - 6 or VDI/VDE 3845 for lift and swivel drives or as remote variant on Bürkert process valves

Customer benefits

- Quick and easy commissioning
- Intuitive and simple operation via graphic display with backlight and touch keypad
- Guaranteed reliability and scheduled maintenance thanks to valve monitoring and diagnostics
- Easy maintenance and process monitoring
- Long service life

Positioner SideCONTROL Remote
Positioner Type 8792 ▶ with remote sensor Type 8798 ▶ Actuator size Ø 70/90/130/225 mm


The intelligent digital positioner and process controller Type 8792 is designed for attachment to lift and swivel drives with standardisation according to IEC 534 - 6 or VDI/VDE 3845 for demanding control tasks. The Type 8798 variant with remote position sensor is used to control Bürkert process control valves. It is operated via a graphic display with backlight. The initialisation of the positioner and process controller can be done automatically by using the TUNE function.

Features

- Illuminated graphic display with backlight and touch keypad
- Universal control system for single and double acting actuators
- Ultra-dynamic actuating system without internal pilot air consumption
- Integrated diagnostic functions for valve monitoring
- PROFIBUS DPV1, EtherNet/IP, PROFINET, Modbus TCP, Bürkert system bus (bÜS)
- Compact and robust design
- Adaptation according to IEC 534 - 6 or VDI/VDE 3845 for lift and swivel drives or as remote variant on Bürkert process valves

Customer benefits

- Quick and easy commissioning
- Intuitive and simple operation via a graphic display with backlight and touch keypad
- Guaranteed reliability and scheduled maintenance thanks to valve monitoring and diagnostics
- Long service life

Positioner SideCONTROL BASIC Remote
Positioner Type 8791 ▶ with remote sensor Type 8798 ▶ Actuator size Ø 70/90/130/225 mm


The intelligent digital positioner and process controller Type 8791/8798 is designed for mounting on linear and rotary actuators with standardisation in accordance with IEC 534 - 6 or VDI/VDE 3845 for demanding control tasks. The variant with remote position sensor Type 8798 is used for controlling Bürkert process control valves. It is operated via a graphic display with backlight. The positioner and process controller can be initialised automatically using the TUNE functions.

Features

- Simple design
- Universal control system for single and double acting actuators
- Highly dynamic actuating system without internal pilot air consumption in the balanced state
- Adaptation according to IEC 534 - 6 or VDI/VDE 3845 for lift and swivel drives or as remote variant on Bürkert process valves
- AS-Interface, IO-Link, Bürkert system bus (bÜS) (only for positioner Type 8791 BASIC Remote)

**Positioner IP20 Type 8791 ▶
with remote sensor
Type 8798 ▶ Actuator size
Ø 70/90/130/225 mm**

Customer benefits

- Simple commissioning
- Simple device for simple control tasks
- Low energy consumption

9. Networking and combination with other Bürkert products

The **Type 2301 Globe Control Valve** can be combined with our extensive range of positioners and process controllers to form the **Continuous ELEMENT valve system, Type 8802-GD**.


The range of the control unit consists of;

- A digital electropneumatic positioner/process controller **Type 8692/8693** (for valve actuator sizes Ø 70/90/130/225 mm)
- A digital electropneumatic positioner, basic **Type 8694** (for valve actuator size Ø 70/90/130/225 mm)
- A digital electropneumatic positioner, basic **Type 8696** (for valve actuator size Ø 50 mm)
- An electropneumatic positioner, SideCONTROL **Type 8792** or an electropneumatic process controller, **Type 8793** (for valve actuator size Ø 70/90/130/225 mm) and a remote sensor, **Type 8798**
- An electropneumatic positioner, SideCONTROL Basic **Type 8791** (for valve actuator size Ø 70/90/130/225 mm) and a remote sensor, **Type 8798**

Note:

- For the configuration of further valve systems please use the **Product Enquiry Form** (see **"10.3. Bürkert Product Enquiry Form" on page 30**).
- You order two components and receive a completely assembled and tested valve.

Example with threaded connection



Control valve



Type 2301

Digital electropneumatic process controller / positioner SideCONTROL

			
Type 8793 ▶ Process controller + Type 8798 ▶ Remote sensor Actuator Ø 70, 90, 130, 225	Type 8792 ▶ Positioner + Type 8798 ▶ Remote sensor Actuator Ø 70, 90, 130, 225	Type 8791 ▶ Positioner + Type 8798 ▶ Remote sensor Actuator Ø 70, 90, 130, 225	SideCONTROL Basic IP20 Positioner Actuator Ø 50

ELEMENT Continuous control valve system

		
Type 8802-GD-Q ▶ 2301 + 8793 + 8798	Type 8802-GD-P ▶ 2301 + 8792 + 8798	Type 8802-GD-O ▶ 2301 + 8791 + 8798

10. Ordering information

10.1. Bürkert eShop



Bürkert eShop – Easy ordering and quick delivery

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

[Order online now](#)

10.2. Bürkert product filter



Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

10.3. Bürkert Product Enquiry Form

Note:

Please see our Product Enquiry Form for a full explanation of our specification key.

Bürkert Product Enquiry Form – Your enquiry quickly and compactly

Would you like to make a specific product enquiry based on your technical requirements? Use our Product Enquiry Form for this purpose. There you will find all the relevant information for your Bürkert contact. This will enable us to provide you with the best possible advice.

[Fill out the form now](#)

10.4. Ordering chart flange connection

Valves with flow direction below seat

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Article no.	
DN	NPS				Seat seal	
			[mm]	[m³/h]	PTFE	Stainless steel
DIN EN 1092 - 1						
10	3/8	3	70 (M)	0.1	—	o. r.
		3	70 (M)	0.2	—	o. r.
		4	70 (M)	0.5	—	o. r.
		6	70 (M)	1.25	370257	350725
		8	70 (M)	2	213985	215212
		10	70 (M)	2.7	213989	215215
15	1/2	3	70 (M)	0.1	—	o. r.
		3	70 (M)	0.2	—	o. r.
		4	70 (M)	0.5	—	o. r.
		6	70 (M)	1.25	234255	378904
		8	70 (M)	2.1	213987	215214
		10	70 (M)	3.1	213991	215217
		15	70 (M)	4.3	204932	205010
20	3/4	10	70 (M)	3.2	210530	215218
		15	70 (M)	5.2	213993	214030
		20	70 (M)	7.1	204935	205012
25	1	15	70 (M)	5.3	213994	214031
		20	70 (M)	7.2	213995	214032
		25	70 (M)	12	204937	205014
			90 (N)	12	242054	229421
32	1 1/4	25	90 (N)	8.9	213997	210446
			130 (P)	13	222634	222655
		32	90 (N)	13.4	204939	205016
			130 (P)	17.8	223597	223598
40	1 1/2	32	90 (N)	14.4	213999	214035
			130 (P)	20.2	222636	222657
		40	90 (N)	17.5	204941	205018
			130 (P)	23.8	219791	222659
50	2	40	90 (N)	18	214001	214037
			130 (P)	24.6	222638	222660
		50	90 (N)	28	204942	205019
			130 (P)	37	214003	214039
65	2 1/2	50	130 (P)	45	214005	214040
			225 (L)	39.5	20060552	20060584
		65	130 (P)	65	217772	219618
			225 (L)	62	20060553	20060585
80	3	65	130 (P)	73	239545	239581
			225 (L)	70	20060554	20060587
		80	130 (P)	100	239540	239576
			225 (L)	100	20060555	20060589
100	4	80	130 (P)	110	239561	239597
			225 (L)	115	20060556	20060590
		100	130 (P)	140	239556	331125
			225 (L)	140	20060557	20060591

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Article no.	
DN	NPS				Seat seal	
			[mm]	[m³/h]	PTFE	Stainless steel
JIS 10K						
15	½	3	70 (M)	0.1	–	o. r.
		3	70 (M)	0.2	–	o. r.
		4	70 (M)	0.5	–	o. r.
		6	70 (M)	1.25	367023 ₪	o. r.
		8	70 (M)	2.1	215203 ₪	215228 ₪
		10	70 (M)	3.1	213913 ₪	213911 ₪
		15	70 (M)	4.3	204953 ₪	205030 ₪
20	¾	10	70 (M)	3.2	215204 ₪	215229 ₪
		15	70 (M)	5.2	213936 ₪	213933 ₪
		20	70 (M)	7.1	204955 ₪	205032 ₪
25	1	15	70 (M)	5.3	214020 ₪	214059 ₪
		20	70 (M)	7.2	213930 ₪	213914 ₪
		25	70 (M)	12	204957 ₪	205034 ₪
			90 (N)	12	242165 ₪	242199 ₪
32	1¼	25	90 (N)	8.9	213939 ₪	213937 ₪
			130 (P)	13	222643 ₪	222665 ₪
		32	90 (N)	13.4	213177 ₪	213178 ₪
			130 (P)	17.8	222645 ₪	222667 ₪
40	1½	32	90 (N)	14.4	213932 ₪	213931 ₪
			130 (P)	20.2	222647 ₪	222668 ₪
		40	90 (N)	17.5	204959 ₪	205037 ₪
			130 (P)	23.8	222649 ₪	222670 ₪
50	2	40	90 (N)	18	213941 ₪	213940 ₪
			130 (P)	24.6	222650 ₪	222671 ₪
		50	90 (N)	28	204960 ₪	205038 ₪
			130 (P)	37	214023 ₪	214062 ₪
65	2½	50	130 (P)	45	214024 ₪	214063 ₪
			225 (L)	39.5	20060565 ₪	20060599 ₪
		65	130 (P)	65	219617 ₪	219620 ₪
			225 (L)	62	20060568 ₪	20060600 ₪
80	3	65	130 (P)	73	239547 ₪	239584 ₪
			225 (L)	70	20060569 ₪	20060601 ₪
		80	130 (P)	100	239542 ₪	239578 ₪
			225 (L)	100	20060570 ₪	20060602 ₪
100	4	80	130 (P)	110	239563 ₪	239599 ₪
			225 (L)	115	20060571 ₪	20060604 ₪
		100	130 (P)	140	239558 ₪	239594 ₪
			225 (L)	140	20060572 ₪	20060605 ₪

o. r. = on request

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Article no.	
DN	NPS				Seat seal	
			[mm]	[m³/h]	PTFE	Stainless steel
ANSI B 16.5						
15	½	3	70 (M)	0.1	–	o. r.
			70 (M)	0.2	–	o. r.
		4	70 (M)	0.5	–	o. r.
		6	70 (M)	1.25	367211 ₪	380948 ₪
		8	70 (M)	2.1	215198 ₪	215221 ₪
		10	70 (M)	3.1	215199 ₪	215222 ₪
		15	70 (M)	4.3	204944 ₪	205021 ₪
20	¾	10	70 (M)	3.2	215200 ₪	215223 ₪
		15	70 (M)	5.2	214009 ₪	214046 ₪
		20	70 (M)	7.1	204946 ₪	205023 ₪
25	1	15	70 (M)	5.3	214010 ₪	214047 ₪
		20	70 (M)	7.2	214011 ₪	214048 ₪
		25	70 (M)	12	204948 ₪	205025 ₪
			90 (N)	12	464851 ₪	464367 ₪
40	1½	32	90 (N)	14.4	215201 ₪	215224 ₪
			130 (P)	20.2	463905 ₪	463913 ₪
		40	90 (N)	17.5	204950 ₪	205027 ₪
			130 (P)	23.8	463907 ₪	463915 ₪
50	2	40	90 (N)	18	214013 ₪	214050 ₪
			130 (P)	24.6	463908 ₪	463916 ₪
		50	90 (N)	28	204951 ₪	205028 ₪
			130 (P)	37	214015 ₪	214052 ₪
65	2½	50	130 (P)	45	239537 ₪	239573 ₪
			225 (L)	39.5	20060558 ₪	20060592 ₪
		65	130 (P)	65	239535 ₪	239572 ₪
			225 (L)	62	20060559 ₪	20060594 ₪
80	3	65	130 (P)	73	239546 ₪	239582 ₪
			225 (L)	70	20060560 ₪	20060595 ₪
		80	130 (P)	100	239541 ₪	239577 ₪
			225 (L)	100	20060562 ₪	20060596 ₪
100	4	80	130 (P)	110	239562 ₪	239598 ₪
			225 (L)	115	20060563 ₪	20060597 ₪
		100	130 (P)	140	239557 ₪	239593 ₪
			225 (L)	140	20060564 ₪	20060598 ₪

o. r. = on request

Further variants on request

**Approval**

FDA, ATEX, (EC Gas Appliance Directive 2009/142/EC)

**Control function/Circuit function**

B (normally open: NO)

**Process connection**

Further valve body connections

10.5. Ordering chart threaded connection

Valves with flow direction below seat

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Article no.	
DN	NPS				Seat seal	
			[mm]	[m³/h]	PTFE	Stainless steel
DIN EN ISO 228 - 1						
10	3/8	3	70 (M)	0.1	—	o. r.
		3	70 (M)	0.2	—	o. r.
		4	70 (M)	0.5	—	o. r.
		6	70 (M)	1.25	322059 ₪	350407 ₪
		8	70 (M)	2	215233 ₪	215242 ₪
		10	70 (M)	2.7	215235 ₪	215245 ₪
15	1/2	3	70 (M)	0.1	—	o. r.
		3	70 (M)	0.2	—	o. r.
		4	70 (M)	0.5	—	o. r.
		6	70 (M)	1.25	236138 ₪	354643 ₪
		8	70 (M)	2.1	212964 ₪	215243 ₪
		10	70 (M)	3.1	215236 ₪	215246 ₪
		15	70 (M)	4.3	206432 ₪	213955 ₪
20	3/4	10	70 (M)	3.2	215237 ₪	215247 ₪
		15	70 (M)	5.2	214067 ₪	215248 ₪
		20	70 (M)	7.1	206584 ₪	211239 ₪
25	1	15	70 (M)	5.3	206588 ₪	210460 ₪
		20	70 (M)	7.2	206586 ₪	210721 ₪
		25	70 (M)	12	189145 ₪	210485 ₪
			90 (N)	12	242203 ₪	242207 ₪
32	1 1/4	25	90 (N)	8.9	214070 ₪	210407 ₪
			130 (P)	13	222677 ₪	222687 ₪
		32	90 (N)	13.4	210097 ₪	210458 ₪
			130 (P)	17.8	223599 ₪	223600 ₪
40	1 1/2	32	90 (N)	14.4	214072 ₪	214084 ₪
			130 (P)	20.2	222679 ₪	222689 ₪
		40	90 (N)	17.5	210098 ₪	207800 ₪
			130 (P)	23.8	222681 ₪	222691 ₪
50	2	40	90 (N)	18	214074 ₪	214086 ₪
			130 (P)	24.6	222682 ₪	222692 ₪
		50	90 (N)	28	210099 ₪	203693 ₪
			130 (P)	37	214076 ₪	214088 ₪
65	2 1/2	50	130 (P)	45	214077 ₪	214089 ₪
		65	130 (P)	65	219621 ₪	219622 ₪

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Article no.	
DN	NPS				Seat seal	
			[mm]	[m³/h]	PTFE	Stainless steel
ISO 7-1 / DIN EN 10226-2						
10	3/8	3	70 (M)	0.1	—	o. r.
		3	70 (M)	0.2	—	o. r.
		4	70 (M)	0.5	—	o. r.
		6	70 (M)	1.25	o. r.	o. r.
		8	70 (M)	2	220418 ₪	220453 ₪
		10	70 (M)	2.7	220421 ₪	220457 ₪
15	1/2	3	70 (M)	0.1	—	o. r.
		3	70 (M)	0.2	—	o. r.
		4	70 (M)	0.5	—	o. r.
		6	70 (M)	1.25	o. r.	o. r.
		8	70 (M)	2.1	220881 ₪	220455 ₪
		10	70 (M)	3.1	220423 ₪	220459 ₪
20	3/4	15	70 (M)	4.3	220882 ₪	220886 ₪
		10	70 (M)	3.2	220425 ₪	220461 ₪
		15	70 (M)	5.2	220427 ₪	220463 ₪
25	1	20	70 (M)	7.1	220430 ₪	220466 ₪
		15	70 (M)	5.3	220428 ₪	220464 ₪
		20	70 (M)	7.2	220431 ₪	220467 ₪
		25	70 (M)	12	220434 ₪	220470 ₪
32	1 1/4	90 (N)	12	12	464864 ₪	464867 ₪
		25	90 (N)	8.9	220435 ₪	220471 ₪
		130 (P)	13	13	463921 ₪	463931 ₪
		32	90 (N)	13.4	220437 ₪	220473 ₪
40	1 1/2	130 (P)	17.8	17.8	463956 ₪	463957 ₪
		32	90 (N)	14.4	220438 ₪	463803 ₪
		130 (P)	20.2	20.2	463923 ₪	463933 ₪
		40	90 (N)	17.5	220440 ₪	220476 ₪
50	2	130 (P)	23.8	23.8	463925 ₪	463935 ₪
		40	90 (N)	18	220441 ₪	220477 ₪
		130 (P)	24.6	24.6	463926 ₪	463936 ₪
		50	90 (N)	28	220443 ₪	220479 ₪
65	2 1/2	130 (P)	37	37	220444 ₪	220480 ₪
		50	130 (P)	45	239536 ₪	239620 ₪
		65	130 (P)	65	239534 ₪	239571 ₪

o. r. = on request

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Article no. RC (ASME B 1.20.1)	
DN	NPS				Seat seal	
			[mm]	[m³/h]	PTFE	Stainless steel
ASME B 1.20.1						
10	3/8	3	70 (M)	0.1	–	o. r.
		3	70 (M)	0.2	–	o. r.
		4	70 (M)	0.5	–	o. r.
		6	70 (M)	1.25	o. r.	o. r.
		8	70 (M)	2	220484	220519
		10	70 (M)	2.7	220487	220523
15	1/2	3	70 (M)	0.1	–	o. r.
		3	70 (M)	0.2	–	o. r.
		4	70 (M)	0.5	–	o. r.
		6	70 (M)	1.25	359073	388407
		8	70 (M)	2.1	220888	220521
		10	70 (M)	3.1	220489	220525
20	3/4	15	70 (M)	4.3	220889	220894
		10	70 (M)	3.2	220491	220527
		15	70 (M)	5.2	220493	220529
25	1	20	70 (M)	7.1	220496	220532
		15	70 (M)	5.3	220494	220530
		20	70 (M)	7.2	220497	220533
		25	70 (M)	12	220500	220536
32	1 1/4	90 (N)	12	12	242377	242380
		25	90 (N)	8.9	220501	220537
		130 (P)	13	13	222740	222777
		32	90 (N)	13.4	220503	220539
40	1 1/2	130 (P)	17.8	17.8	223605	223606
		32	90 (N)	14.4	220504	220540
		130 (P)	20.2	20.2	222742	222763
		40	90 (N)	17.5	220506	220542
50	2	130 (P)	23.8	23.8	222765	222767
		40	90 (N)	18	220507	220543
		130 (P)	24.6	24.6	222768	222766
		50	90 (N)	28	220509	220545
65	2 1/2	130 (P)	37	37	220510	220546
		50	130 (P)	45	220511	220547
		65	130 (P)	65	220512	220548

o. r. = on request

Further variants on request



Approval

FDA, ATEX, (EC Gas Appliance Directive 2009/142/EC)



Control function/Circuit function

B (normally open: NO)



Process connection

Further valve body connections

10.6. Ordering chart welded connection

Valves with flow direction below seat

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Connection MW x TW	Article no.	
DN	NPS					Seat seal	
			[mm]	[m³/h]		PTFE	Stainless steel
DIN EN ISO 1127 - 1 / ISO 4200 / DIN 11866 series B							
10	3/8	3	70 (M)	0.1	17.2 × 1.6	–	o. r.
		3	70 (M)	0.2	17.2 × 1.6	–	o. r.
		4	70 (M)	0.5	17.2 × 1.6	–	o. r.
		6	70 (M)	1.25	17.2 × 1.6	232888 ₪	378908 ₪
		8	70 (M)	2	17.2 × 1.6	232891 ₪	315915 ₪
		10	70 (M)	2.7	17.2 × 1.6	o. r.	337061 ₪
15	1/2	3	70 (M)	0.1	21.3 × 1.6	–	o. r.
		3	70 (M)	0.2	21.3 × 1.6	–	o. r.
		4	70 (M)	0.5	21.3 × 1.6	–	o. r.
		6	70 (M)	1.25	21.3 × 1.6	288140 ₪	360750 ₪
		8	70 (M)	2.1	21.3 × 1.6	212392 ₪	216407 ₪
		10	70 (M)	3.1	21.3 × 1.6	212393 ₪	215873 ₪
		15	70 (M)	4.3	21.3 × 1.6	209571 ₪	216409 ₪
20	3/4	15	70 (M)	5.2	26.9 × 1.6	214094 ₪	214132 ₪
		20	70 (M)	7.1	26.9 × 1.6	214096 ₪	210696 ₪
25	1	20	70 (M)	7.2	33.7 × 2.0	214097 ₪	214135 ₪
		25	70 (M)	12	33.7 × 2.0	209572 ₪	214138 ₪
32	1 1/4	25	90 (N)	8.9	42.4 × 2.0	214101 ₪	214139 ₪
		32	90 (N)	13.4	42.4 × 2.0	214103 ₪	214141 ₪
40	1 1/2	32	90 (N)	14.4	48.3 × 2.0	214104 ₪	214142 ₪
			130 (P)	20.2	48.3 × 2.0	222700 ₪	222721 ₪
		40	90 (N)	17.5	48.3 × 2.0	209440 ₪	214144 ₪
			130 (P)	23.8	48.3 × 2.0	222702 ₪	222723 ₪
50	2	40	90 (N)	18	60.3 × 2.0	210756 ₪	213561 ₪
			130 (P)	24.6	60.3 × 2.0	222703 ₪	222724 ₪
		50	90 (N)	28	60.3 × 2.0	214107 ₪	214146 ₪
			130 (P)	37	60.3 × 2.0	214108 ₪	214147 ₪
65	2 1/2	65	130 (P)	65	76.1 × 2.3	219623 ₪	219626 ₪
			225 (L)	62	76.1 × 2.3	20060573 ₪	20060607 ₪
80	3	80	130 (P)	100	88.9 × 2.3	239543 ₪	239579 ₪
			225 (L)	100	88.9 × 2.3	20060574 ₪	20060608 ₪
100	4	100	130 (P)	140	114.3 × 2.6	239559 ₪	239595 ₪
			225 (L)	140	114.3 × 2.6	20060575 ₪	20060609 ₪

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Connection MW x TW	Article no.	
DN	NPS					Seat seal	
			[mm]	[m ³ /h]		PTFE	Stainless steel
DIN 11850 - 2 / DIN 11866 series A / DIN EN 10357 series A							
10	⅜	3	70 (M)	0.1	13.0 × 1.5	—	o. r.
		3	70 (M)	0.2	13.0 × 1.5	—	o. r.
		4	70 (M)	0.5	13.0 × 1.5	—	o. r.
		6	70 (M)	1.25	13.0 × 1.5	260632 ㉔	357231 ㉔
		8	70 (M)	2	13.0 × 1.5	300236 ㉔	284179 ㉔
		10	70 (M)	2.7	13.0 × 1.5	257412 ㉔	208553 ㉔
15	½	3	70 (M)	0.1	19.0 × 1.5	—	o. r.
		3	70 (M)	0.2	19.0 × 1.5	—	o. r.
		4	70 (M)	0.5	19.0 × 1.5	—	o. r.
		6	70 (M)	1.25	19.0 × 1.5	248881 ㉔	367704 ㉔
		8	70 (M)	2.1	19.0 × 1.5	215250 ㉔	215911 ㉔
		10	70 (M)	3.1	19.0 × 1.5	215251 ㉔	215913 ㉔
20	¾	15	70 (M)	4.3	19.0 × 1.5	215253 ㉔	209173 ㉔
		20	70 (M)	5.2	23.0 × 1.5	214113 ㉔	208555 ㉔
		20	70 (M)	7.1	23.0 × 1.5	211937 ㉔	211953 ㉔
25	1	20	70 (M)	7.2	29.0 × 1.5	214116 ㉔	214154 ㉔
		25	70 (M)	12	29.0 × 1.5	209384 ㉔	209089 ㉔
32	1¼	25	90 (N)	8.9	35.0 × 1.5	214119 ㉔	214156 ㉔
		32	90 (N)	13.4	35.0 × 1.5	211965 ㉔	209181 ㉔
40	1½	32	90 (N)	14.4	41.0 × 1.5	214121 ㉔	213487 ㉔
			130 (P)	20.2	41.0 × 1.5	222711 ㉔	222732 ㉔
		40	90 (N)	17.5	41.0 × 1.5	211967 ㉔	209110 ㉔
			130 (P)	23.8	41.0 × 1.5	222713 ㉔	222734 ㉔
50	2	40	90 (N)	18	53.0 × 1.5	214123 ㉔	213411 ㉔
			130 (P)	24.6	53.0 × 1.5	222714 ㉔	222735 ㉔
		50	90 (N)	28	53.0 × 1.5	211968 ㉔	209185 ㉔
			130 (P)	37	53.0 × 1.5	214125 ㉔	214159 ㉔
65	2½	65	130 (P)	65	70.0 × 2.0	219625 ㉔	219628 ㉔
			225 (L)	62	70.0 × 2.0	20060577 ㉔	20060610 ㉔
80	3	80	130 (P)	100	85.0 × 2.0	239544 ㉔	239580 ㉔
			225 (L)	100	85.0 × 2.0	20060578 ㉔	20060612 ㉔
100	4	100	130 (P)	140	104.0 × 2.0	239560 ㉔	239596 ㉔
			225 (L)	140	104.0 × 2.0	20060580 ㉔	20060613 ㉔

o. r. = on request

Nominal diameter (port connection)	Seat size	Actuator size Ø	K _{vs} value	Connection Ø DS x WS	Operating pressure	Article no.	
						Seat seal	
NPS		[mm]	[m³/h]			PTFE (VI)	Stainless steel (IV)
ASME BPE / DIN 11866 series C							
1/2	3	70 (M)	0.1	12.7 × 1.65	25 (IV)	–	o. r.
	3	70 (M)	0.2	12.7 × 1.65	–	–	o. r.
	4	70 (M)	0.5	12.7 × 1.65	25 (IV)	–	o. r.
	6	70 (M)	1.25	12.7 × 1.65	25 (IV)	226651 ⅈ	20001538 ⅈ
	8	70 (M)	2	12.7 × 1.65	25 (IV)	379940 ⅈ	216879 ⅈ
	10	70 (M)	2.7	12.7 × 1.65	25 (IV)	225463 ⅈ	313806 ⅈ
3/4	10	70 (M)	3.1	19.05 × 1.65	25 (IV)	241143 ⅈ	o. r.
	15	70 (M)	4.3	19.05 × 1.65	25 (IV)	335739 ⅈ	335741 ⅈ
1	10	70 (M)	3.2	25.4 × 1.65	25 (IV)	241633 ⅈ	242576 ⅈ
	15	70 (M)	5.2	25.4 × 1.65	25 (IV)	226329 ⅈ	242579 ⅈ
	20	70 (M)	7.1	25.4 × 1.65	16 (IV)	230405 ⅈ	216902 ⅈ
1 1/2	32	90 (N)	13.4	38.1 × 1.65	16 (IV)	230409 ⅈ	242587 ⅈ
		130 (P)	17.8	38.1 × 1.65	25 (IV)	242557 ⅈ	242589 ⅈ
2	40	90 (N)	17.5	50.8 × 1.65	12 (IV)	211655 ⅈ	242592 ⅈ
		130 (P)	23.8	50.8 × 1.65	25 (IV)	242561 ⅈ	242593 ⅈ
2 1/2	50	130 (P)	37	63.5 × 1.65	25 (20 ¹⁾) (IV)	335735 ⅈ	335737 ⅈ
3	65	130 (P)	65	76.2 × 1.65	16 (15 ¹⁾) (IV)	268682 ⅈ	350667 ⅈ
		225 (L)	62	76.2 × 1.65	–	20060581 ⅈ	20060615 ⅈ
4	80	130 (P)	110	101.6 × 2.11	10 (IV)	298386 ⅈ	o. r.
		225 (L)	115	101.6 × 2.11	–	20060582 ⅈ	20060616 ⅈ
	100	130 (P)	140	101.6 × 2.11	6 (IV)	275103 ⅈ	289251 ⅈ
		225 (L)	140	101.6 × 2.11	–	20060583 ⅈ	20060617 ⅈ

o. r. = on request

1.) According to the Pressure Equipment Directive 97/23/EC for compressible fluids of Group 1 (hazardous gases and vapours according to Article 3 No. 1.3 letter a first dash)

Further variants on request

**Approval**

FDA, ATEX, (EC Gas Appliance Directive 2009/142/EC)

**Control function/Circuit function**

B (normally open: NO)

**Process connection**

Further valve body connections

10.7. Ordering chart clamp connection

Valves with flow direction below seat

Nominal diameter (port connection)		Seat size	Actuator size Ø	K _{vs} value	Connection MC x TC, CC	Article no.	
DN	NPS					Seat seal	
			[mm]	[m³/h]		PTFE	Stainless steel
DIN 32676 series A							
15	½	15	70 (M)	4.3	19 × 1.5. 34	222593 	282208 
20	¾	20	70 (M)	7.1	23 × 1.5. 34	225647 	282209 
25	1	25	90 (N)	12.0	29 × 1.5. 50.5	222594 	282210 
32	1¼	32	90 (N)	13.4	35 × 1.5. 50.5	240415 	282211 
40	1½	40	130 (P)	23.8	41 × 1.5. 50.5	240351 	282212 
50	2	50	130 (P)	37.0	53 × 1.5. 64	282258 	282259 
DIN 32676 series B							
15	½	15	70 (M)	4.3	21.3 × 1.6. 50.5	273974 	282213 
20	¾	20	70 (M)	7.1	26.9 × 1.6. 50.5	209438 	282214 
25	1	25	90 (N)	12.0	33.7 × 2.0. 50.5	241115 	282215 
40	1½	40	130 (P)	23.8	48.3 × 2.0. 64.0	209880 	284181 
50	2	50	130 (P)	37.0	60.3 × 2.0. 77.5	282261 	282263 

Further variants on request



Approval

FDA, ATEX, (EC Gas Appliance Directive 2009/142/EC)



Control function/Circuit function

B (normally open: NO)



Process connection

Further valve body connections