

Plunger valve 3/2-way direct-acting

- Direct-acting, compact valve with diameter of up to DN 2.5
- Vibration-proof, bolted coil system
- Banjo threaded connection for direct mounting on pneumatic valves
- Explosion proof variants
- Energy-saving variants with Kick and Drop available

Product variants described in the data sheet may differ from the product presentation and description.

Can be combined with



Type 2518
Cable plug, form A according to DIN EN 175301-803



Type 1087
Timer,
form A according to DIN EN 175301-803



Type 2509
Cable plug,
form A according to DIN EN 175301-803

Type description

Valve 6014 is a direct-acting plunger valve. The stopper and core guide tube are welded together to enhance pressure resistance and leak-tightness. Various seal material combinations are available depending on the application. A Bürkert-specific flange variant (SFB) enables space-saving arrangement of valves on a manifold. Kick and Drop coils are available for the reduction of electrical power consumption during operation.

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

© Christian Bürkert GmbH & Co. KG, Subject to alteration

Visit product website

valvesgo.com

Table of contents

1. General technical data 4

2. Circuit functions 5

3. Approvals and conformities 5

3.1. General notes ... 5
3.2. Conformity ... 5
3.3. Standards ... 5
3.4. Explosion protection ... 6
3.5. North America (USA/Canada) ... 6
3.6. Drinking water ... 7
3.7. Foods and beverages/Hygiene ... 7
3.8. Others ... 7
DNV GL classification ... 7
Fire protection on railway vehicles ... 8

4. Materials 8

4.1. Bürkert resistApp ... 8
4.2. Material specifications ... 8
Standard variant ... 8
Banjo variant ... 9
ATEX/IECEx m cable variant ... 9
ATEX/IECEx m terminal box variant ... 10

5. Dimensions 11

5.1. Standard variant ... 11
Pin assignment ... 12
5.2. Banjo variant ... 12
With 76 mm banjo bolt ... 12
With 60 mm banjo bolt ... 13
5.3. ATEX/IECEx m cable variant ... 14
5.4. ATEX/IECEx m terminal box variant ... 15
5.5. ATEX/IECEx ia variant ... 16
5.6. Single manifold ... 17
5.7. Multiple manifold ... 17
5.8. Manifolds for block mounting ... 18

6. Performance specifications 18

6.1. Power consumption ... 18
6.2. Utilisation in another circuit function ... 18
6.3. Electrical data explosion-proof variant EEx ia ... 19

7. Product installation 19

7.1. Installation notes ... 19
Control for impulse variant with polarity reversal control ... 19

8. Product accessories 20

8.1. Cable glands for ATEX/IECEx terminal box ... 20
8.2. Special tool to turn the terminal box ... 20

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

valvesgo.com

9. Ordering information **21**

9.1. Bürkert eShop 21
9.2. Bürkert product filter 21
9.3. Bürkert Product Enquiry Form 21
9.4. Ordering chart 22
Standard variant 22
Banjo variant 24
ATEX/IECEx m cable variant 25
ATEX/IECEx m terminal box variant 26
ATEX/IECEx ia variant 27
9.5. Ordering chart accessories 27
Single manifold 27
Multiple manifold 27
Cable plug Type 2518, form A according to DIN EN 175301 - 803 27
Cable plug Type 2509, form A according to DIN EN 175301 - 803 28
Cable glands for ATEX/IECEX terminal box 28

valvesgo.com

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com




DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

1. General technical data

Product properties	
Dimensions	Further information can be found in chapter "5. Dimensions" on page 11.
Material	
Seal	FKM (EPDM on request)
Body	Brass, stainless steel 1.4305/303, polyamide (sub-base)
Coil	Polyamide (epoxy on request)
Manual override	This is an "emergency manual override" which allows manual operation in the event of a fault. (Leakage possible)
Orifice	DN 1.5...DN 2.5
Circuit function	C, D and T Further information can be found in chapter "2. Circuit functions" on page 5.
Thermal insulation class of solenoid coil	Polyamide coil class B Epoxy coil class H
Performance data	
Duty cycle/single valve with block assembly	100 % continuous operation Intermittent operation 60 % (30 min) or with 5 W coil (on request)
Electrical data	
Operating voltage	24 V DC, 24 V 50 Hz, 24 V 60 Hz, 110 V 50 Hz, 120 V 60 Hz, 230 V 50 Hz, 240 V 60 Hz (other voltages on request)
Power consumption	Further information can be found in chapter "6.1. Power consumption" on page 18.
Voltage tolerance	± 10 %
Medium data	
Operating medium	Technical vacuum, neutral gases and liquids (e.g. compressed air, town gas, natural gas, water, hydraulic oil, petrol)
Medium temperature	
With FKM	- 10 °C...+ 100 °C (PA coil), - 10 °C...+ 120 °C (epoxy coil), - 40 °C on request
With PTFE/Graphite	- 40 °C...+ 180 °C (further information can be found in chapter "4.1. Bürkert resistApp" on page 8)
With FKM, circuit function B	- 10 °C...+ 100 °C (AC), - 10 °C...+ 120 °C (DC)
Viscosity	Max. 21 mm^2/s
Product connections	
Electrical connection	• Plug contacts according to DIN EN 175 301 - 803 form A for cable plug **Type 2518** ▶. Further information can be found in chapter "Cable plug Type 2518, form A according to DIN EN 175301 - 803" on page 27. • Plug contacts according to DIN EN 175 301 - 803 form A for cable plug **Type 2509** ▶. Further information can be found in chapter "Cable plug Type 2509, form A according to DIN EN 175301 - 803" on page 28. • ATEX/IECEx variant with 3 m moulded cable or terminal box
Port connection	G ⅛, G ¼, NPT ⅛, NPT ¼, sub-base (SFB)
Approvals and conformities	
Degree of protection	IP65 with cable plug **Type 2518** ▶ NEMA 4X with cable plug **Type 2509** ▶ with stainless steel variants
Explosion protection	Further information can be found in chapter "3.4. Explosion protection" on page 6.
North America (USA/Canada)	Further information can be found in chapter "3.5. North America (USA/Canada)" on page 6.
Drinking water	Further information can be found in chapter "3.5. North America (USA/Canada)" on page 6.
Foods and beverages/Hygiene	Further information can be found in chapter "3.7. Foods and beverages/Hygiene" on page 7.
Others	Further information can be found in chapter "3.8. Others" on page 7.
Environment and installation	
Installation position	As required, preferably with actuator upright
Ambient temperature	Max. + 55 °C

valvesgo.com

2. Circuit functions

Symbol	Description
	**Circuit function C (CF C)** 3/2-way solenoid valve Direct-acting Normally closed
	**Circuit function D (CF D)** 3/2-way solenoid valve Direct-acting Normally open
	**Circuit function T (CF T)** 3/2-way solenoid valve Direct-acting Flow direction optional Normally closed

3. Approvals and conformities

3.1. General notes

- The approvals and conformities listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available variants can be supplied with the below mentioned approvals or conformities.

3.2. Conformity

In accordance with the Declaration of Conformity, the product is compliant with the EU Directives.

3.3. Standards

The applied standards which are used to demonstrate compliance with the EU Directives are listed in the EU-Type Examination Certificate and/or the EU Declaration of Conformity.

Valvesgo.com

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

3.4. Explosion protection

Approval	Description
	Optional: Explosion protection according to category 2 (zone 1/21) Ex marking of the components according to the following table:

Coil Type AC10	
Coils with cable outlet	**Coils with terminal box**
ATEX: EPS 18 ATEX 1232 X II 2G Ex mb IIC T4 Gb II 2D Ex mb IIIC T130 °C Db **IECEx:** IECEx EPS 18.0110 X Ex mb IIC T4 Gb Ex mb IIIC T130 °C Db	**ATEX:** EPS 18 ATEX 1232 X II 2G Ex eb mb IIC T4 Gb II 2D Ex mb tb IIIC T130 °C Db **IECEx:** IECEx EPS 18.0110 X Ex eb mb IIC T4 Gb Ex mb tb IIIC T130 °C Db

Coil Type AC10 (Ex-i variant)
ATEX: EPS 18 ATEX 1 088 X II 2G Ex ia IIC T6/T4 Gb II 2D Ex ia IIIC T135 °C Db **IECEx:** IECEx EPS 18.0038 X Ex ia IIC T6/T4 Gb Ex ia IIIC T135 °C Db

Optional: Explosion protection according to category 3 (zone 2/22)

Ex marking of the components according to the following table:

Coil Type AC10
Coil with plug contacts form A and cable plug Type 2509
ATEX: EPS 21 ATEX 1234 X II 3G Ex ec IIC T4 Gc II 3D Ex tc IIIC T135 °C Dc **IECEx:** IECEx EPS 21.0078X Ex ec IIC T4 Gc Ex tc IIIC T135 °C Dc

3.5. North America (USA/Canada)

Approval	Description
LISTED	**Optional: UL Listed for the USA (valid for valves)** The valves are UL Listed for the USA according to: • UL 429 (electrically operated valves)
c UL us LISTED SOLENOID FOR USE IN HAZARDOUS LOCATIONS E504714	**Optional: UL Hazardous Locations – Explosion Protection (valid for coils)** UL Listed for Hazardous Locations for USA and Canada Class I, Zone 1 Class I, Division 2, Group A, B, C and D Class II + III, Division 2, Group F and G

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

Approval	Description
	Optional: UL Recognized for the USA (valid for valves) The valves are UL Recognized for the USA according to: • UL 429 (electrically operated valves)
	Optional: CSA for Canada (valid for valves) The valves are CSA approved for Canada according to: • CSA 139 (electrically operated valves)
	Optional: FM (Factory Mutual) – Explosion Protection (valid for coils) FM for Hazardous Locations for USA and Canada Class I, Zone 1 Class I, Division 1, Groups A, B, C and D Class II + III, Division 1, Groups E, F and G
CRN	**Canadian Registration Number (CRN) – Technical Standards and Safety Act, Boilers and Pressure Vessels Regulation, and CSA Standard B51** The product fittings comply with all of the requirements of ASME Section B31.3 (Process Piping). Registration number Canada: 0C2430.C R2

3.6. Drinking water

Conformity	Description
H_2O	**Suitable for use in drinking water applications** The materials comply with the assessment principles (UBA) for materials in contact with drinking water (TrinkwasserV). **Brass body/Stainless steel body:** PF39: Suitable for products with a maximum temperature of + 85 °C (hot water)

3.7. Foods and beverages/Hygiene

Conformity	Description
FDA	**FDA – Code of Federal Regulations (valid for the variable code PL02, PL03)** All wetted materials are compliant with the Code of Federal Regulations published by the FDA (Food and Drug Administration, USA) according to the manufacturer's declaration.
USP	**United States Pharmacopeial Convention (USP) (valid for the variable code PL04)** All wetted materials are biocompatible according to the manufacturer's declaration.
	EC Regulation 1935/2004 of the European Parliament and of the Council (valid for the variable code PL01, PL02) All wetted materials are compliant with EC Regulation 1935/2004/EC according to the manufacturer's declaration.

3.8. Others

DNV GL classification

Approval	Description
	DNV GL classification – Ships, offshore units, and high speed and light craft The products are accepted for installation on all vessels classed by DNV GL.

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026


valvesgo.com

Fire protection on railway vehicles

Approval	Description
DIN EN 45545	**Optional: Fire protection on railway vehicles in accordance with DIN EN 45545 applicable parts 2 and 5: requirements for fire behaviour of materials and components** The products comply with the fire protection requirements in accordance with applicable parts 2 and 5 of DIN EN 45545 for use in the interior of railway vehicles for operating classes 1 - 3 (OC1 - 3) in conjunction with hazard levels 1 - 2 (HL1 - 2) in accordance with the manufacturer's declaration.

4. Materials

4.1. Bürkert resistApp




Bürkert resistApp – Chemical resistance chart

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.

Start chemical resistance check

4.2. Material specifications

Standard variant




No.	Element	Material
1	Stopper	Stainless steel 1.4105/430F
2	Shading ring	Cu (brass variant) Ag (stainless steel variant)
3	Plunger seal	FKM
4	Spring	Stainless steel 1.4310/301
5	Magnetic core	Stainless steel 1.4105/430F
6	Core guide tube	Stainless steel 1.4303/305/308
7	O-ring	FKM
8	Plunger seal	FKM
9	Valve body	Brass Stainless steel 1.4305/303 Stainless steel 1.4401/316
10	Spring	Stainless steel 1.4310/301
11	Sub-base	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4301/304 (stainless steel variant)
12	Coil	PA (Polyamide) Epoxy (High temperature variant)
13	Nut	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4305/303 PTFE coated (stainless steel variant)

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026


valvesgo.com

Banjo variant



No.	Element	Material
1	Nut	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4305/303 PTFE coated (stainless steel variant)
2	Coil	PA (Polyamide) Epoxy (High temperature variant)
3	Stopper	Stainless steel 1.4105/430F
4	Shading ring	Cu (brass variant) Ag (stainless steel variant)
5	Core guide tube	Stainless steel 1.4303/305/308
6	Magnetic core	Stainless steel 1.4105/430F
7	Spring	Stainless steel 1.4310/301
8	Sub-base	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4301/304 (stainless steel variant)
9	Plunger seal	FKM
10	O-ring	FKM
11	Valve body	PPS
12	Pressure connection P	–
13	Screw	Brass/Stainless steel 1.4301/304
14	O-ring	FKM
15	Pressure connection A	–
16	R connection	–

ATEX/IECEx m cable variant




No.	Element	Material
1	Stopper	Stainless steel 1.4105/430F
2	Nut	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4305/303 PTFE coated (stainless steel variant)
3	Shading ring	Cu (brass variant) Ag (stainless steel variant)
4	Plunger seal	FKM
5	Spring	Stainless steel 1.4310/301
6	Magnetic core	Stainless steel 1.4105/430F
7	Core guide tube	Stainless steel 1.4303/305/308
8	O-ring	FKM
9	Plunger seal	FKM
10	Valve body	Brass Stainless steel 1.4305/303 Stainless steel 1.4401/316
11	Spring	Stainless steel 1.4310/301
12	Sub-base	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4301/304 (stainless steel variant)
13	Coil	Epoxy

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

ATEX/IECEx m terminal box variant



No.	Element	Material
1	Nut	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4305/303 PTFE coated (stainless steel variant)
2	Stopper	Stainless steel 1.4105/430F
3	Coil	Epoxy
4	Shading ring	Cu (brass variant) Ag (stainless steel variant)
5	Plunger seal	FKM
6	Spring	Stainless steel 1.4310/301
7	Magnetic core	Stainless steel 1.4105/430F
8	Core guide tube	Stainless steel 1.4303/305/308
9	O-ring	FKM
10	Plunger seal	FKM
11	Valve body	Brass Stainless steel 1.4305/303 (G ⅛) Stainless steel 1.4401/316 (G ¼)
12	Spring	Stainless steel 1.4310/301
13	Sub-base	Steel, surface finish thick-film passivated (brass variant) Stainless steel 1.4301/304 (stainless steel variant)
14	Terminal box	Aluminium


DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

5. Dimensions

5.1. Standard variant

Note:
Dimensions in mm



Port connection	A	B	C	D	G
	[inch]	[mm]	[mm]	[mm]	[mm]
Threaded without manual override	G ⅛	32	20.8	32.6	8
	G ¼	46	26.8	49	12
Threaded with manual override	G ⅛	32	20.8	32.6	8
	G ¼	46	26.8	49	12
Sub-base	–	32	14.3	32.6	–

Coil size	E	F
	[mm]	[mm]
5	32	45
6	40	51

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

Pin assignment


For the positions marked with *, ** or *** in the drawing, the connections are marked with the letters shown in the table above, depending on the circuit function. Unused circuit functions A or B connections will be closed off with a blanking plug or cap nut.

Circuit function	Connection Type		
	*	**	***
A	P	blank off	A
B	blank off	B	P
C	P	R	A
D	R	P	B
T	P	R	A

5.2. Banjo variant

With 76 mm banjo bolt

Note:
Dimensions in mm



Variant	A	P	G
	[inch]	[inch]	[mm]
BJ02	G ¼	G ¼	10
BJ03	G ⅛	NPT ¼	
BJ04	G ¼	NPT ¼	
BJ05	G ⅛	G ¼	
BJ07	G ⅛	NPT ⅛	


Coil size	E	F
	[mm]	[mm]
5	32	45
6	40	51

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

With 60 mm banjo bolt

Note:
Dimensions in mm



Variant	A	P
	[inch]	[inch]
BJ01	G ⅛	G ⅛
BJ06	G ¼	G ⅛

Coil size	E	F
	[mm]	[mm]
5	32	45
6	40	51


valvesgo.com

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

5.3. ATEX/IECEx m cable variant

Note:
Dimensions in mm



Port connection	A	B	C	D	G
	[inch]	[mm]	[mm]	[mm]	[mm]
Threaded variant	G ⅛	32	20.8	32.6	8
	G ¼	46	26.8	49	12
Sub-base variant	–	32	14.3	32.6	–

Coil size	E	F
	[mm]	[mm]
5	32	46
6	40	52


DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

5.4. ATEX/IECEx m terminal box variant

Note:
Dimensions in mm

Threaded version G1/8 + G1/4



Port connection	A	B	C	D	G
	[inch]	[mm]	[mm]	[mm]	[mm]
Threaded variant	G ⅛	32	20.8	32.6	8
	G ¼	46	26.8	49	12
Sub-base variant	–	32	14.3	32.6	–

Coil size	E	F
	[mm]	[mm]
5	32	44
6	40	51


DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

5.5. ATEX/IECEx ia variant

Note:

- Dimensions in mm
- Further information about electrical data can be found in chapter "6.3. Electrical data explosion-proof variant EEx ia" on page 19.




valvesgo.com

valvesgo.com

5.6. Single manifold

Note:


- Dimensions in mm
- Further information about the installation of manifolds can be found in chapter "5.8. Manifolds for block mounting" on page 18.



5.7. Multiple manifold

Note:

- Dimensions in mm
- The manifold is only possible with coil size 5.
- Brass or stainless steel manifolds is available on request.



Accessory parts	Number of valve positions	Hole spacing A		Total length B		Hole spacing C		Article no.
		[mm]	[inch]	[mm]	[inch]	[mm]	[inch]	
Multiple manifold (aluminium)	2	57	2.24	65	2.56	–	–	005023
	3	90	3.54	98	3.86	–	–	005286
	4	123	4.84	131	5.16	–	–	005287
	5	156	6.14	164	6.46	57	2.24	005035
	6	189	7.44	197	7.76	57	2.24	005038
	8	255	10	263	10.35	90	3.54	005386
	10	321	12.64	329	12.95	90	3.54	005764
Single manifold (aluminium)								005020
Plug nipple with O-rings for connecting manifolds								005040
Covering plate with screws and O-ring for closing off unused valve positions								005630

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

5.8. Manifolds for block mounting

Note:

- Close open ports for valves that are not required with cover plates (see accessories).
- Fasten the manifolds to a standard rail.
- Refer to chapter "5.7. Multiple manifold" on page 17 for more information about the dimensions.

With manifold mounting, please comply with the permissible duty cycle (5 W variants with 100 % continuous rating or 8 W variant with 60 % duty cycle). The pressure port for the manifold is designated with P (R), and the outlet port with A (B). Only connect together ports with the same designation.

2/2-way valves of Type 6013 can be operated together on a manifold with 3/2-way valves of Type 6014, circuit function C (not D or T!) if the operating pressures matches according to the rating plates. The manifolds can also be expanded if the valve functions are taken into consideration. Connector nipples with O-rings are used to connect the P (R) ports.

6. Performance specifications

6.1. Power consumption

Orifice	Coil power	Power consumption		Response times [1.)]	
		Inrush AC	Hold AC	Opening	Closing
[mm]	[W]	[VA]	[VA/W]	[ms]	[ms]
1.5	8 W AC or 8 W DC (9)	24	8	10...15	15...20
2.0	8 W AC or 8 W DC (9)			10...15	15...20
2.5	8 W AC or 8 W DC (9)			15...20	10...22

1.) Measurement at + 20 °C, 6 bar at the valve outlet, opening: pressure build-up 0...90 %, closing: pressure reduction 100...10 %

6.2. Utilisation in another circuit function

The valves are equipped with different springs for specific circuit functions. When used with other circuit functions, the permissible operating pressure changes according to the following table.

Standard variant		Max. operating pressure [bar] for valve application in circuit function				
DN	Circuit function	A	B	C	D	T
1.5	C	16	22	16	2	2
	D	2	2.5	2	16	2
	T	10	16	10	6	6
2.0	C	10	14	10	1	1
	D	1	1.5	1	10	1
	T	6	10	6	4	4
2.5	C	6	9	6	0.7	0.7
	D	0.7	1	0.7	6	0.7
	T	3.5	6	3.5	2.5	2.5


DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

6.3. Electrical data explosion-proof variant EEx ia

Note:

- The valve is intended for operation at 24 V/DC outputs via the intermedia switching of a corresponding intrinsically safe operating resource (isolating module or barrier).
-
- Ignition protection class: EEx ia IIC T6 according to PTB-No. Ex- 96.D.2010
- Further information can be found in the **operating instructions EPS 18 ATEX 1088X ▶**.



7. Product installation


7.1. Installation notes

Control for impulse variant with polarity reversal control


Note:

- Please use only the cable plug without electrical wiring for the impulse variant.
- Pulse duration at least 50 ms

Polarity (is marked on the coil with a label)	**Features**	**Terminal connections**
– switch ON +	valve open	(+) on terminal 2 and (–) on terminal 1 (see below)
+ switch OFF –	valve closed	(+) on terminal 1 and (–) on terminal 2 (see below)



Polarity is marked on the coil with a label:
- switch ON +
+ switch OFF -





DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

8. Product accessories

8.1. Cable glands for ATEX/IECEx terminal box

Note:
A polyamide cable gland is included in the scope of delivery. A nickel-plated brass variant can be ordered for a surcharge, see "Cable glands for ATEX/IECEX terminal box" on page 28.

Description	Ex approval		Dimensions	
	Certification	Identification		
Ex cable gland, nickel-plated brass, 6...13 mm 	PTB 04 ATEX 1112 X, IECEx PTB 13.0027X	II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db IP68		TL 29...37 mm L 6 mm D 20 mm SW 24 mm E 27 mm
Ex cable gland, polyamide, 7...13 mm 	PTB 13 ATEX 1015 X, IECEx PTB 13.0034X	II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db IP68		TL 36...45 mm L 10 mm D 20 mm SW 24 mm E 28 mm

8.2. Special tool to turn the terminal box

Note:
This special tool is not included in the scope of delivery of the valve, see "Cable glands for ATEX/IECEX terminal box" on page 28.

Description	Components of the set
Set SC02-AC10 	• Special tool • Service manual

valvesgo.com

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

9. Ordering information

9.1. Bürkert eShop



Bürkert eShop – Easy ordering and quick delivery

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

Order online now

9.2. Bürkert product filter




Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements?
Use the Bürkert product filter and find suitable articles for your application quickly and easily.

Try out our product filter

9.3. Bürkert Product Enquiry Form

Note:
Please see our Product Enquiry Form for a full explanation of our specification key.



Bürkert Product Enquiry Form – Your enquiry quickly and compactly

Would you like to make a specific product enquiry based on your technical requirements? Use our Product Enquiry Form for this purpose. There you will find all the relevant information for your Bürkert contact. This will enable us to provide you with the best possible advice.

Fill out the form now







DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

9.4. Ordering chart

Standard variant


Note:
Please note that the cable plug has to be ordered separately, see "9.5. Ordering chart accessories" on page 27 or separate datasheet **Type 2518**.

Circuit function	Port connection	Orifice	K_V value water [1.]	Coil power	Pressure range [2.]	Article no.		
						024/DC	024/50	230/50
		[mm]	[m³/h]	[W]	[bar]	[V/Hz]	[V/Hz]	[V/Hz]
Threaded variant with FKM seal, (class B)								
Brass body								
CF C 3/2-way solenoid valve Direct-acting Normally closed 	G ⅛	1.5	0.07	8	0...16	125329	125331	125332
	G ⅛	2.0	0.11	8	0...10	125333	125334	125336
	G ¼		0.11	8	0...10	125348	126138	126140
	G ⅛	2.5	0.16	8	0...6	125341	125340	125342
	G ¼		0.16	8	0...6	126142	126143	126145
CF D 3/2-way solenoid valve Direct-acting Normally open 	G ⅛	1.5	0.07	8	0...16	126195	126196	125355
	G ⅛	2.0	0.11	8	0...10	125357	125358	125360
	G ¼		0.11	8	0...10	126198	126199	126201
	G ⅛	2.5	0.16	8	0...6	125363	126202	126204
	G ¼		0.16	8	0...6	126205	126206	126208
CF T 3/2-way solenoid valve Direct-acting Flow direction optional Normally closed 	G ⅛	1.5	0.07	8	0...7	126150	126151	126153
With manual override								
CF C 3/2-way solenoid valve Direct-acting Normally closed 	G ⅛	2.0	0.11	8	0...10	125337	125338	125339
	G ¼		0.11	8	0...10	125349	126147	126149
CF D 3/2-way solenoid valve Direct-acting Normally open 	G ⅛	2.0	0.11	8	0...10	126209	125361	126211
	G ¼		0.11	8	0...10	126212	126213	126215
Stainless steel body								
CF C 3/2-way solenoid valve Direct-acting Normally closed 	G ⅛	1.5	0.07	8	0...16	126216	126217	126219
	G ⅛	2.0	0.11	8	0...10	126220	126221	126223
	G ¼	2.0	0.11	8	0...10	126224	126225	126227

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026





valvesgo.com

valvesgo.com

Circuit function	Port connection	Orifice	K_V value water [1.]	Coil power	Pressure range [2.]	Article no.		
						024/DC	024/50	230/50
		[mm]	[m³/h]	[W]	[bar]	[V/Hz]	[V/Hz]	[V/Hz]
CF T 3/2-way solenoid valve Direct-acting Flow direction optional Normally closed 	G ⅛	1.5	0.07	8	0...7	126228	126229	126231


1.) Measurement at + 20 °C, 1 bar [2.] at the valve inlet and free outlet
2.) Pressure data: overpressure to atmospheric pressure

Note:
Please note that the cable plug must be ordered separately, see "9.5. Ordering chart accessories" on page 27 or separate datasheet **Type 2518** ▸.


Circuit function	Orifice	K_V value water [1.]	Coil power	Pressure range [2.]	Article no.		
					024/DC	024/50	230/50
	[mm]	[m³/h]	[W]	[bar]	[V/Hz]	[V/Hz]	[V/Hz]
Sub-base body (SFB) with FKM seal (class B)							
Brass body							
CF C 3/2-way solenoid valve Direct-acting Normally closed 	1.5	0.07	8	0...16	126154	126155	125366
	2.0	0.11	8	0...10	125367	125368	125370
CF D 3/2-way solenoid valve Direct-acting Normally open 	2.0	0.11	8	0...10	126161	126162	125383
With manual override							
CF C 3/2-way solenoid valve Direct-acting Normally closed 	1.5	0.07	5	0...10	126403	126404	126406
	1.5	0.07	8	0...16	126157	126158	126160
	2.0	0.11	5	0...6	126407	126408	126410
	2.0	0.11	8	0...10	125371	125372	125374
Polyamide body							
CF C 3/2-way solenoid valve Direct-acting Normally closed 	1.5	0.07	5	0...10	126390	126391	126393

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

Circuit function	Orifice	K_V value water [1.]	Coil power	Pressure range [2.]	Article no.		
					024/DC	024/50	230/50
	[mm]	[m³/h]	[W]	[bar]	[V/Hz]	[V/Hz]	[V/Hz]
With manual override							
CF C 3/2-way solenoid valve Direct-acting Normally closed 	1.5	0.07	5	0...10	126396	126397	126399

1.) Measurement at + 20 °C, 1 bar [2.] at the valve inlet and free outlet
2.) Pressure data: overpressure to atmospheric pressure


Circuit function	Port connection		Orifice	K_V value water [1.]	Power consumption DC (warm/cold coil)	Pressure range [2.]	Article no.	
							012/DC	024/DC
			[mm]	[m³/h]	[W]	[bar]	[V/Hz]	[V/Hz]
Impulse variant with FKM seal and brass body (class H)								
CF C 3/2-way solenoid valve Direct-acting Normally closed 	Threaded port	G ⅛	1.5	0.07	7	0...16	209280	209284
			2.0	0.11	7	0...10	209281	209285
	Sub-base (SFB)	Sub-base (SFB)	1.5	0.07	7	0...16	209278	209282
			2.0	0.11	7	0...10	209279	209283

1.) Measurement at + 20 °C, 1 bar [2.] at the valve inlet and free outlet
2.) Pressure data: overpressure to atmospheric pressure

Banjo variant

Note:

- Please note that the cable plug must be ordered separately, see "9.5. Ordering chart accessories" on page 27 or separate data sheet **Type 2518** ▶.
- Stainless steel hollow screws are available on request.

Circuit function	Variant	Pressure port P	Working port A (banjo bolt)	banjo bolt	Q_{Nn} value air	Power consumption	Pressure range	Material banjo bolt	Article no.		
									024/DC	024/50	230/50
				[mm]	[l/min]	[W]	[bar]		[V/Hz]	[V/Hz]	[V/Hz]
With FKM seal and manual override											
CF C 3/2-way solenoid valve Direct-acting Normally closed 	BJ01	G ⅛	G ⅛	1,5	75	8	0...16	Brass	20098150	389539	389541
	BJ01	G ⅛	G ⅛	2,0	120	8	0...10	Brass	20098151	389545	389547
	BJ02	G ¼	G ¼	1,5	75	8	0...16	Brass	334869	389542	389543
	BJ02	G ¼	G ¼	2,0	120	8	0...10	Brass	334870	389548	389550
	BJ03	NPT ¼	G ⅛	1,5	75	8	0...16	Brass	o. r.	o. r.	o. r.
	BJ03	NPT ¼	G ⅛	2,0	120	8	0...10	Brass	o. r.	o. r.	o. r.
	BJ04	NPT ¼	G ¼	1,5	75	8	0...16	Brass	o. r.	o. r.	o. r.
	BJ04	NPT ¼	G ¼	2,0	120	8	0...10	Brass	o. r.	o. r.	o. r.
	BJ05	G ¼	G ⅛	1,5	75	8	0...16	Brass	20058931	o. r.	o. r.
	BJ05	G ¼	G ⅛	2,0	120	8	0...10	Brass	20034151	o. r.	o. r.
	BJ06	G ⅛	G ¼	1,5	75	8	0...16	Brass	o. r.	o. r.	o. r.
	BJ06	G ⅛	G ¼	2,0	120	8	0...10	Brass	o. r.	20051143	20043155
	BJ07	NPT ⅛	G ⅛	1,5	75	8	0...16	Brass	o. r.	o. r.	o. r.
	BJ07	NPT ⅛	G ⅛	2,0	120	8	0...10	Brass	o. r.	o. r.	o. r.


o. r. = on request



DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

ATEX/IECEx m cable variant

Note:
The maximum medium temperature must never exceed the permitted temperature class (T4: + 135 °C, T5: + 100 °C, T6: + 85 °C) minus 5 K.

Circuit function	Port connection	Orifice [mm]	K_v value water [m³/h]	Voltage/ frequency [V/Hz]	Coil power [W]	Pressure range [bar]	Body material	Article no. with manual override
Ex m II T4, with FKM seal and sub-base (SFB) connection with 3 m moulded cable, approved for block mounting, ambient temperature from - 10 °C...+ 40 °C								
CF C 3/2-way solenoid valve Direct-acting Normally closed 	Sub-base (SFB)	1.5	0.07	024/UC	7	0...10	PA	364568
				230/UC				352017
				024/UC	7		Brass	351967
				230/UC				364570
	Sub-base (SFB)	2.0	0.11	024/UC	7	0...6	Brass	351981
				230/UC				351990

Circuit function	Port connection	Orifice [mm]	K_v value water [m³/h]	Voltage/ frequency [V/Hz]	Coil power [W]	Pressure range [bar]	Body material	Article no. without manual override	Article no. with manual override
Ex m II T4, with FKM seal and threaded connection with 3 m moulded cable, approved for single mounting, ambient temperature from - 10 °C...+ 55 °C									
CF C 3/2-way solenoid valve Direct-acting Normally closed 	G ⅛	2.0	0.11	024/UC	9	0...10	Brass	351966	351979
				230/UC				351982	352034
				024/UC	9		Stainless steel	351988	o. r.
				230/UC				352026	o. r.
	G ¼		0.11	024/UC	9	0...10	Brass	351969	351970
				230/UC				351978	352006
				024/UC	9		Stainless steel	351963	o. r.
				230/UC				352002	o. r.
	G ⅛	2.5	0.16	024/UC	9	0...6	Brass	o. r.	o. r.
				230/UC				o. r.	o. r.
	G ¼		0.16	024/UC	9	0...6	Brass	351995	352000
				230/UC				364572	o. r.
CF T 3/2-way solenoid valve Direct-acting Flow direction optional Normally closed 	G ⅛	1.5	0.07	024/UC	9	0...7	Brass	364573	o. r.
				230/UC				o. r.	o. r.
				024/UC	9		Stainless steel	352009	o. r.
				230/UC				351989	o. r.
	G ¼		0.07	024/UC	9	0...7	Brass	o. r.	o. r.
				230/UC				o. r.	o. r.
				024/UC	9		Stainless steel	351994	o. r.
				230/UC				o. r.	o. r.


o. r. = on request

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026



valvesgo.com

ATEX/IECEx m terminal box variant

Note:
The maximum medium temperature must never exceed the permitted temperature class (T4: + 135 °C, T5: + 100 °C, T6: + 85 °C) minus 5 K.

Circuit function	Port connection	Orifice	K_v value water	Voltage/ frequency	Coil power	Pressure range	Body material	Article no. with manual override
		[mm]	[m³/h]	[V/Hz]	[W]	[bar]		
Ex m II T4, with FKM seal and sub-base (SFB), approved for block mounting, ambient temperature from - 10 °C...+ 40 °C								
CF C 3/2-way solenoid valve Direct-acting Normally closed 	Sub-base (SFB)	1.5	0.07	024/UC	7	0...10	PA	352062
				230/UC				364576
				024/UC	7		Brass	o. r.
				230/UC				o. r.
	Sub-base (SFB)	2.0	0.11	024/UC	7	0...6	Brass	o. r.
				230/UC				o. r.

o. r. = on request

Circuit function	Port connection	Orifice	K_v value water	Voltage/ frequency	Coil power	Pressure range	Body material	Article no. without manual override	Article no. with manual override
		[mm]	[m³/h]	[V/Hz]	[W]	[bar]			
Ex m II T4, with FKM seal and threaded connection, approved for single mounting, ambient temperature form - 10 °C...+ 55 °C									
CF C 3/2-way solenoid valve Direct-acting Normally closed 	G ⅛	2.0	0.11	024/UC	9	0...10	Brass	352001	351983
				230/UC				352005	364614
				024/UC	9		Stainless steel	351998	o. r.
				230/UC				364581	o. r.
	G ¼		0.11	024/UC	9	0...10	Brass	351992	351980
				230/UC				364587	352071
				024/UC	9		Stainless steel	352067	o. r.
				230/UC				352041	o. r.
	G ⅛	2.5	0.16	024/UC	9	0...6	Brass	364595	o. r.
				230/UC				364598	o. r.
	G ¼		0.16	024/UC	9	0...6	Brass	364600	364615
				230/UC				364603	364618
CF T 3/2-way solenoid valve Direct-acting Flow direction optional Normally closed 	G ⅛	1.5	0.07	024/UC	9	0...7	Brass	364606	o. r.
				230/UC				o. r.	o. r.
				024/UC	9		Stainless steel	o. r.	o. r.
				230/UC				o. r.	o. r.
	G ¼		0.07	024/UC	9	0...7	Brass	o. r.	o. r.
				230/UC				o. r.	o. r.
				024/UC	9		Stainless steel	364610	o. r.
				230/UC				364611	o. r.


o. r. = on request

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

ATEX/IECEx ia variant

Note:
The maximum medium temperature must never exceed the permitted temperature class (T4: + 135 °C, T5: + 100 °C, T6: + 85 °C) minus 5 K.

Circuit function	Port connection	Orifice [mm]	Q_{Nn} value air [l/min]	Pressure range [bar]	Body material	Article no.
Ex ia II T6 with FKM seal only for approved single mounting, cable plug acc. to DIN EN 175 301 - 803 form A, ambient temperature from - 10 °C...+ 60 °C for T6, - 10...- 75 °C for T5						
CF C 3/2-way solenoid valve Direct-acting Normally closed 	Bürkert sub-base (SFB)	0.9	30	Vac. to 10	Stainless steel	20003982
	G ⅛					394532
	Bürkert sub-base (SFB)				Brass	394531
	G ⅛					394530

Further variants on request			
Additional Orifice: 1.2 mm, 3.0 mm		**Voltage** Non-standard voltages	
Approval Further information can be found in chapter "3. Approvals and conformities" on page 5.		**Material** Epoxy coil according to form A Seal material EPDM	

9.5. Ordering chart accessories

Single manifold


Note:
Refer to chapter "5.6. Single manifold" on page 17 for more order information.

Multiple manifold

Note:
Refer to chapter "5.7. Multiple manifold" on page 17 for more order information.

Cable plug Type 2518, form A according to DIN EN 175301 - 803

Note:
- Dimensions in mm
- For further variants see data sheet **Type 2518** ▶.

Cable plug	Dimensions	Variant	Voltage	Article no.
		Without wiring (AC/DC)	0...250 V AC/DC	314802
		With LED (AC/DC)	12...24 V AC/DC	314812
		With LED and varistor (AC/DC)	12...24 V AC/DC	314820
		With rectifier, LED and varistor	12...24 V AC/DC	314816


DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com

Cable plug Type 2509, form A according to DIN EN 175301 - 803

Note:

- Dimensions in mm
- Without wiring (standard)
- The cable plug Type 2509 meets the requirements of ATEX Cat. 3 GD in assembly with a Bürkert solenoid valve.
- The cable plug Type 2509 meets the requirements of UL Listed (UL 429) in assembly with a Bürkert solenoid valve.
- Refer to data sheet **Type 2509** ▶ for more information about the cable plug.

Cable plug	Dimensions	Variant	Voltage	Article no.
		Without wiring	0...250 V AC/DC	137943

Cable glands for ATEX/IECEX terminal box

Note:

- A polyamide cable gland is included in the scope of delivery. A nickel-plated brass variant can be ordered for a surcharge.
- Refer to **"8.1. Cable glands for ATEX/IECEx terminal box" on page 20** for more information about Ex cable glands.
- Refer to **"8.2. Special tool to turn the terminal box" on page 20** for more information about special tool.

Description	Article no.
Ex cable gland, nickel-plated brass, 6...13 mm [1.]	773278
Ex cable gland, polyamide, 7...13 mm [1.]	773277
Set SC02-AC10: special tool [2.] incl. service manual	293488

1.) Cable diameter
2.) Not included in the scope of delivery of the valve

DTS 1000010721 EN Version: - Status: RL (released | freigegeben | valide) printed: 28.10.2026

valvesgo.com