



## Servo-assisted 2/2-way diaphragm valve

- Servo-assisted diaphragm valve up to DN 50
- Vibration-resistant, centrally screwed coil system
- Damped design for quiet closing
- Energy-saving double coil technology with kick and drop variant
- Explosion-proof variants



Product variants described in the data sheet may differ from the product presentation and description.

### Can be combined with



#### Type 2518

Cable plug,  
form A according to  
DIN EN 175301-803



#### Type 2509

Cable plug,  
form A according to  
DIN EN 175301-803

### Type description

Valve 6281 is a servo-assisted diaphragm valve. A minimum differential pressure is always required for the valve to function. Various diaphragm materials and circuit functions are available depending on the actual application. The standard brass body meets European drinking water requirements. For other markets, dezincification-resistant brass is available. The range includes a variant with a stainless steel body. To reduce electrical power consumption during operation, coils with integrated Kick-and-Drop (KD) electronics featuring double coil technology are available. The valve can be supplied with manual operation for easy maintenance and commissioning.

## Table of contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>1. General technical data</b>                                 | <b>4</b>  |
| <b>2. Circuit functions</b>                                      | <b>5</b>  |
| <b>3. Approvals and conformities</b>                             | <b>5</b>  |
| 3.1. General notes .....                                         | 5         |
| 3.2. Conformity .....                                            | 5         |
| 3.3. Standards .....                                             | 5         |
| 3.4. Explosion protection .....                                  | 5         |
| 3.5. North America (USA/Canada) .....                            | 6         |
| 3.6. Drinking water .....                                        | 6         |
| 3.7. Others .....                                                | 6         |
| DNV GL classification .....                                      | 6         |
| Oxygen .....                                                     | 6         |
| VDE – Certificate of conformity with factory surveillance .....  | 7         |
| <b>4. Materials</b>                                              | <b>7</b>  |
| 4.1. Bürkert resistApp .....                                     | 7         |
| 4.2. Material specifications .....                               | 7         |
| <b>5. Dimensions</b>                                             | <b>8</b>  |
| 5.1. Standard variant .....                                      | 8         |
| Threaded variant .....                                           | 8         |
| Flange variant according to DIN EN 1092 - 1 .....                | 9         |
| 5.2. ATEX/IECEX variant .....                                    | 11        |
| Cable variant .....                                              | 11        |
| Terminal box variant .....                                       | 12        |
| Flange variant according to DIN EN 1092 - 1 .....                | 13        |
| 5.3. Compressor relief valves .....                              | 14        |
| <b>6. Performance specifications</b>                             | <b>15</b> |
| 6.1. Power consumption .....                                     | 15        |
| Standard variant .....                                           | 15        |
| With Kick and Drop coil .....                                    | 15        |
| <b>7. Product accessories</b>                                    | <b>15</b> |
| 7.1. Cable glands for ATEX/IECEX terminal box .....              | 15        |
| 7.2. Special tool to turn the terminal box .....                 | 16        |
| <b>8. Ordering information</b>                                   | <b>16</b> |
| 8.1. Bürkert eShop .....                                         | 16        |
| 8.2. Bürkert product filter .....                                | 16        |
| 8.3. Bürkert Product Enquiry Form .....                          | 16        |
| 8.4. Ordering chart .....                                        | 17        |
| Standard variant with brass body .....                           | 17        |
| Standard variant in brass with stainless steel flange body ..... | 18        |
| Standard variant with stainless steel body .....                 | 20        |
| ATEX/IECEX cable variant .....                                   | 22        |
| ATEX/IECEX terminal box variant .....                            | 23        |
| Compressor relief valve with brass body .....                    | 24        |

8.5.    Ordering chart accessories.....24

        Cable plug Type 2518, form A according to DIN EN 175301 - 803 .....24

        Cable plug Type 2509, form A according to DIN EN 175301 - 803.....25

        Cable glands for ATEX/IECEX terminal box .....25

        Mounting bracket kit for DN 10 .....25



valvesgo.com

## 1. General technical data

|                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product properties</b>                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Dimensions                                | Further information can be found in chapter <b>"5. Dimensions"</b> on page 8.                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Material</b>                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Seal                                      | NBR, EPDM, FKM                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Body                                      | Brass acc. to DIN EN 50930 - 6, stainless steel (dezincification resistant on request)                                                                                                                                                                                                                                                                                                                                                                                         |
| Inner valve parts                         | Stainless steel, brass, plastic (PPS)                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Orifice                                   | DN 10...DN 50                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Circuit function                          | Further information can be found in chapter <b>"2. Circuit functions"</b> on page 5.                                                                                                                                                                                                                                                                                                                                                                                           |
| Thermal insulation class of solenoid coil | Polyamide coil class B<br>Epoxy coil class H                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Performance data</b>                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Duty cycle                                | 100 % continuous operation                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Switching time <sup>1)</sup>              | Opening: 0.1...1.5 s<br>Closing: 0.2...4 s                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Electrical data</b>                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Operating voltage                         | 24 V DC, 24 V UC, 24 V 50/60 Hz, 230 V UC, 230 V 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power consumption                         | Further information can be found in chapter <b>"6. Performance specifications"</b> on page 15.                                                                                                                                                                                                                                                                                                                                                                                 |
| Voltage tolerance                         | ± 10 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Medium data</b>                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Operating medium                          | Medium that does not attack the housing and sealing materials<br>Further information can be found in chapter <b>"4.1. Bürkert resistApp"</b> on page 7.                                                                                                                                                                                                                                                                                                                        |
| <b>Medium temperature</b>                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| With NBR                                  | - 10 °C...+ 80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| With EPDM                                 | - 30 °C...+ 90 °C (with epoxy coil to + 100 °C)<br>0 °C...+ 60 °C (with drinking water approval according to UBA (PF36))                                                                                                                                                                                                                                                                                                                                                       |
| With FKM                                  | 0 °C...+ 90 °C (with epoxy coil to + 120 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Product connections</b>                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Electrical connection                     | <ul style="list-style-type: none"> <li>Cable plug <b>Type 2518</b> ▶, form A according to DIN EN 175301 - 803<br/>Further information can be found in chapter <b>"Cable plug Type 2518, form A according to DIN EN 175301 - 803"</b> on page 24.</li> <li>Cable plug <b>Type 2509</b> ▶, form A according to DIN EN 175301 - 803<br/>Further information can be found in chapter <b>"Cable plug Type 2509, form A according to DIN EN 175301 - 803"</b> on page 25.</li> </ul> |
| <b>Approvals and conformities</b>         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Directives                                | CE, EAC                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Degree of protection                      | IP65 with cable plug, cable connection and terminal box                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Explosion protection                      | Further information can be found in chapter <b>"3.4. Explosion protection"</b> on page 5.                                                                                                                                                                                                                                                                                                                                                                                      |
| North America (USA/Canada)                | Further information can be found in chapter <b>"3.5. North America (USA/Canada)"</b> on page 6.                                                                                                                                                                                                                                                                                                                                                                                |
| Drinking water                            | Further information can be found in chapter <b>"3.6. Drinking water"</b> on page 6.                                                                                                                                                                                                                                                                                                                                                                                            |
| Others                                    | Further information can be found in chapter <b>"3.7. Others"</b> on page 6.                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Environment and installation</b>       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Installation                              | As required, preferably with actuator upright                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Ambient temperature</b>                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Standard variant                          | Max. + 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Variant with kick and drop coil           | Max. + 70 °C (max. 30 switching operations/min)<br>Max. + 85 °C (max. 1 switching operation/min)<br>Max. + 55 °C (for variants with UR/UL approval)                                                                                                                                                                                                                                                                                                                            |

1) Measurement at + 20 °C, 6 bar at the valve inlet and free outlet, opening: pressure reduction to 90 % of the difference to the flow pressure, closing: pressure build-up to 90 % of the inlet pressure

## 2. Circuit functions

| Symbol                                                                            | Description                                                                                       |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
|  | <b>Circuit function A (CF A)</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed |
|  | <b>Circuit function B (CF B)</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally open   |

## 3. Approvals and conformities

### 3.1. General notes

- The approvals and conformities listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available variants can be supplied with the below mentioned approvals or conformities.

### 3.2. Conformity

In accordance with the Declaration of Conformity, the product is compliant with the EU Directives.

### 3.3. Standards

The applied standards which are used to demonstrate compliance with the EU Directives are listed in the EU-Type Examination Certificate and/or the EU Declaration of Conformity.

### 3.4. Explosion protection

| Approval                                                                                                                                                                   | Description                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br> | <b>Optional: Explosion protection</b><br><br><b>ATEX:</b><br>EPS 18 ATEX 1232 X<br>II 2G Ex mb IIC T4 Gb<br>II 2D Ex mb IIIC T130 °C Db<br>II 2G Ex eb mb IIC T4 Gb<br>II 2D Ex mb tb IIIC T130 °C Db<br><br><b>IECEx:</b><br>IECEx EPS 18.0110 X<br>Ex mb IIC T4 Gb<br>Ex mb IIIC T130 °C Db<br>Ex eb mb IIC T4 Gb<br>Ex mb tb IIIC T130 °C Db |

### 3.5. North America (USA/Canada)

| Approval                                                                          | Description                                                                                                                                                                                                                                                                 |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <b>Valid for valves: UL Listed for the USA</b><br>The valves are UL Listed for the USA according to: <ul style="list-style-type: none"> <li>UL 429 (electrically operated valves) and UL 429A (Electrically Operated Valves for Fire Protection Service)</li> </ul>         |
|  | <b>Valid for coils: UL Hazardous Locations – Explosion Protection</b><br>UL Listed for Hazardous Locations for USA and Canada<br>Class I, Zone 1<br>Class I, Division 2, Group A, B, C and D<br>Class II + III, Division 2, Group F and G                                   |
|  | <b>Valid for valves: UL Recognized for the USA</b><br>The valves are UL Recognized for the USA according to: <ul style="list-style-type: none"> <li>UL 429 (electrically operated valves) and UL 429A (Electrically Operated Valves for Fire Protection Service)</li> </ul> |
|  | <b>Valid for coils: UL Recognized for the USA and Canada</b><br>The coils are UL Recognized for the USA and Canada according to: <ul style="list-style-type: none"> <li>UL 429 (electrically operated valves)</li> <li>CAN/CSA-C22.2 No. 61010-1</li> </ul>                 |
|  | <b>Valid for valves: CSA for Canada</b><br>The valves are CSA approved for Canada according to: <ul style="list-style-type: none"> <li>CSA 139 (electrically operated valves)</li> </ul>                                                                                    |

### 3.6. Drinking water

| Conformity                                                                          | Description                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <b>Suitable for use in drinking water applications</b><br>The materials comply with the assessment principles (UBA) for materials in contact with drinking water (Trinkwasser).<br><br>PF39: Suitable for products with a maximum temperature of + 85 °C (hot water)<br>PF36: Suitable for products with a maximum temperature of + 60 °C (warm water) |

### 3.7. Others

#### DNV GL classification

| Approval                                                                            | Description                                                                                                                                                          |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <b>DNV GL classification – Ships, offshore units, and high speed and light craft</b><br>The products are accepted for installation on all vessels classed by DNV GL. |

#### Oxygen


| Conformity                                                                          | Description                                                                                                                                                                       |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <b>Optional: Suitability for oxygen (valid for the variable code NL02)</b><br>The products are suitable for use with gaseous oxygen, according to the manufacturer's declaration. |

VDE – Certificate of conformity with factory surveillance

| Approval                                                                          | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p><b>Optional: Certificate of conformity with factory surveillance (VDE Testing and Certification Institute) (valid for the variable code PW01 and PW02)</b></p> <p>The electrically operated water valves are tested and certified according to:</p> <ul style="list-style-type: none"><li>• DIN EN 60730-1 (VDE 0631-1)</li><li>• EN 60730-1</li><li>• DIN EN IEC 60730-2-8 (VDE 0631-2-8)</li></ul> <p>The electrically operated water valves also fulfill the requirements of:</p> <ul style="list-style-type: none"><li>• IEC 60730-1</li><li>• IEC 60730-2-8</li></ul> |

4. Materials

4.1. Bürkert resistApp




**Bürkert resistApp – Chemical resistance chart**

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.

[Start chemical resistance check](#)

4.2. Material specifications



| No. | Element          | Material                                                        |
|-----|------------------|-----------------------------------------------------------------|
| 1   | Coil             | Polyamide <sup>1.)</sup> or epoxy <sup>2.)</sup>                |
| 2   | Stopper          | Stainless steel 1.4113                                          |
| 3   | Shading ring     | Cu (brass variant)<br>Ag (stainless steel variant)              |
| 4   | Magnetic core    | Stainless steel 1.4113                                          |
| 5   | O-ring           | NBR, FKM, EPDM                                                  |
| 6   | Core seal        | NBR, FKM, EPDM                                                  |
| 7   | Spring           | Stainless steel 1.4310                                          |
| 8   | O-ring           | NBR, FKM, EPDM                                                  |
| 9   | Diaphragm        | NBR, FKM, EPDM                                                  |
| 10  | Diaphragm holder | PPSGF40, DN 50: brass and stainless steel                       |
| 11  | Valve body       | Brass acc. to DIN EN 50930 - 6 or stainless steel 1.4408 (CF8M) |

1.) With NBR/EPDM seal  
2.) With FKM seal


5. Dimensions

5.1. Standard variant

Threaded variant

Note:

- Dimensions in mm
- The dimensions F1 and G1 apply to G thread.
- The dimensions F2 and G2 apply to NPT thread.
- The dimensions F3 and G3 apply to Rc thread.



| Coil size | H  | J    | K  | M    | O   |
|-----------|----|------|----|------|-----|
| 5         | 32 | 20.5 | 45 | 41   | 3.4 |
| 6         | 40 | 23.5 | 51 | 41.4 | 3.8 |


| DN               | A     | B     | C  | D    | E     | G  |      | NPT  |        | Rc   |       | L  | SW | N  |
|------------------|-------|-------|----|------|-------|----|------|------|--------|------|-------|----|----|----|
|                  |       |       |    |      |       | F1 | G1   | F2   | G2     | F3   | G3    |    |    |    |
| 10 <sup>1)</sup> | 83.1  | 94.1  | 32 | 44   | 22    | 12 | G ¼  | 10   | NPT ¼  | –    | –     | 50 | 22 | –  |
|                  |       |       |    |      |       | 12 | G ⅜  | 10.3 | NPT ⅜  | 10.1 | Rc ⅜  |    |    |    |
|                  | 85.1  | 98.6  |    |      | 24.5  | 14 | G ½  | 13.7 | NPT ½  | –    | –     |    |    |    |
| 10 <sup>2)</sup> | 83.6  | 94.6  | 32 | 44   | 22    | 12 | G ¼  | 10   | NPT ¼  | –    | –     | 50 | 22 | –  |
|                  |       |       |    |      |       | 12 | G ⅜  | 10.3 | NPT ⅜  | 10.1 | Rc ⅜  |    |    |    |
|                  | 85.6  | 99.1  |    |      | 24.5  | 14 | G ½  | 13.7 | NPT ½  | –    | –     |    |    |    |
| 13 <sup>1)</sup> | 91.1  | 104.6 | 42 | 54.5 | 27.25 | 12 | G ⅜  | –    | –      | –    | –     | 58 | 27 | –  |
| 13               |       |       |    |      | 32.5  | 14 | G ½  | 13.7 | NPT ½  | 13.2 | Rc ½  | 65 | 27 | –  |
|                  | 93.1  | 109.1 |    |      |       | 16 | G ¾  | 14   | NPT ¾  | –    | –     | 65 | 32 |    |
| 20               | 99.6  | 115.6 | 60 | 74   | 37    | 16 | G ¾  | 14   | NPT ¾  | 14.5 | Rc ¾  | 80 | 32 | 10 |
|                  | 102.1 | 122.6 |    |      | 37.5  | 18 | G 1  | 16.8 | NPT 1  | –    | –     | 80 | 41 |    |
| 25               | 106.6 | 127.1 | 70 | 85   | 46    | 18 | G 1  | 16.8 | NPT 1  | 16.8 | Rc 1  | 95 | 41 | 15 |
|                  | 111.6 | 136.6 |    |      |       | 20 | G 1¼ | 17.3 | NPT 1¼ | 19.1 | Rc 1¼ | 95 | 50 |    |

| DN                | A     | B     | C   | D   | E    | G  |      | NPT  |        | Rc   |       | L   | SW | N  |
|-------------------|-------|-------|-----|-----|------|----|------|------|--------|------|-------|-----|----|----|
|                   |       |       |     |     |      | F1 | G1   | F2   | G2     | F3   | G3    |     |    |    |
| 40 <sup>1.)</sup> | 120.1 | 145.1 | 99  | 114 | 61   | 20 | G 1¼ | 17.3 | NPT 1¼ | 19.1 | Rc 1¼ | 126 | 50 | 23 |
| 40                | 125.6 | 155.6 |     |     |      | 22 | G 1½ |      | NPT 1½ |      | Rc 1½ | 126 | 60 |    |
|                   | 131.6 | 166.6 |     |     |      | 64 | G 2  |      | NPT 2  |      | Rc 2  | 132 | 70 |    |
| 50 <sup>1.)</sup> | 119.9 | 154.9 | 115 | 132 | 82   | 24 | G 2  | 17.6 | NPT 2  | 23.4 | Rc 2  | 164 | 70 | 37 |
|                   | 119.6 | 162.1 |     |     | 89.5 | 27 | G 2½ |      |        |      |       | 179 | 85 |    |

1.) Only threaded brass connection  
2.) Only threaded stainless steel connection

Flange variant according to DIN EN 1092 - 1

**Note:**  
Dimensions in mm



DTS 1000152082 EN Version: T Status: RL (released | freigegeben | valide) printed: 09.04.2026


| DN | A     | B     | C   | D   | L   | N  | P   | R   | S  | T   |
|----|-------|-------|-----|-----|-----|----|-----|-----|----|-----|
| 25 | 102.6 | 160.1 | 70  | 85  | 160 | 15 | 68  | 115 | 14 | 85  |
| 40 | 116.2 | 186.6 | 99  | 114 | 180 | 23 | 78  | 140 | 18 | 100 |
| 40 | 125.6 | 200.6 |     |     | 200 |    | 88  | 150 | 18 | 110 |
| 50 | 119.9 | 202.4 | 115 | 132 | 230 | 37 | 102 | 165 | 18 | 125 |

5.2. ATEX/IECEx variant

Cable variant

Note:

- Dimensions in mm
- The dimensions F1 and G1 apply to G thread.
- The dimensions F2 and G2 apply to NPT thread.
- The dimensions F3 and G3 apply to Rc thread.
- For DN 50 see dimensions “Terminal box variant” on page 12




| Coil size | H  | J    | K  | P    | R    | S     |
|-----------|----|------|----|------|------|-------|
| 5         | 32 | 20.5 | 46 | 68.8 | 99.8 | 174.7 |
| 6         | 40 | 23.5 | 52 | 74.8 | 103  | 177.7 |

- 1.) Only threaded brass connection
- 2.) Only threaded stainless steel connection


**Note:**

- Dimensions in mm
- Standard at DN 50



Flange variant according to DIN EN 1092 - 1

**Note:**  
Dimensions in mm




| DN | A     | B     | C   | D   | L   | N  | P   | R   | S  | T   |
|----|-------|-------|-----|-----|-----|----|-----|-----|----|-----|
| 25 | 102.6 | 160.1 | 70  | 85  | 160 | 15 | 68  | 115 | 14 | 85  |
| 40 | 116.2 | 186.6 | 99  | 114 | 180 | 23 | 78  | 140 | 18 | 100 |
| 40 | 125.6 | 200.6 |     |     | 200 |    | 88  | 150 | 18 | 110 |
| 50 | 119.9 | 202.4 | 115 | 132 | 230 | 37 | 102 | 165 | 18 | 125 |
| 40 | 125.6 | 200.6 | 99  | 114 | 200 | 23 | 88  | 150 | 18 | 110 |

5.3. Compressor relief valves

Note:

- Dimensions in mm
- The dimensions F1 and G1 apply to G thread.
- The dimensions F2 and G2 apply to NPT thread.
- The dimensions F3 and G3 apply to Rc thread.



| Coil size | H  | J    | K  | M    | O    |
|-----------|----|------|----|------|------|
| 5         | 32 | 20.5 | 46 | 41   | 11.2 |
| 6         | 40 | 23.5 | 52 | 41.4 | 10.8 |

| DN | A     | B     | C  | D    | E     | G    |       | NPT  |       | Rc   |      | L  | SW |
|----|-------|-------|----|------|-------|------|-------|------|-------|------|------|----|----|
|    |       |       |    |      |       | F1   | G1    | F2   | G2    | F3   | G3   |    |    |
| 10 | 90.5  | 101.5 | 32 | 44   | 22    | 12   | G ¼   | 10   | NPT ¼ | –    | –    | 50 | 22 |
|    | 12    | G ⅜   |    |      |       | 10.3 | NPT ⅜ | 10.1 | Rc ⅜  |      |      |    |    |
|    | 92.5  | 106   |    |      | 24.5  | 14   | G ½   | 13.7 | NPT ½ | 13.2 | Rc ½ |    | 27 |
| 13 | 90    | 103.5 | 42 | 54.5 | 27.25 | 12   | G ⅜   | –    | –     | –    | –    | 58 | 27 |
|    |       | 14    |    |      | G ½   | 13.7 | NPT ½ | 13.2 | Rc ½  |      |      |    |    |
|    | 92    | 108   |    |      | 32.5  | 16   | G ¾   | 14   | NPT ¾ | 14.5 | Rc ¾ | 65 | 32 |
| 20 | 107   | 123   | 60 | 74   | 37    | 16   | G ¾   | 14   | NPT ¾ | 14.5 | Rc ¾ | 80 | 32 |
|    | 109.5 | 130   |    |      | 37.5  | 18   | G 1   | 16.8 | NPT 1 | –    | –    |    | 41 |

## 6. Performance specifications

### 6.1. Power consumption

#### Standard variant

| Circuit function | Orifice<br>[mm] | Coil size<br>[mm] | AC                   |                           |   | DC                |                   | ATEX AC/DC<br>Nominal power<br>[W] |
|------------------|-----------------|-------------------|----------------------|---------------------------|---|-------------------|-------------------|------------------------------------|
|                  |                 |                   | Inrush power<br>[VA] | Holding power<br>[VA] [W] |   | Cold power<br>[W] | Warm power<br>[W] |                                    |
| A                | 10...50         | 32                | 24                   | 14                        | 8 | 9.5               | 8                 | –                                  |
| A                | 10...50         | 32                | 24                   | 16                        | 7 | 9.5               | 8                 | –                                  |
| A / B            | 13...50         | 40                | –                    | –                         | – | –                 | –                 | 9                                  |
| A                | 10              | 32                | –                    | –                         | – | –                 | –                 | 7                                  |
| B                | 10              | 40                | –                    | –                         | – | –                 | –                 | 9                                  |
| B u. CF05        | 10              | 32                | 18                   | 11                        | 5 | 6                 | 5                 | –                                  |
| B u. MX62        | 13              | 32                | 24                   | 14                        | 8 | –                 | –                 | –                                  |
| B u. MX62        | 13              | 40                | –                    | –                         | – | 11                | 9.5               | –                                  |

#### With Kick and Drop coil



| Circuit function | Orifice<br>[mm] | Coil size<br>[mm] | Voltage<br>[V] | Inrush power (approx. 500 ms) |     | Holding power<br>[W] |
|------------------|-----------------|-------------------|----------------|-------------------------------|-----|----------------------|
|                  |                 |                   |                | [VA]                          | [W] |                      |
| A                | 10...50         | 40                | 024/UC         | –                             | 12  | 0.6                  |
| A                | 10...50         | 40                | 230/56         | 20                            | –   | 2                    |
| B                | 10...50         | 40                | 024/UC         | –                             | 20  | 2                    |
| B                | 10...50         | 40                | 230/56         | 20                            | –   | 2                    |

## 7. Product accessories

### 7.1. Cable glands for ATEX/IECEx terminal box

#### Note:


A polyamide cable gland is included in the scope of delivery. A nickel-plated brass variant can be ordered for a surcharge, see ["Cable glands for ATEX/IECEx terminal box"](#) on page 25.

| Description                                                                                                                                  | Ex approval                               |                                                  | Dimensions                                                                                                                                                                                                                                                                        |    |            |   |       |   |       |    |       |   |       |
|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|--------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|------------|---|-------|---|-------|----|-------|---|-------|
|                                                                                                                                              | Certification                             | Identification                                   |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| Ex cable gland,<br>nickel-plated brass, 6...13 mm<br><br> | PTB 04 ATEX 1112 X,<br>IECEX PTB 13.0027X | II 2 G Ex e IIC Gb,<br>II 2 D Ex tb IIIC Db IP68 |  <table><tr><td>TL</td><td>29...37 mm</td></tr><tr><td>L</td><td>6 mm</td></tr><tr><td>D</td><td>20 mm</td></tr><tr><td>SW</td><td>24 mm</td></tr><tr><td>E</td><td>27 mm</td></tr></table>  | TL | 29...37 mm | L | 6 mm  | D | 20 mm | SW | 24 mm | E | 27 mm |
| TL                                                                                                                                           | 29...37 mm                                |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| L                                                                                                                                            | 6 mm                                      |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| D                                                                                                                                            | 20 mm                                     |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| SW                                                                                                                                           | 24 mm                                     |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| E                                                                                                                                            | 27 mm                                     |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| Ex cable gland,<br>polyamide, 7...13 mm<br><br>           | PTB 13 ATEX 1015 X,<br>IECEX PTB 13.0034X | II 2 G Ex e IIC Gb,<br>II 2 D Ex tb IIIC Db IP68 |  <table><tr><td>TL</td><td>36...45 mm</td></tr><tr><td>L</td><td>10 mm</td></tr><tr><td>D</td><td>20 mm</td></tr><tr><td>SW</td><td>24 mm</td></tr><tr><td>E</td><td>28 mm</td></tr></table> | TL | 36...45 mm | L | 10 mm | D | 20 mm | SW | 24 mm | E | 28 mm |
| TL                                                                                                                                           | 36...45 mm                                |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| L                                                                                                                                            | 10 mm                                     |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| D                                                                                                                                            | 20 mm                                     |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| SW                                                                                                                                           | 24 mm                                     |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |
| E                                                                                                                                            | 28 mm                                     |                                                  |                                                                                                                                                                                                                                                                                   |    |            |   |       |   |       |    |       |   |       |

## 7.2. Special tool to turn the terminal box

### Note:

This special tool is not included in the scope of delivery of the valve, see ["Cable glands for ATEX/IECEx terminal box"](#) on page 25.

| Description                                                                                        | Components of the set                                                                      |
|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Set SC02-AC10<br> | <ul style="list-style-type: none"> <li>• Special tool</li> <li>• Service manual</li> </ul> |

## 8. Ordering information

### 8.1. Bürkert eShop



#### Bürkert eShop – Easy ordering and quick delivery

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

[Order online now](#)

### 8.2. Bürkert product filter




#### Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

### 8.3. Bürkert Product Enquiry Form



#### Bürkert Product Enquiry Form – Your enquiry quickly and compactly

Would you like to make a specific product enquiry based on your technical requirements? Use our Product Enquiry Form for this purpose. There you will find all the relevant information for your Bürkert contact. This will enable us to provide you with the best possible advice.

[Fill out the form now](#)




## 8.4. Ordering chart


### Standard variant with brass body

#### Circuit function A

##### Note:

Please note that the cable plug must be ordered separately, see **"8.5. Ordering chart accessories"** on page 24 or separate data sheet for **Type 2518** ▶.

| Circuit function                                                                                                                                                    | Port connection                                                   | Orifice | K <sub>v</sub> value<br>water <sup>1.) 2.)</sup> | Pressure<br>range <sup>3.)</sup> | Weight                                                                                     | Article no.                                                                                |                                                                                            |                                                                                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------|--------------------------------------------------|----------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
|                                                                                                                                                                     |                                                                   | [mm]    | [m³/h]                                           | [bar]                            | [kg]                                                                                       | 024/DC<br>[V/Hz]                                                                           | 024/50...60<br>[V/Hz]                                                                      | 230/50...60<br>[V/Hz]                                                                      |
| Seal material NBR, polyamide coil, medium temperature - 10 °C...+ 80 °C                                                                                             |                                                                   |         |                                                  |                                  |                                                                                            |                                                                                            |                                                                                            |                                                                                            |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br>   | G ¼                                                               | 10      | 1.5                                              | 0.2...16                         | 0.43                                                                                       | 322499    | 322500    | 322501    |
|                                                                                                                                                                     | G ⅜                                                               | 10      | 1.9                                              | 0.2...16                         | 0.40                                                                                       | 322502    | 322503    | 322504    |
|                                                                                                                                                                     | G ⅜                                                               | 13      | 3.8                                              | 0.2...16                         | 0.58                                                                                       | 221841    | 221842    | 221843    |
|                                                                                                                                                                     | G ½                                                               | 13      | 3.8                                              | 0.2...16                         | 0.54                                                                                       | 221844    | 221845    | 221846    |
|                                                                                                                                                                     | G ¾                                                               | 13      | 3.8                                              | 0.2...16                         | 0.59                                                                                       | 221847    | 221848    | 221849    |
|                                                                                                                                                                     | G ¾                                                               | 20      | 8.5                                              | 0.2...16                         | 0.89                                                                                       | 221850    | 221851    | 221852    |
|                                                                                                                                                                     | G 1                                                               | 20      | 8.5                                              | 0.2...16                         | 1.0                                                                                        | 221853    | 221854    | 221855    |
|                                                                                                                                                                     | G 1                                                               | 25      | 12                                               | 0.2...16                         | 1.3                                                                                        | 221856    | 221857    | 221858    |
|                                                                                                                                                                     | G 1¼                                                              | 25      | 12                                               | 0.2...16                         | 1.5                                                                                        | 221859    | 221860    | 221861    |
|                                                                                                                                                                     | G 1¼                                                              | 40      | 23                                               | 0.2...16                         | 2.7                                                                                        | 270131    | 268550    | 270132    |
|                                                                                                                                                                     | G 1½                                                              | 40      | 30                                               | 0.2...16                         | 3.0                                                                                        | 221862    | 221863    | 221864    |
|                                                                                                                                                                     | G 2                                                               | 40      | 30                                               | 0.2...16                         | 3.2                                                                                        | 221865    | 221866    | 221867    |
|                                                                                                                                                                     | G 2                                                               | 50      | 40                                               | 0.2...16                         | 4.5                                                                                        | 253156   | 253157   | 253158   |
| G 2½                                                                                                                                                                | 50                                                                | 40      | 0.2...16                                         | 5.2                              | 253159  | 253160  | 253161  |                                                                                            |
| Seal material NBR, polyamide coil, medium temperature - 10 °C...+ 80 °C, with manual override                                                                       |                                                                   |         |                                                  |                                  |                                                                                            |                                                                                            |                                                                                            |                                                                                            |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G ¼                                                               | 10      | 1.5                                              | 0.2...16                         | 0.43                                                                                       | 322505  | 322506  | 322507  |
|                                                                                                                                                                     | G ⅜                                                               | 10      | 1.9                                              | 0.2...16                         | 0.40                                                                                       | 322508  | 322509  | 322510  |
|                                                                                                                                                                     | G ½                                                               | 13      | 3.8                                              | 0.2...16                         | 0.54                                                                                       | 221952  | o. r.                                                                                      | 221953  |
|                                                                                                                                                                     | G ¾                                                               | 13      | 3.8                                              | 0.2...16                         | 0.59                                                                                       | 221954  | o. r.                                                                                      | 221955  |
|                                                                                                                                                                     | G ¾                                                               | 20      | 8.5                                              | 0.2...16                         | 0.89                                                                                       | 221956  | o. r.                                                                                      | 221957  |
|                                                                                                                                                                     | G 1                                                               | 20      | 8.5                                              | 0.2...16                         | 1.0                                                                                        | 221958  | o. r.                                                                                      | 221959  |
|                                                                                                                                                                     | G 1                                                               | 25      | 12                                               | 0.2...16                         | 1.3                                                                                        | 221960  | o. r.                                                                                      | 221961  |
|                                                                                                                                                                     | G 1¼                                                              | 25      | 12                                               | 0.2...16                         | 1.5                                                                                        | 221962  | o. r.                                                                                      | 221963  |
|                                                                                                                                                                     | G 1¼                                                              | 40      | 23                                               | 0.2...16                         | 2.7                                                                                        | 270142  | o. r.                                                                                      | 270143  |
|                                                                                                                                                                     | G 1½                                                              | 40      | 30                                               | 0.2...16                         | 3.0                                                                                        | 221964  | o. r.                                                                                      | 221965  |
|                                                                                                                                                                     | G 2                                                               | 40      | 30                                               | 0.2...16                         | 3.2                                                                                        | 221966  | o. r.                                                                                      | 221967  |
|                                                                                                                                                                     | Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C |         |                                                  |                                  |                                                                                            |                                                                                            |                                                                                            |                                                                                            |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G ¼                                                               | 10      | 1.5                                              | 0.2...16                         | 0.43                                                                                       | 322511  | 322512  | 322513  |
|                                                                                                                                                                     | G ⅜                                                               | 10      | 1.9                                              | 0.2...16                         | 0.40                                                                                       | 322514  | 322515  | 322516  |
|                                                                                                                                                                     | G ⅜                                                               | 13      | 3.8                                              | 0.2...16                         | 0.58                                                                                       | 221868  | 221869  | 221870  |
|                                                                                                                                                                     | G ½                                                               | 13      | 3.8                                              | 0.2...16                         | 0.54                                                                                       | 221871  | 221872  | 221873  |
|                                                                                                                                                                     | G ¾                                                               | 13      | 3.8                                              | 0.2...16                         | 0.59                                                                                       | 221874  | 221875  | 221876  |
|                                                                                                                                                                     | G ¾                                                               | 20      | 8.5                                              | 0.2...16                         | 0.89                                                                                       | 221877  | 221878  | 221879  |
|                                                                                                                                                                     | G 1                                                               | 20      | 8.5                                              | 0.2...16                         | 1.0                                                                                        | 221880  | 221881  | 221882  |
|                                                                                                                                                                     | G 1                                                               | 25      | 12                                               | 0.2...16                         | 1.3                                                                                        | 221883  | 221884  | 221885  |
|                                                                                                                                                                     | G 1¼                                                              | 25      | 12                                               | 0.2...16                         | 1.5                                                                                        | 221886  | 221887  | 221888  |
|                                                                                                                                                                     | G 1¼                                                              | 40      | 23                                               | 0.2...16                         | 2.7                                                                                        | 270133  | 270134  | 270135  |
|                                                                                                                                                                     | G 1½                                                              | 40      | 30                                               | 0.2...16                         | 3.0                                                                                        | 221889  | 221890  | 221891  |
|                                                                                                                                                                     | G 2                                                               | 40      | 30                                               | 0.2...16                         | 3.2                                                                                        | 221892  | 221893  | 221894  |
|                                                                                                                                                                     | G 2                                                               | 50      | 40                                               | 0.2...16                         | 4.5                                                                                        | 253168  | 253169  | 253170  |
|                                                                                                                                                                     | G 2½                                                              | 50      | 40                                               | 0.2...16                         | 5.2                                                                                        | 253171  | 253172  | 253173  |

| Circuit function                                                                                                                                                  | Port connection | Orifice           | K <sub>v</sub> value water <sup>1.) 2.)</sup> | Pressure range <sup>3.)</sup> | Weight | Article no. |             |             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------------|-----------------------------------------------|-------------------------------|--------|-------------|-------------|-------------|
|                                                                                                                                                                   |                 | [mm]              |                                               |                               |        | 024/DC      | 024/50...60 | 230/50...60 |
|                                                                                                                                                                   |                 |                   | [m <sup>3</sup> /h]                           | [bar]                         | [kg]   | [V/Hz]      | [V/Hz]      | [V/Hz]      |
| Seal material EPDM, polyamide coil, medium temperature - 30 °C...+ 90 °C                                                                                          |                 |                   |                                               |                               |        |             |             |             |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G 1/4           | 10                | 1.5                                           | 0.2...16                      | 0.43   | 322517      | 322518      | 322519      |
|                                                                                                                                                                   | G 3/8           | 10                | 1.9                                           | 0.2...16                      | 0.40   | 322520      | 322521      | 322522      |
|                                                                                                                                                                   | G 3/8           | 13                | 3.8                                           | 0.2...16                      | 0.58   | 221895      | 221896      | 221897      |
|                                                                                                                                                                   | G 1/2           | 13                | 3.8                                           | 0.2...16                      | 0.54   | 221898      | 221899      | 221900      |
|                                                                                                                                                                   | G 3/4           | 13                | 3.8                                           | 0.2...16                      | 0.59   | 221901      | 221902      | 221903      |
|                                                                                                                                                                   | G 3/4           | 20                | 8.5                                           | 0.2...16                      | 0.89   | 221904      | 221905      | 221906      |
|                                                                                                                                                                   | G 1             | 20                | 8.5                                           | 0.2...16                      | 1.0    | 221907      | 221908      | 221909      |
|                                                                                                                                                                   | G 1             | 25                | 12                                            | 0.2...16                      | 1.3    | 221910      | 221911      | 221912      |
|                                                                                                                                                                   | G 1 1/4         | 25                | 12                                            | 0.2...16                      | 1.5    | 221913      | 221914      | 221915      |
|                                                                                                                                                                   | G 1 1/4         | 40                | 23                                            | 0.2...16                      | 2.7    | 270136      | 270137      | 270138      |
|                                                                                                                                                                   | G 1 1/2         | 40                | 30                                            | 0.2...16                      | 3.0    | 221916      | 221917      | 221918      |
|                                                                                                                                                                   | G 2             | 40                | 30                                            | 0.2...16                      | 3.2    | 221919      | 221920      | 221921      |
|                                                                                                                                                                   | G 2             | 50 <sup>4.)</sup> | 40                                            | 0.2...16                      | 4.5    | 253162      | 253163      | 253164      |
|                                                                                                                                                                   | G 2 1/2         | 50 <sup>4.)</sup> | 40                                            | 0.2...16                      | 5.2    | 253165      | 253166      | 253167      |

o. r. = on request

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.


3.) Pressure data: overpressure to atmospheric pressure

4.) Approved for drinking water according to KTW and W270

### Standard variant in brass with stainless steel flange body

#### Note:

Please note that the cable plug must be ordered separately, see ["8.5. Ordering chart accessories"](#) on page 24 or separate data sheet for **Type 2518** ▶.

| Circuit function                                                                                                                                                    | Port connection | Orifice | K <sub>v</sub> value water <sup>1.) 2.)</sup> | Pressure range <sup>3.)</sup> | Weight | Article no. |             |             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|-----------------------------------------------|-------------------------------|--------|-------------|-------------|-------------|
|                                                                                                                                                                     |                 | [mm]    |                                               |                               |        | 024/DC      | 024/50...60 | 230/50...60 |
|                                                                                                                                                                     |                 |         | [m <sup>3</sup> /h]                           | [bar]                         | [kg]   | [V/Hz]      | [V/Hz]      | [V/Hz]      |
| Flange connection according to DIN EN 1092 - 1, seal material NBR, medium temperature - 10 °C...+ 80 °C                                                             |                 |         |                                               |                               |        |             |             |             |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | Flange DN 25    | 25      | 12                                            | 0.2...16                      | 3.75   | 20131970    | 20131971    | 20131972    |
|                                                                                                                                                                     | Flange DN 32    | 40      | 23                                            | 0.2...16                      | 6.10   | 20131976    | 20131977    | 20131978    |
|                                                                                                                                                                     | Flange DN 40    | 40      | 30                                            | 0.2...16                      | 6.10   | 20131982    | 20131983    | 20131985    |
|                                                                                                                                                                     | Flange DN 50    | 50      | 40                                            | 0.2...16                      | 10     | 20131989    | 20131991    | 20131992    |

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet


2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

## Circuit function B

## Note:

Please note that the cable plug must be ordered separately, see **"8.5. Ordering chart accessories" on page 24** or separate data sheet for **Type 2518** ▶.

| Circuit function                                                                                                                                                | Port connection | Orifice | K <sub>v</sub> value water <sup>1.) 2.)</sup> | Pressure range <sup>3.)</sup> | Weight | Article no. |        |        |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|-----------------------------------------------|-------------------------------|--------|-------------|--------|--------|
|                                                                                                                                                                 |                 | [mm]    |                                               |                               |        | 024/DC      | 024/50 | 230/50 |
|                                                                                                                                                                 |                 |         | [m <sup>3</sup> /h]                           | [bar]                         | [kg]   | [V/Hz]      | [V/Hz] | [V/Hz] |
| Seal material NBR, epoxy coil, medium temperature - 10 °C...+ 80 °C                                                                                             |                 |         |                                               |                               |        |             |        |        |
| <b>CF B</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally open<br> | G 1/4           | 10      | 1.5                                           | 0.2...16                      | 0.43   | 322523      | 322524 | 322525 |
|                                                                                                                                                                 | G 3/8           | 10      | 1.9                                           | 0.2...16                      | 0.40   | 322526      | 322527 | 322528 |
|                                                                                                                                                                 | G 3/8           | 13      | 3.8                                           | 0.2...16                      | 0.58   | 221923      | 221924 | 221925 |
|                                                                                                                                                                 | G 1/2           | 13      | 3.8                                           | 0.2...16                      | 0.54   | 221926      | 221928 | 221929 |
|                                                                                                                                                                 | G 3/4           | 13      | 3.8                                           | 0.2...16                      | 0.59   | 221930      | 221931 | 221933 |
|                                                                                                                                                                 | G 3/4           | 20      | 8.5                                           | 0.2...16                      | 0.89   | 221934      | 221935 | 221936 |
|                                                                                                                                                                 | G 1             | 20      | 8.5                                           | 0.2...16                      | 1.0    | 221937      | 221938 | 221939 |
|                                                                                                                                                                 | G 1             | 25      | 12                                            | 0.2...16                      | 1.3    | 221940      | 221941 | 221942 |
|                                                                                                                                                                 | G 1 1/4         | 25      | 12                                            | 0.2...16                      | 1.5    | 221943      | 221944 | 221945 |
|                                                                                                                                                                 | G 1 1/4         | 40      | 23                                            | 0.2...16                      | 2.7    | 270139      | 270140 | 270141 |
|                                                                                                                                                                 | G 1 1/2         | 40      | 30                                            | 0.2...16                      | 3.0    | 221946      | 221947 | 221948 |
|                                                                                                                                                                 | G 2             | 40      | 30                                            | 0.2...16                      | 3.2    | 221949      | 221950 | 221951 |
|                                                                                                                                                                 | G 2             | 50      | 40                                            | 0.2...16                      | 4.5    | 253174      | 253175 | 253176 |
|                                                                                                                                                                 | G 2 1/2         | 50      | 40                                            | 0.2...16                      | 5.2    | 253177      | 253178 | 253179 |

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet


2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

## Circuit function A, with Kick and Drop coil

## Note:

- Please note that the cable plug must be ordered separately, see **"8.5. Ordering chart accessories" on page 24** or separate data sheet for **Type 2518** ▶.
- The Kick and Drop coil (AC/DC) features integrated electronics for short-term power increase and decrease in double coil technology.

| Circuit function                                                                                                                                                    | Port connection | Orifice | K <sub>v</sub> value water <sup>1.) 2.)</sup> | Pressure range <sup>3.)</sup> | Weight | Article no. |               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|-----------------------------------------------|-------------------------------|--------|-------------|---------------|
|                                                                                                                                                                     |                 | [mm]    |                                               |                               |        | 024 / AC/DC | 230 / 50...60 |
|                                                                                                                                                                     |                 |         | [m <sup>3</sup> /h]                           | [bar]                         | [kg]   | [V/Hz]      | [V/Hz]        |
| Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C                                                                                                   |                 |         |                                               |                               |        |             |               |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G 1/4           | 10      | 1.5                                           | 0.2...16                      | 0.43   | 20046906    | 20046961      |
|                                                                                                                                                                     | G 3/8           | 10      | 1.9                                           | 0.2...16                      | 0.40   | 20046907    | 20046960      |
|                                                                                                                                                                     | G 1/2           | 13      | 3.8                                           | 0.2...16                      | 0.54   | 20046908    | 20046963      |
|                                                                                                                                                                     | G 3/4           | 20      | 8.5                                           | 0.2...16                      | 0.89   | 20046909    | 20046964      |
|                                                                                                                                                                     | G 1             | 25      | 12                                            | 0.2...16                      | 1.3    | 20046910    | 20046965      |
|                                                                                                                                                                     | G 1 1/4         | 40      | 23                                            | 0.2...16                      | 2.7    | 20046911    | 20046966      |
|                                                                                                                                                                     | G 1 1/2         | 40      | 30                                            | 0.2...16                      | 3.0    | 20046912    | 20046967      |
|                                                                                                                                                                     | G 2             | 50      | 40                                            | 0.2...16                      | 4.5    | 20046913    | 20046968      |
|                                                                                                                                                                     | G 2 1/2         | 50      | 40                                            | 0.2...16                      | 5.2    | 20046914    | 20046969      |

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet


2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

## Circuit function B, with Kick and Drop coil

## Note:

- Please note that the cable plug must be ordered separately, see ["8.5. Ordering chart accessories" on page 24](#) or separate data sheet for **Type 2518** ▶.
- The Kick and Drop coil (AC/DC) features integrated electronics for short-term power increase and decrease in double coil technology.

| Circuit function                                                                                                                                                | Port connection | Orifice | K <sub>v</sub> value water <sup>1.) 2.)</sup> | Pressure range <sup>3.)</sup> | Weight | Article no.                                                                                |                                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|-----------------------------------------------|-------------------------------|--------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
|                                                                                                                                                                 |                 |         |                                               |                               |        | 024 / AC/DC                                                                                | 230 / 50...60                                                                              |
|                                                                                                                                                                 |                 | [mm]    | [m³/h]                                        | [bar]                         | [kg]   | [V/Hz]                                                                                     | [V/Hz]                                                                                     |
| Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C                                                                                               |                 |         |                                               |                               |        |                                                                                            |                                                                                            |
| <b>CF B</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally open<br> | G ¼             | 10      | 1.5                                           | 0.2...16                      | 0.43   | 20046924  | 20046970  |
|                                                                                                                                                                 | G ⅜             | 10      | 1.9                                           | 0.2...16                      | 0.40   | 20046925  | 20046971  |
|                                                                                                                                                                 | G ½             | 13      | 3.8                                           | 0.2...16                      | 0.54   | 20046927  | 20046972  |
|                                                                                                                                                                 | G ¾             | 20      | 8.5                                           | 0.2...16                      | 0.89   | 20046928  | 20046973  |
|                                                                                                                                                                 | G 1             | 25      | 12                                            | 0.2...16                      | 1.3    | 20046929  | 20046974  |
|                                                                                                                                                                 | G 1¼            | 40      | 23                                            | 0.2...16                      | 2.7    | 20046930  | 20046975  |
|                                                                                                                                                                 | G 1½            | 40      | 30                                            | 0.2...16                      | 3.0    | 20046931  | 20046976  |
|                                                                                                                                                                 | G 2             | 50      | 40                                            | 0.2...16                      | 4.5    | 20046932  | 20046978  |
|                                                                                                                                                                 | G 2½            | 50      | 40                                            | 0.2...16                      | 5.2    | 20046933  | 20046979  |

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.



3.) Pressure data: overpressure to atmospheric pressure




## Standard variant with stainless steel body

## Circuit function A

## Note:

Please note that the cable plug must be ordered separately, see ["8.5. Ordering chart accessories" on page 24](#) or separate data sheet for **Type 2518** ▶.

| Circuit function                                                                                                                                                    | Port connection | Orifice | K <sub>v</sub> value water <sup>1.) 2.)</sup> | Pressure range <sup>3.)</sup> | Weight | Article no.                                                                                  |                                                                                              |                                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|-----------------------------------------------|-------------------------------|--------|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
|                                                                                                                                                                     |                 | [mm]    | [m³/h]                                        | [bar]                         | [kg]   | 024/DC<br>[V/Hz]                                                                             | 024/50...60<br>[V/Hz]                                                                        | 230/50...60<br>[V/Hz]                                                                        |
| Seal material NBR, polyamide coil, medium temperature - 10 °C...+ 80 °C                                                                                             |                 |         |                                               |                               |        |                                                                                              |                                                                                              |                                                                                              |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G ¼             | 10      | 1.5                                           | 0.2...16                      | 0.43   | 322529  | 322530  | 322531  |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                           | 0.2...16                      | 0.40   | 322532  | 322533  | 322534  |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                           | 0.2...16                      | 0.54   | 221968  | 221969  | 221970  |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                           | 0.2...16                      | 0.86   | 221971  | 221972  | 221973  |
|                                                                                                                                                                     | G 1             | 20      | 8.5                                           | 0.2...16                      | 0.97   | 221974  | 221975  | 221976  |
|                                                                                                                                                                     | G 1             | 25      | 12                                            | 0.2...16                      | 1.3    | 221977  | 221978  | 221979  |
|                                                                                                                                                                     | G 1¼            | 25      | 12                                            | 0.2...16                      | 1.4    | 221980  | 221981  | 221982  |
|                                                                                                                                                                     | G 1½            | 40      | 30                                            | 0.2...16                      | 2.8    | 221983  | 221984  | 221985  |
|                                                                                                                                                                     | G 2             | 40      | 30                                            | 0.2...16                      | 3.0    | 221986  | 221987  | 221988  |
| Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C                                                                                                   |                 |         |                                               |                               |        |                                                                                              |                                                                                              |                                                                                              |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G ¼             | 10      | 1.5                                           | 0.2...16                      | 0.43   | 322535  | 322536  | 322537  |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                           | 0.2...16                      | 0.40   | 322538  | 322539  | 322540  |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                           | 0.2...16                      | 0.54   | 221989  | 221990  | 221991  |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                           | 0.2...16                      | 0.86   | 221992  | 221993  | 221994  |
|                                                                                                                                                                     | G 1             | 20      | 8.5                                           | 0.2...16                      | 0.97   | 221995  | 221996  | 221997  |
|                                                                                                                                                                     | G 1             | 25      | 12                                            | 0.2...16                      | 1.3    | 221998  | 221999  | 222000  |
|                                                                                                                                                                     | G 1¼            | 25      | 12                                            | 0.2...16                      | 1.4    | 222001  | 222002  | 222003  |
|                                                                                                                                                                     | G 1½            | 40      | 30                                            | 0.2...16                      | 2.8    | 222004  | 222005  | 222006  |
|                                                                                                                                                                     | G 2             | 40      | 30                                            | 0.2...16                      | 3.0    | 222007  | 222008  | 222009  |

| Circuit function                                                                                                                                                    | Port connection | Orifice | K <sub>v</sub> value<br>water <sup>1.) 2.)</sup> | Pressure<br>range <sup>3.)</sup> | Weight | Article no. |             |             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|--------------------------------------------------|----------------------------------|--------|-------------|-------------|-------------|
|                                                                                                                                                                     |                 | [mm]    |                                                  |                                  |        | 024/DC      | 024/50...60 | 230/50...60 |
|                                                                                                                                                                     |                 |         | [m <sup>3</sup> /h]                              | [bar]                            | [kg]   | [V/Hz]      | [V/Hz]      | [V/Hz]      |
| <b>Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C, with manual override</b>                                                                      |                 |         |                                                  |                                  |        |             |             |             |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br>   | G ¼             | 10      | 1.5                                              | 0.2...16                         | 0.43   | 323894 ☞    | o. r.       | 323968 ☞    |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                              | 0.2...16                         | 0.40   | 323971 ☞    | o. r.       | 323972 ☞    |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                              | 0.2...16                         | 0.54   | 323973 ☞    | o. r.       | 323975 ☞    |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                              | 0.2...16                         | 0.86   | 323977 ☞    | o. r.       | 323978 ☞    |
|                                                                                                                                                                     | G 1             | 25      | 12                                               | 0.2...16                         | 1.3    | 323979 ☞    | o. r.       | 323980 ☞    |
|                                                                                                                                                                     | G 1¼            | 25      | 1.4                                              | 0.2...16                         | 1.4    | 323982 ☞    | o. r.       | 323984 ☞    |
|                                                                                                                                                                     | G 1½            | 40      | 30                                               | 0.2...16                         | 2.8    | 323986 ☞    | o. r.       | 323987 ☞    |
|                                                                                                                                                                     | G 2             | 40      | 30                                               | 0.2...16                         | 3.0    | 323988 ☞    | o. r.       | 323989 ☞    |
| <b>Seal material EPDM, polyamide coil, medium temperature - 30 °C...+ 90 °C</b>                                                                                     |                 |         |                                                  |                                  |        |             |             |             |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br>   | G ¼             | 10      | 1.5                                              | 0.2...16                         | 0.43   | 322541 ☞    | 322542 ☞    | 322543 ☞    |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                              | 0.2...16                         | 0.40   | 322544 ☞    | 322545 ☞    | 322546 ☞    |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                              | 0.2...16                         | 0.54   | 222010 ☞    | 222011 ☞    | 222012 ☞    |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                              | 0.2...16                         | 0.86   | 222013 ☞    | 222014 ☞    | 222015 ☞    |
|                                                                                                                                                                     | G 1             | 20      | 8.5                                              | 0.2...16                         | 0.97   | 222016 ☞    | 222017 ☞    | 222018 ☞    |
|                                                                                                                                                                     | G 1             | 25      | 12                                               | 0.2...16                         | 1.3    | 222019 ☞    | 222020 ☞    | 222021 ☞    |
|                                                                                                                                                                     | G 1¼            | 25      | 12                                               | 0.2...16                         | 1.4    | 222022 ☞    | 222023 ☞    | 222024 ☞    |
|                                                                                                                                                                     | G 1½            | 40      | 30                                               | 0.2...16                         | 2.8    | 222025 ☞    | 222026 ☞    | 222027 ☞    |
|                                                                                                                                                                     | G 2             | 40      | 30                                               | 0.2...16                         | 3.0    | 222028 ☞    | 222029 ☞    | 222031 ☞    |
| <b>Flange connection according to DIN EN 1092-1, seal material FKM, medium temperature 0 °C...+ 120 °C</b>                                                          |                 |         |                                                  |                                  |        |             |             |             |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | Flange DN 25    | 25      | 12                                               | 0.2...16                         | 3.75   | 20131973 ☞  | 20131974 ☞  | 20131975 ☞  |
|                                                                                                                                                                     | Flange DN 32    | 40      | 23                                               | 0.2...16                         | 6.10   | 20131979 ☞  | 20131980 ☞  | 20131981 ☞  |
|                                                                                                                                                                     | Flange DN 40    | 40      | 30                                               | 0.2...16                         | 6.10   | 20131986 ☞  | 20131987 ☞  | 20131988 ☞  |

o. r. = on request


1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

**Circuit function B****Note:**

Please note that the cable plug must be ordered separately, see **"8.5. Ordering chart accessories"** on page 24 or separate data sheet for **Type 2518** ▶

| Circuit function                                                                                                                                                  | Port connection | Orifice | K <sub>v</sub> value<br>water <sup>1.) 2.)</sup> | Pressure<br>range <sup>3.)</sup> | Weight | Article no. |          |          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|--------------------------------------------------|----------------------------------|--------|-------------|----------|----------|
|                                                                                                                                                                   |                 | [mm]    |                                                  |                                  |        | 024/DC      | 024/50   | 230/50   |
|                                                                                                                                                                   |                 |         | [m <sup>3</sup> /h]                              | [bar]                            | [kg]   | [V/Hz]      | [V/Hz]   | [V/Hz]   |
| <b>Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C</b>                                                                                          |                 |         |                                                  |                                  |        |             |          |          |
| <b>CF B</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally open<br> | G ¼             | 10      | 1.5                                              | 0.2...16                         | 0.43   | 322547 ☞    | 322548 ☞ | 322549 ☞ |
|                                                                                                                                                                   | G ⅜             | 10      | 1.9                                              | 0.2...16                         | 0.40   | 322550 ☞    | 322551 ☞ | 322552 ☞ |
|                                                                                                                                                                   | G ½             | 13      | 3.8                                              | 0.2...16                         | 0.54   | 228387 ☞    | 228388 ☞ | 228389 ☞ |
|                                                                                                                                                                   | G ¾             | 20      | 8.5                                              | 0.2...16                         | 0.86   | 228390 ☞    | 228391 ☞ | 228392 ☞ |
|                                                                                                                                                                   | G 1             | 25      | 12                                               | 0.2...16                         | 1.3    | 228393 ☞    | 228394 ☞ | 228395 ☞ |
|                                                                                                                                                                   | G 1¼            | 25      | 12                                               | 0.2...16                         | 1.4    | 228396 ☞    | 228397 ☞ | 228398 ☞ |
|                                                                                                                                                                   | G 1½            | 40      | 30                                               | 0.2...16                         | 2.8    | 228399 ☞    | 228400 ☞ | 228401 ☞ |
|                                                                                                                                                                   | G 2             | 40      | 30                                               | 0.2...16                         | 3.0    | 228402 ☞    | 228403 ☞ | 228404 ☞ |

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet



2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

## ATEX/IECEx cable variant

## Note:

- The maximum medium temperature must never exceed the permitted temperature class (T4: +135 °C, T5: +100 °C, T6: +85 °C) minus 5 K.
- Delivery includes 3 metre cable.
- Refer to chapter “3. Approvals and conformities” on page 5 for more information about the approvals.

| Circuit function                                                                                                                                                    | Port connection | Orifice | K <sub>v</sub> value<br>water <sup>1.) 2.)</sup> | Pressure<br>range <sup>3.)</sup> | Weight                                                                                     | Article no.                                                                                  |                                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|--------------------------------------------------|----------------------------------|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
|                                                                                                                                                                     |                 |         |                                                  |                                  |                                                                                            | 024 / AC/DC                                                                                  | 230 / AC/DC                                                                                  |
|                                                                                                                                                                     |                 | [mm]    | [m <sup>3</sup> /h]                              | [bar]                            | [kg]                                                                                       | [V/Hz]                                                                                       | [V/Hz]                                                                                       |
| Seal material NBR, brass body, medium temperature - 10 °C...+ 80 °C                                                                                                 |                 |         |                                                  |                                  |                                                                                            |                                                                                              |                                                                                              |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br>   | G ¼             | 10      | 1.5                                              | 0.2...16                         | 0.62                                                                                       | 349656    | 349658    |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                              | 0.2...16                         | 0.59                                                                                       | 349660    | 349662    |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                              | 0.2...16                         | 0.84                                                                                       | 349690    | 349696    |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                              | 0.2...16                         | 1.2                                                                                        | 349717    | 349719    |
|                                                                                                                                                                     | G 1             | 25      | 12                                               | 0.2...16                         | 1.7                                                                                        | 349731    | 349734    |
|                                                                                                                                                                     | G 1¼            | 25      | 12                                               | 0.2...16                         | 1.8                                                                                        | 349737    | 349739    |
|                                                                                                                                                                     | G 1¼            | 40      | 23                                               | 0.2...16                         | 3.0                                                                                        | 349751    | 349754    |
|                                                                                                                                                                     | G 1½            | 40      | 30                                               | 0.2...16                         | 3.3                                                                                        | 349756    | 349758    |
|                                                                                                                                                                     | G 2             | 40      | 30                                               | 0.2...16                         | 3.5                                                                                        | 349760    | 349762    |
|                                                                                                                                                                     | G 2             | 50      | 40                                               | 0.2...16                         | 4.8                                                                                        | 349773    | 349775    |
| G 2½                                                                                                                                                                | 50              | 40      | 0.2...16                                         | 5.5                              | 349777  | 349778    |                                                                                              |
| Seal material FKM, stainless steel body, medium temperature 0 °C...+ 90 °C                                                                                          |                 |         |                                                  |                                  |                                                                                            |                                                                                              |                                                                                              |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G ¼             | 10      | 1.5                                              | 0.2...16                         | 0.62                                                                                       | 349665   | 349666   |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                              | 0.2...16                         | 0.59                                                                                       | 349669  | 349670  |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                              | 0.2...16                         | 0.84                                                                                       | 349707  | 349708  |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                              | 0.2...16                         | 1.2                                                                                        | 349724  | 349727  |
|                                                                                                                                                                     | G 1             | 25      | 12                                               | 0.2...16                         | 1.6                                                                                        | 349742  | 349744  |
|                                                                                                                                                                     | G 1¼            | 25      | 12                                               | 0.2...16                         | 1.7                                                                                        | 349747  | 349750  |
|                                                                                                                                                                     | G 1½            | 40      | 30                                               | 0.2...16                         | 3.1                                                                                        | 349765  | 349767  |
|                                                                                                                                                                     | G 2             | 40      | 30                                               | 0.2...16                         | 3.3                                                                                        | 349770  | 349771  |

1.) Measurement at +20 °C, 1 bar at the valve inlet and free outlet



2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

## ATEX/IECEx terminal box variant

## Note:

- The maximum medium temperature must never exceed the permitted temperature class (T4: +135 °C, T5: +100 °C, T6: +85 °C) minus 5 K.
- Refer to chapter "3. Approvals and conformities" on page 5 for more information about the approvals.

| Circuit function                                                                                                                                                    | Port connection | Orifice | K <sub>V</sub> value water <sup>1.) 2.)</sup> | Pressure range <sup>3.)</sup> | Weight | Article no. |             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|-----------------------------------------------|-------------------------------|--------|-------------|-------------|
|                                                                                                                                                                     |                 |         |                                               |                               |        | 024 / AC/DC | 230 / AC/DC |
|                                                                                                                                                                     |                 | [mm]    | [m³/h]                                        | [bar]                         | [kg]   | [V/Hz]      | [V/Hz]      |
| Seal material NBR, brass body, medium temperature - 10 °C...+ 80 °C                                                                                                 |                 |         |                                               |                               |        |             |             |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br>   | G ¼             | 10      | 1.5                                           | 0.2...16                      | 0.62   | 349657 ㉞    | 349659 ㉞    |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                           | 0.2...16                      | 0.59   | 349661 ㉞    | 349663 ㉞    |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                           | 0.2...16                      | 0.84   | 349691 ㉞    | 349697 ㉞    |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                           | 0.2...16                      | 1.2    | 349718 ㉞    | 349720 ㉞    |
|                                                                                                                                                                     | G 1             | 25      | 12                                            | 0.2...16                      | 1.7    | 349733 ㉞    | 349735 ㉞    |
|                                                                                                                                                                     | G 1¼            | 25      | 12                                            | 0.2...16                      | 1.8    | 349738 ㉞    | 349740 ㉞    |
|                                                                                                                                                                     | G 1¼            | 40      | 23                                            | 0.2...16                      | 3.0    | 349753 ㉞    | 349755 ㉞    |
|                                                                                                                                                                     | G 1½            | 40      | 30                                            | 0.2...16                      | 3.3    | 349757 ㉞    | 349759 ㉞    |
|                                                                                                                                                                     | G 2             | 40      | 30                                            | 0.2...16                      | 3.5    | 349761 ㉞    | 349763 ㉞    |
|                                                                                                                                                                     | G 2             | 50      | 40                                            | 0.2...16                      | 4.8    | 349774 ㉞    | 349776 ㉞    |
| Seal material FKM, stainless steel body, medium temperature 0 °C...+ 90 °C                                                                                          |                 |         |                                               |                               |        |             |             |
| <b>CF A</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally closed<br> | G ¼             | 10      | 1.5                                           | 0.2...16                      | 0.62   | 349664 ㉞    | 349667 ㉞    |
|                                                                                                                                                                     | G ⅜             | 10      | 1.9                                           | 0.2...16                      | 0.59   | 349668 ㉞    | 349671 ㉞    |
|                                                                                                                                                                     | G ½             | 13      | 3.8                                           | 0.2...16                      | 0.84   | 349705 ㉞    | 349709 ㉞    |
|                                                                                                                                                                     | G ¾             | 20      | 8.5                                           | 0.2...16                      | 1.2    | 349725 ㉞    | 349728 ㉞    |
|                                                                                                                                                                     | G 1             | 25      | 12                                            | 0.2...16                      | 1.6    | 349743 ㉞    | 349745 ㉞    |
|                                                                                                                                                                     | G 1¼            | 25      | 12                                            | 0.2...16                      | 1.7    | 349748 ㉞    | 349749 ㉞    |
|                                                                                                                                                                     | G 1½            | 40      | 30                                            | 0.2...16                      | 3.1    | 349766 ㉞    | 349768 ㉞    |
|                                                                                                                                                                     | G 2             | 40      | 30                                            | 0.2...16                      | 3.3    | 349769 ㉞    | 349772 ㉞    |

1.) Measurement at +20 °C, 1 bar at the valve inlet and free outlet



2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

## Compressor relief valve with brass body

## Note:

- Please note that the cable plug must be ordered separately, see **"8.5. Ordering chart accessories" on page 24** or separate data sheet for **Type 2518** ▶.
- The valve is open in the rest position. The medium also flows via the exhaust port on the solenoid.

| Circuit function                                                                                                                                                     | Port connection | Orifice | K <sub>v</sub> value<br>water <sup>1.) 2.)</sup> | Pressure<br>range <sup>3.)</sup> | Weight | Article no.                                                                              |                                                                                          |                                                                                          |                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|--------------------------------------------------|----------------------------------|--------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
|                                                                                                                                                                      |                 |         |                                                  |                                  |        | 024/DC                                                                                   | 024/50...60                                                                              | 110/50...60                                                                              | 230/50...60                                                                              |
|                                                                                                                                                                      |                 | [mm]    | [m³/h]                                           | [bar]                            | [kg]   | [V/Hz]                                                                                   | [V/Hz]                                                                                   | [V/Hz]                                                                                   | [V/Hz]                                                                                   |
| Seal material FKM, polyamide coil, medium temperature 0 °C...+ 90 °C, DN 10                                                                                          |                 |         |                                                  |                                  |        |                                                                                          |                                                                                          |                                                                                          |                                                                                          |
| <b>CF B</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally open<br><br>  | G 3/8           | 10      | 1.9                                              | 0.2...16                         | 0.43   | 330985  | 330986  | 330987  | 330988  |
|                                                                                                                                                                      | G 1/2           | 10      | 1.9                                              | 0.2...16                         | 0.40   | 330989  | 331007  | 331008  | 331009  |
|                                                                                                                                                                      |                 |         |                                                  |                                  |        |                                                                                          |                                                                                          |                                                                                          |                                                                                          |
| Seal material FKM, polyamide coil, medium temperature 0 °C...+ 90 °C, DN 13                                                                                          |                 |         |                                                  |                                  |        |                                                                                          |                                                                                          |                                                                                          |                                                                                          |
| <b>CF B</b><br>2/2-way solenoid valve<br>Servo-controlled<br>Normally open<br><br> | G 3/8           | 13      | 3.6                                              | 0.5...16                         | 0.58   | 310663  | 310662  | 310661  | 310659  |
|                                                                                                                                                                      | G 1/2           | 13      | 3.6                                              | 0.5...16                         | 0.54   | 310667  | 310666  | 310665  | 310664  |
|                                                                                                                                                                      |                 |         |                                                  |                                  |        |                                                                                          |                                                                                          |                                                                                          |                                                                                          |

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

## Further variants on request


|                                                                                     |                                                    |                                                                                     |                                                                                                                     |
|-------------------------------------------------------------------------------------|----------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
|  | <b>Material</b><br>Brass dezincification resistant |  | <b>Temperature</b><br>• EPDM variant up to + 100 °C with epoxy coil<br>• FKM variant up to + 120 °C with epoxy coil |
|  | <b>Process connection</b><br>NPT, Rc               |  | <b>Approval</b><br>Further information can be found in chapter <b>"3. Approvals and conformities" on page 5.</b>    |
|  | <b>Voltage</b><br>Further voltages                 |                                                                                     |                                                                                                                     |

## 8.5. Ordering chart accessories

## Cable plug Type 2518, form A according to DIN EN 175301 - 803

## Note:


For further variants see data sheet **Type 2518** ▶.

| Cable plug                                                                          | Dimensions                                                                          | Variant                                                                                             | Voltage         | Article no.                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------|----------------------------------------------------------------------------------------------|
|  |  | Without wiring (AC/DC)                                                                              | 0...250 V AC/DC | 314802  |
|                                                                                     |                                                                                     | With LED (AC/DC)                                                                                    | 12...24 V AC/DC | 314812  |
|                                                                                     |                                                                                     | With LED and varistor (AC/DC)                                                                       | 12...24 V AC/DC | 314820  |
|                                                                                     |                                                                                     | With rectifier, LED and varistor                                                                    | 12...24 V AC/DC | 314816  |
|                                                                                     |                                                                                     | Without wiring (AC/DC) with silicone seal for higher ambient temperature, e.g. steam variant (NA07) | 0...250 V AC/DC | 361687  |
|                                                                                     |                                                                                     |                                                                                                     |                 |                                                                                              |

Cable plug Type 2509, form A according to DIN EN 175301 - 803

Note:

- Without wiring (standard)
- Refer to data sheet **Type 2509** ▶ for more information about the cable plug.

| Cable plug                                                                        | Dimensions                                                                        | Variant        | Voltage         | Article no.                                                                                |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------------|-----------------|--------------------------------------------------------------------------------------------|
|  |  | Without wiring | 0...250 V AC/DC | 137943  |

Cable glands for ATEX/IECEx terminal box

Note:



- A polyamide cable gland is included in the scope of delivery. A nickel-plated brass variant can be ordered for a surcharge.
- Refer to **"7.1. Cable glands for ATEX/IECEx terminal box"** on page 15 for more information about Ex cable glands.
- Refer to **"7.2. Special tool to turn the terminal box"** on page 16 for more information about Special tool.

| Description                                                    | Article no.                                                                                  |
|----------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Ex cable gland, nickel-plated brass, 6...13 mm <sup>1)</sup>   | 773278  |
| Ex cable gland, polyamide, 7...13 mm <sup>1)</sup>             | 773277  |
| Set SC02-AC10: special tool <sup>2)</sup> incl. service manual | 293488  |

1.) Cable diameter

2.) Not included in the scope of delivery of the valve

Mounting bracket kit for DN 10

| Mounting bracket kit                                                                | Dimensions                                                                          | Description                                                      | Article no.                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
|  |  | Mounting bracket kit (consisting of mounting bracket and screws) | 365730  |