



# 316L Stainless Steel Double Ended DOT-Compliant Sample Cylinder, 1/4 in. FNPT, 300 cm<sup>3</sup>, 1800 psig (124 bar) with Sulfinert Coating

Part #: 316L-HDF4-300-12457

Specifications	
Body Material	316L Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/4 in.
Connection 1 Type	Female NPT
Connection 2 Size	1/4 in.
Connection 2 Type	Female NPT
Maximum Temperature, °F (°C)	800 (426)
Minimum Temperature, °F (°C)	-65 (-53)
Platings/Coatings	Sulfinert Coating
Testing	DOT-3E
eClass (4.1)	36030101
eClass (5.1.4)	36030101
eClass (6.0)	36030104
eClass (6.1)	36030104
eClass (10.1)	36030104
UNSPSC (4.03)	24111800
UNSPSC (10.0)	24111802
UNSPSC (11.0501)	24111802
UNSPSC (13.0601)	41111636
UNSPSC (15.1)	41111636
UNSPSC (17.1001)	24111800

## Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

---

*The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.*

## DOT-Compliant Cylinders

Achieve leak-tight chemical containment with Swagelok sample cylinders meeting DOT and Canadian Standards.



© 2026 Swagelok Company. All rights reserved.