



316L VAR VCR Face Seal Fitting, Flow Restrictor, 0.030 in. (0.762 mm) Minimum Nominal Opening

Part #: 6LV-4-VCR-6-DM-030P

Specifications	
Body Material	316L VAR
Cleaning Process	Ultrahigh-Purity Process Specification (SC-01)
Connection 1 Size	1/4 in.
Connection 1 Type	VCR® Metal Gasket Face Seal Fitting
Connection 2 Size	1/4 in.
Connection 2 Type	VCR® Metal Gasket Face Seal Fitting
Feature	Electropolished
Flow Restrictor	Yes
Minimum Nominal Opening	0.030 in. (0.762 mm)
eClass (4.1)	37020701
eClass (5.1.4)	37020590
eClass (6.0)	37020590
eClass (6.1)	37020590
eClass (10.1)	37020590
UNSPSC (4.03)	40142603
UNSPSC (10.0)	40141700
UNSPSC (11.0501)	40141700
UNSPSC (13.0601)	40141700
UNSPSC (15.1)	40141700
UNSPSC (17.1001)	40183103

Straights

VCR® straight union delivers robust, high-purity face seal connections—ideal for critical fluid systems requiring zero-leak performance.

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.



© 2026 Swagelok Company. All rights reserved.