



316L VIM-VAR UHP 2-Port Diaphragm Sealed Valve, 1/4 in. TBW, SC-01 Cleaned, NC Actuator

Part #: 6LVV-DPR11P-C

Specifications	
Body Material	316L VIM-VAR
Cleaning Process	Ultrahigh-Purity Process Specification (SC-01)
Connection 1 Size	1/4 in.
Connection 1 Type	Tube Butt Weld
Connection 2 Size	1/4 in.
Connection 2 Type	Tube Butt Weld
Connection 3 Size	1/4 in.
Connection 3 Type	Tube Butt Weld
CV Maximum	0.27
Maximum Temperature, °F (°C)	150 (65)
Minimum Temperature, °F (°C)	-10 (-23)
eClass (4.1)	37010206
eClass (5.1.4)	37011800
eClass (6.0)	37011801
eClass (6.1)	37011801
eClass (10.1)	37011801
UNSPSC (4.03)	40141600
UNSPSC (10.0)	40141621
UNSPSC (11.0501)	40141621
UNSPSC (13.0601)	40141621
UNSPSC (15.1)	40141621
UNSPSC (17.1001)	40183102

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Straight Pattern and Multiport

Fulfill your high-purity or ultrahigh-purity system needs with Swagelok diaphragm-sealed valves, which are available in a wide variety of sizes, materials, and configurations for a range of applications.



© 2026 Swagelok Company. All rights reserved.