



Brass Medium Flow Angle Pattern Metering Valve, 1/8 in. FNPT

Part #: B-2MA4

Specifications

Body Material	Silver-Mist Chrome-Plated Brass
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/8 in.
Connection 1 Type	Female NPT
Connection 2 Size	1/8 in.
Connection 2 Type	Female NPT
CV Maximum	0.03
Handle Style	Knurled
Maximum Temperature, °F (°C)	300 (148)
Minimum Temperature, °F (°C)	-10 (-23)
eClass (4.1)	37010203
eClass (5.1.4)	37010203
eClass (6.0)	37010203
eClass (6.1)	37010203
eClass (10.1)	37010203
UNSPSC (4.03)	40141602
UNSPSC (10.0)	40141600
UNSPSC (11.0501)	40141609
UNSPSC (13.0601)	40141600
UNSPSC (15.1)	40141600
UNSPSC (17.1001)	40183103

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Angle Pattern, Medium Flow

Make fine adjustments in low- or high- pressure, and low-, medium-, or high- flow applications with Swagelok metering valves that deliver accurate flow control when it matters in situations such as analytical or research applications.



© 2026 Swagelok Company. All rights reserved.