



Brass Instrumentation Quick Connect Stem without Valve, 0.3 Cv, 1/4 in. Male NPT

Part #: B-QC4-S-4PM

Specifications

Body Material	Brass
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/4 in.
Connection 1 Type	Male NPT
CV Maximum	0.3 - If coupled with a standard or reverse flow body, 0.4 - If coupled with a full flow body
Lubricant	Without lube on any components
O-Ring Material	Buna N (Standard)
Pressure Rating Coupled at Max Temp	250 PSIG @ 250 °F /17.2 BAR @ 121 °C
Pressure Rating Coupled at Room Temp	2000 PSIG @ 70 °F /137 BAR @ 21 °C
Series	QC4
eClass (4.1)	37110302
eClass (5.1.4)	37110302
eClass (6.0)	37020590
eClass (6.1)	37020590
eClass (10.1)	37020590
UNSPSC (4.03)	31163101
UNSPSC (10.0)	27121701
UNSPSC (11.0501)	27121701
UNSPSC (13.0601)	27121701
UNSPSC (15.1)	27121701
UNSPSC (17.1001)	27121701

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Stems

Make quick, easy connections with Swagelok quick connects for applications requiring frequent connections, minimal air inclusion and minimal spillage.



© 2026 Swagelok Company. All rights reserved.