



Maintenance Kit for Stainless Steel KPR Series Regulator, 0-10 psig (0.68 bar) and 0 to 25 psig (1.7 bar), 1/4 in. FNPT, 0.06 Cv, PCTFE Seat, Alloy X-750 Diaphragm

Part #: KPR1D00412A0-KIT

Specifications	
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Flow Coefficient	0.06 Cv
Maximum Inlet Pressure	25 psig (1.7 bar)
Ports	1/4 in. Female NPT
Pressure Control Range	0-10 psig (0.68 bar) and 0-25 psig (1.7 bar)
Sensing Mechanism	X750 Diaphragm
eClass (4.1)	37010602
eClass (5.1.4)	37019190
eClass (6.0)	37019102
eClass (6.1)	37019102
eClass (10.1)	37019102
UNSPSC (4.03)	41112404
UNSPSC (10.0)	40141616
UNSPSC (11.0501)	40141616
UNSPSC (13.0601)	40141616
UNSPSC (15.1)	40141616
UNSPSC (17.1001)	40141616

KPR Series Rebuild Kit

Maintenance kits include all wetted components, except for the regulator body and piston, wetted lubricant with MSDS, and instructions.

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.



© 2026 Swagelok Company. All rights reserved.