



Gap Inspection Gauge, 7/8 in., 20 mm and 22 mm Female Nuts

Part #: MS-IG-1410

Specifications	
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	7/8 in., 20 mm, 22 mm
Flow Restrictor	No
eClass (4.1)	37020718
eClass (5.1.4)	21172090
eClass (6.0)	21170207
eClass (6.1)	21170207
eClass (10.1)	21170207
UNSPSC (4.03)	27111800
UNSPSC (10.0)	41111619
UNSPSC (11.0501)	41111619
UNSPSC (13.0601)	41111619
UNSPSC (15.1)	41111619
UNSPSC (17.1001)	41111619

Gap Inspection Gauges

Gap inspection gauge verifies proper fitting assembly by checking ferrule placement—ideal for ensuring consistent, leak-tight tube connections.

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.



© 2026 Swagelok Company. All rights reserved.