



Snoop® Liquid Leak Detector, 2 oz. (59 mL) Bottle

Part #: MS-SNOOP-2OZ

Specifications

Container Size	2 oz. (59 mL)
Maximum Temperature, °F (°C)	200 (93)
Minimum Temperature, °F (°C)	27 (-2)
Temperature Range	27 to 200°F (-2 to 93°C)
eClass (4.1)	30040101
eClass (5.1.4)	30040101
eClass (6.0)	30040101
eClass (6.1)	30040101
eClass (10.1)	30040101
UNSPSC (4.03)	40141616
UNSPSC (10.0)	41111932
UNSPSC (11.0501)	41111932
UNSPSC (13.0601)	41111932
UNSPSC (15.1)	41111932
UNSPSC (17.1001)	41111932

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Snoop® Liquid Leak Detector

Sniff out even small, hard-to-reach leaks with Snoop® Liquid Leak Detector, featuring a flexible snoopers tube and sustained bubbling action.



© 2026 Swagelok Company. All rights reserved.