



# Stainless Steel Integral Bonnet Non-Rotating Stem Angle-Pattern Valve, 1/4 in. MNPT x 1/4 in. FNPT, 1900 psig (130 bar) Rupture Disc

Part #: SS-16DKM4-F4-A-1

Specifications	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/4 in.
Connection 1 Type	Male NPT
Connection 2 Size	1/4 in.
Connection 2 Type	Female NPT
CV Maximum	0.53
Maximum Temperature, °F (°C)	200 (93)
Max Temperature Pressure Rating	200°F @ 2580 PSIG /93°C @ 177 BAR
Minimum Temperature, °F (°C)	-20 (-28)
Rupture Disc	1900 psig (130 bar)
Stem Tip Material	PCTFE
Stem Type	Soft-Seat PCTFE
eClass (4.1)	37010201
eClass (5.1.4)	37010201
eClass (6.0)	37010203
eClass (6.1)	37010203
eClass (10.1)	37010203
UNSPSC (4.03)	40141602
UNSPSC (10.0)	40141602
UNSPSC (11.0501)	40141602
UNSPSC (13.0601)	40141602
UNSPSC (15.1)	40141602
UNSPSC (17.1001)	40141602

## Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

*The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.*

*Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.*

## Angle Pattern, Non-rotating Stem

Integral-bonnet needle valve are compact needle valves available in a full range of sizes, configurations, and materials for a variety of applications.



© 2026 Swagelok Company. All rights reserved.