



Stainless Steel 1-Piece 40G Series Ball Valve, 0.6 Cv, 1/4 in. Swagelok Tube Fitting, SC-11 Cleaned

The 40G series ball valve performs efficiently in various temperature conditions, resists thermal cycling effects, and minimizes leakage.

Part #: SS-42GS4-SC11

Specifications

Ball/Stem Material	Stainless Steel
Body Material	316 Stainless Steel
Cleaning Process	Special Cleaning and Packaging (SC-11)
Connection 1 Size	1/4 in.
Connection 1 Type	Swagelok® Tube Fitting
Connection 2 Size	1/4 in.
Connection 2 Type	Swagelok® Tube Fitting
CV Maximum	0.6
Flow Path	Standard
Flow Pattern	2-Way, Shutoff, Straight
Handle Color	Black
Handle Style	Lever
Low Emissions Certified	Yes
Lubricant	Nonhydrocarbon lubricants
Orifice	0.125 in /3.2 mm
Packing Material	Modified PTFE UHMWPE
Ring/Disc Material	Stainless Steel
Room Temperature Pressure Rating	2500 PSIG @ 100°F /172 BAR @ 37°C
Testing	Testing according to WS-22
eClass (4.1)	37010401
eClass (5.1.4)	37010401
eClass (6.0)	37010401
eClass (6.1)	37010401
eClass (10.1)	37010401
UNSPSC (4.03)	40141607
UNSPSC (10.0)	40141607
UNSPSC (11.0501)	40141607
UNSPSC (13.0601)	40141607
UNSPSC (15.1)	40141607
UNSPSC (17.1001)	40141607

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

2-Way Straight Pattern

The 40 series valves and the 40G series valves offer multiple actuator, flow path, and handle options. These valves allow for packing adjustments while remaining inline.



© 2026 Swagelok Company. All rights reserved.