



Stainless Steel 1-Piece 40 Series Ball Valve, 6.3 Cv, 1/2 in. Female ISO Tapered

Ensure optimal on-off service with the integrated instrumentation provided by the 40 series ball valve, featuring a two-way straight pattern design.

Part #: SS-45F8RT

Specifications	
Ball/Stem Material	Stainless Steel
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/2 in.
Connection 1 Type	Female ISO Tapered Thread
Connection 2 Size	1/2 in.
Connection 2 Type	Female ISO Tapered Thread
CV Maximum	6.3
Flow Path	Standard
Flow Pattern	2-Way, Shutoff, Straight
Handle Color	Black
Handle Style	Lever
Low Emissions Certified	Yes
Orifice	0.406 in /10.3 mm
Packing Material	PTFE
Ring/Disc Material	PTFE-Coated Stainless Steel
Room Temperature Pressure Rating	2500 PSIG @ 100°F /172 BAR @ 37°C
Service Class	General
Testing	Testing according to WS-22
eClass (4.1)	37010401
eClass (5.1.4)	37010401
eClass (6.0)	37010401
eClass (6.1)	37010401
eClass (10.1)	37010401
UNSPSC (4.03)	40141607
UNSPSC (10.0)	40141607
UNSPSC (11.0501)	40141607
UNSPSC (13.0601)	40141607
UNSPSC (15.1)	40141607
UNSPSC (17.1001)	40183103

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

2-Way Straight Pattern

The 40 series valves and the 40G series valves offer multiple actuator, flow path, and handle options. These valves allow for packing adjustments while remaining inline.

