





# Stainless Steel Metering Bellows Sealed Valve, Gasketed, Regulating Stem Tip, 1/4 in. TSW x 3/8 in. TBW

Part #: SS-4BMRG-TW

Specifications	
Actuator Type	Manual
Bellows Material	321 Stainless Steel
Body Material	316 Stainless Steel
Body Seal	Gasket with metal seat
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/4 in.
Connection 1 Type	Tube Socket Weld
Connection 2 Size	3/8 in.
Connection 2 Type	Tube Butt Weld
CV Maximum	0.3
Flow Pattern	Straight (2-way)
Gasket	Silver-Plated 316 SS Gasket
Handle Color	Not Applicable
Handle Style	Silver-mist Chrome-plated 313 SS
Maximum Temperature, °F (°C)	600 (315)
Max Temperature Pressure Rating	600°F @ 300 PSIG /315°C @ 20.6 BAR
Minimum Temperature, °F (°C)	-20 (-28)
Room Temperature Pressure Rating	700 PSIG @ 100°F /48.2 BAR @ 37°C
Service Class	General
Stem Tip Material	Chrome Plated 316 Stainless Steel
Stem Type	Regulating
Surface Finish	Standard
Testing	Helium leak testing according to SCS-00020
eClass (4.1)	37010201
eClass (5.1.4)	37010201
eClass (6.0)	37010201
eClass (6.1)	37010201
eClass (10.1)	37010201
UNSPSC (4.03)	40141600
UNSPSC (10.0)	40141609
UNSPSC (11.0501)	40141609
UNSPSC (13.0601)	40141609
UNSPSC (15.1)	40141609
UNSPSC (17.1001)	40183102

## Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

*The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.*

*Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.*

## Straight Pattern

Isolate system fluids and achieve reliable, leak-tight performance with Swagelok bellows valves, which use a packless design and a welded seal. Bellows valves are ideal for applications where the seal to atmosphere is critical, and we offer multiple options for general and high-purity service.



# **Stainless Steel Metering Bellows Sealed Valve, Gasketed, Regulating Stem Tip, 1/4 in. TSW x 3/8 in. TBW**

**Part #: SS-4BMRG-TW**



© 2026 Swagelok Company. All rights reserved.