

Stainless Steel Rising Plug Screwed-Bonnet Needle Valve, Acetal Seat, 1/4 in. FNPT, Gauge Port

Part #: SS-4PDGF4

Specifications	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/4 in.
Connection 1 Type	Female NPT
Connection 2 Size	1/4 in.
Connection 2 Type	Female NPT
CV Maximum	0.63
Feature	1/4" Gauge Port
Low Emissions Certified	Yes
Maximum Temperature, °F (°C)	250 (121)
Minimum Temperature, °F (°C)	-20 (-28)
eClass (4.1)	37010201
eClass (5.1.4)	37010201
eClass (6.0)	37010203
eClass (6.1)	37010203
eClass (10.1)	37010203
UNSPSC (4.03)	40141602
UNSPSC (10.0)	40141602
UNSPSC (11.0501)	40141602
UNSPSC (13.0601)	40141602
UNSPSC (15.1)	40141602
UNSPSC (17.1001)	40183103

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Straight Pattern with Gauge Port

Rising plug valves offer a roddable, straight-through orifice, gauge ports, and a variety of material options for system versatility.



© 2026 Swagelok Company. All rights reserved.