



Stainless Steel Lift Check Valve, 0.30 Cv, 6 mm Swagelok Tube Fitting

Part #: SS-53S6MM

Specifications	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	6 mm
Connection 1 Type	Swagelok® Tube Fitting
Connection 2 Size	6 mm
Connection 2 Type	Swagelok® Tube Fitting
CV Maximum	0.3
Room Temperature Pressure Rating	6000 PSIG @ 100°F /413 BAR @ 37°C
Surface Finish	Standard
Testing	No Optional Testing
eClass (4.1)	37010801
eClass (5.1.4)	27300400
eClass (6.0)	27292001
eClass (6.1)	27292001
eClass (10.1)	27292001
UNSPSC (4.03)	40141622
UNSPSC (10.0)	40141634
UNSPSC (11.0501)	40141634
UNSPSC (13.0601)	40141634
UNSPSC (15.1)	40141659
UNSPSC (17.1001)	40183101

Fixed Pressure

Swagelok lift check valves feature a unique bonnet design that enables the use of gravity to limit reverse flow under pressures up to 6000 psig (413 bar) and temperatures up to 900°F (482°C).

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.



© 2026 Swagelok Company. All rights reserved.