



Stainless Steel Bellows Sealed Valve, Gasketed, PCTFE Stem Tip, 1/2 in. Swagelok Tube Fitting, SC-11 Cleaned, NC Actuator

Part #: SS-8BK-1C

Specifications	
Actuator Model	1 Series
Actuator Operation Mode	Normally Closed Spring Return
Actuator Type	Pneumatic
Bellows Material	321 Stainless Steel
Body Material	316 Stainless Steel
Body Seal	Gasket with soft seat
Cleaning Process	Special Cleaning and Packaging (SC-11)
Connection 1 Size	1/2 in.
Connection 1 Type	Swagelok® Tube Fitting
Connection 2 Size	1/2 in.
Connection 2 Type	Swagelok® Tube Fitting
CV Maximum	0.96
Flow Pattern	Straight (2-way)
Gasket	PTFE-Coated 316 SS Gasket
Maximum Temperature, °F (°C)	200 (93)
Max Temperature Pressure Rating	200°F @ 125 PSIG /93°C @ 8.6 BAR
Minimum Temperature, °F (°C)	-20 (-28)
Room Temperature Pressure Rating	125 PSIG @ 100°F /8.6 BAR @ 37°C
Service Class	General
Stem Tip Material	PCTFE
Stem Type	Conical
Surface Finish	Standard
Testing	Helium leak testing according to SCS-00020
eClass (4.1)	37010201
eClass (5.1.4)	37010201
eClass (6.0)	37010201
eClass (6.1)	37010201
eClass (10.1)	37010201
UNSPSC (4.03)	40141600
UNSPSC (10.0)	40141609
UNSPSC (11.0501)	40141609
UNSPSC (13.0601)	40141609
UNSPSC (15.1)	40141609
UNSPSC (17.1001)	40183102

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Straight Pattern, with Actuator

Isolate system fluids and achieve reliable, leak-tight performance with Swagelok bellows valves which use a packless design and a welded seal. Bellows valves are ideal for applications where the seal to atmosphere is critical, and we offer multiple options for general and high-purity service.



Stainless Steel Bellows Sealed Valve, Gasketed, PCTFE Stem Tip, 1/2 in. Swagelok Tube Fitting, SC-11 Cleaned, NC Actuator

Part #: SS-8BK-1C



© 2026 Swagelok Company. All rights reserved.