



Stainless Steel 3-Piece 60 Series Fire Series Ball Valve, Reinforced PTFE Seats, 1/2 in. FNPT

Fire Series 2-way 316 SS valve with 1/2" FNPT ports, PTFE seats, and swing-out design for reliable shutoff in high-temperature, fire-tested applications.

Part #: SS-A63TF8

Specifications	
Ball/Stem Material	Stainless Steel
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/2 in.
Connection 1 Type	Female NPT
Connection 2 Size	1/2 in.
Connection 2 Type	Female NPT
CV Maximum	12
Fastener Material	316 Stainless Steel
Feature	Fire Series
Flange Seal Material	Grafoil®
Flow Pattern	2-Way, Shutoff, Straight
Handle Color	Red
Handle Style	Lever
Room Temperature Pressure Rating	2200 PSIG @ 100°F /151 BAR @ 37°C
Seat Material	Reinforced PTFE
Seat Spring Material	316 Stainless Steel
Service Class	Fire Service
Stem Bearing Material	Alloy X750
Testing	Testing according to WS-22
eClass (4.1)	37010401
eClass (5.1.4)	37010401
eClass (6.0)	37010401
eClass (6.1)	37010401
eClass (10.1)	37010401
UNSPSC (4.03)	40141607
UNSPSC (10.0)	40141607
UNSPSC (11.0501)	40141607
UNSPSC (13.0601)	40141607
UNSPSC (15.1)	40141607
UNSPSC (17.1001)	40183106

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Fire Series 2-Way Straight Pattern

Fire-rated 2-way valve with swing-out design and spring-loaded seats—built for safety, durability, and low-maintenance in critical process systems.

