



316L Stainless Steel Convuluted (FM) Hose, 3/8 in., 316L Stainless Steel Braid, 3/8 in. Tube Fitting, 18 in. (45.7 cm) Length

Part #: SS-FM6SL6SL6-18

Specifications

Body Material	316L Stainless Steel
Connection 1 Size	3/8 in.
Connection 1 Type	Swagelok® Tube Fitting
Connection 2 Size	3/8 in.
Connection 2 Type	Swagelok® Tube Fitting
End Connection Material	316 Stainless Steel
Hose Length	18 in.
Hose Size	3/8 in.
Maximum Temperature, °F (°C)	850 (454)
Max Temperature Pressure Rating	1120 psig (77.1 bar)
Minimum Temperature, °F (°C)	-325 (-198)
Room Temperature Pressure Rating	2000 PSIG @ 100°F /137 BAR @ 37°C
eClass (4.1)	37110202
eClass (5.1.4)	37110202
eClass (6.0)	37110000
eClass (6.1)	37110000
eClass (10.1)	37110000
UNSPSC (4.03)	40142009
UNSPSC (10.0)	40142000
UNSPSC (11.0501)	40142000
UNSPSC (13.0601)	40142000
UNSPSC (15.1)	40142000
UNSPSC (17.1001)	39120000

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

FM Series Flexible Metal Hose

Overcome your high-temperature, vacuum, medium-pressure, or corrosive environmental challenges with a variety of Swagelok stainless steel and braided hose options.



© 2026 Swagelok Company. All rights reserved.