



Stainless Steel Full Flow Quick Connect Stem without Valve, 7.1 Cv, 3/8 in. Male NPT

Part #: SS-QF8-S-6PM

Specifications	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	3/8 in.
Connection 1 Type	Male NPT
CV Maximum	7.1 - Coupled with a body
Lubricant	Without lube on any components
O-Ring Material	Fluorocarbon FKM
Pressure Rating Coupled at Max Temp	100 PSIG @ 400 °F /6.8 BAR @ 204 °C
Pressure Rating Coupled at Room Temp	6000 PSIG @ 70 °F /413 BAR @ 21 °C
Series	QF8
eClass (4.1)	37110302
eClass (5.1.4)	37110302
eClass (6.0)	37020500
eClass (6.1)	37020500
eClass (10.1)	37020500
UNSPSC (4.03)	31163101
UNSPSC (10.0)	27121701
UNSPSC (11.0501)	27121701
UNSPSC (13.0601)	27121701
UNSPSC (15.1)	27121701
UNSPSC (17.1001)	27121701

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Stems

Achieve unrestricted flow and easy maintenance with Swagelok full-flow quick-connects for your transfer, drain, and vent systems.



© 2026 Swagelok Company. All rights reserved.