



Stainless Steel Miniature Quick Connect Stem without Valve, 0.06 Cv, 1/16 in. Swagelok Tube Fitting

Part #: SS-QM2-S-100

Specifications	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/16 in.
Connection 1 Type	Swagelok® Tube Fitting
CV Maximum	0.06 - If coupled with a full flow body, 0.06 - If coupled with a standard or reverse flow body
Lubricant	Without lube on any components
O-Ring Material	Fluorocarbon FKM
Pressure Rating Coupled at Max Temp	100 PSIG @ 400 °F /6.8 BAR @ 204 °C
Pressure Rating Coupled at Room Temp	4000 PSIG @ 70 °F /275 BAR @ 21 °C
Series	QM2
eClass (4.1)	37110302
eClass (5.1.4)	37110302
eClass (6.0)	37020500
eClass (6.1)	37020500
eClass (10.1)	37020500
UNSPSC (4.03)	31163101
UNSPSC (10.0)	27121701
UNSPSC (11.0501)	27121701
UNSPSC (13.0601)	27121701
UNSPSC (15.1)	27121701
UNSPSC (17.1001)	27121701

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

Stems

Make quick, easy connections with Swagelok miniature quick connects for applications, like laboratories, requiring frequent connections and reduced spillage and air inclusion with low dead volume, in a limited space.



© 2026 Swagelok Company. All rights reserved.