



Stainless Steel Low Pressure Proportional Relief Valve, 1/2 in. MNPT x 1/2 in. Swagelok Tube Fitting

Part #: SS-RL4M8S8

Specifications	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/2 in.
Connection 1 Type	Male NPT
Connection 2 Size	1/2 in.
Connection 2 Type	Swagelok® Tube Fitting
Handle Style	No Handle
Room Temperature Pressure Rating	225 PSIG @ 100°F /15.5 BAR @ 37°C5
Seal Material	Fluorocarbon FKM
Service Class	Low Pressure
Testing	No Optional Testing
eClass (4.1)	37010901
eClass (5.1.4)	37019901
eClass (6.0)	37010901
eClass (6.1)	37019901
eClass (10.1)	37019901
UNSPSC (4.03)	40141606
UNSPSC (10.0)	40141606
UNSPSC (11.0501)	40141606
UNSPSC (13.0601)	40141606
UNSPSC (15.1)	40141606
UNSPSC (17.1001)	40183109

Low Pressure Relief Valve

Obtain over-pressure protection for a variety of applications with Swagelok proportional relief valves with easy external set pressure adjustments.

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.



© 2026 Swagelok Company. All rights reserved.