



316L VAR UHP Inline Gas Filter, 3 in. (76.2 mm), 1/4 in. Male VCR Fitting, SC-01 Cleaned, 30 L/m

Part #: SS-SCF3-VR4-P-30

Specifications

Body Material	316L VAR
Cleaning Process	Ultrahigh-Purity Process Specification (SC-01)
Connection 1 Size	1/4 in.
Connection 1 Type	Face Seal (Metal Gasket) Male VCR
Connection 2 Size	1/4 in.
Connection 2 Type	Face Seal (Metal Gasket) Male VCR
Maximum Flow Rate	30 std L/m
Maximum Temperature, °F (°C)	122°F (50°C)
eClass (4.1)	37110200
eClass (5.1.4)	36102090
eClass (6.0)	36102000
eClass (6.1)	36102000
UNSPSC (4.03)	40142603
UNSPSC (10.0)	40161516
UNSPSC (11.0501)	40161516
UNSPSC (13.0601)	40161516
UNSPSC (15.1)	40161516
UNSPSC (17.1001)	40161516

Inline Gas Filters

Remove particulate contaminants with Swagelok filters in demanding gas or liquid applications where purity is a requirement, and space is limited.

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.



© 2026 Swagelok Company. All rights reserved.