



Stainless Steel Excess Flow Valve, 1/4 in. Swagelok Tube Fitting

Part #: SS-XSS4

Specifications	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/4 in.
Connection 1 Type	Swagelok® Tube Fitting
Connection 2 Size	1/4 in.
Connection 2 Type	Swagelok® Tube Fitting
CV Maximum	0.5
Spring Trip Range U.S. gal/min (L/min)	3.9 to 5.8 (14.7 to 21.9)
eClass (4.1)	37010906
eClass (5.1.4)	37011902
eClass (6.0)	22560307
eClass (6.1)	22560307
eClass (10.1)	22560307
UNSPSC (4.03)	40141622
UNSPSC (10.0)	40141600
UNSPSC (11.0501)	40141600
UNSPSC (13.0601)	40141600
UNSPSC (15.1)	40141600
UNSPSC (17.1001)	40183101

Fixed Pressure

Stop uncontrolled release of system media if your downstream line ruptures with the Swagelok excess flow valve. Our excess flow valves have a slotted poppet which moves to the tripped position when excess flow occurs downstream, then resets when pressure equalizes.

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection.

When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.



© 2026 Swagelok Company. All rights reserved.