



Specification	
Fluid	
Set Press.	MPa
Temp.	
Flow Rate	

No.	Name of Parts	Material	部品名	材質	QTY
15	Rivet	Carbon Steel	打込みねじ	S15C	2
14	Name Plate	Stainless Steel	銘板	SUS304	1
13	Gasket	PTFE	ガスケット	PTFE	1
12	Gasket	PTFE	ガスケット	PTFE	1
11	Cap	Brass	キャップ	C3604	1
10	Lock Nut	Brass	ロックナット	C3604	1
9	Adjusting Screw	Brass	調節ねじ	C3604	1
8	Top Spring Plate	Brass	上部ばね受	C3604	1
7	Bottom Spring Plate	Brass	下部ばね受	C3604	1
6	Spring	Stainless Steel	調節ばね	SUS304	1
5	Spindle	Brass	弁棒	C3604	1
4	Valve	Stainless Steel	弁体	SUS304	1
3	Valve Seat	Stainless Steel	弁座	SUS304	1
2	Valve Case	Bronze	弁箱	CAC406	1
1	Spring Case	Bronze	ばね箱	CAC406	1

Size	d	L	H1	H	Weight (kg)
15A	Rc 1/2	34	41	129	0.7
20A	Rc 3/4	38	45	131	0.9
25A	Rc 1	43	51.5	145	1.2
32A	Rc 1 1/4	50	63.5	184	1.9
40A	Rc 1 1/2	60	64.5	210	2.8
50A	Rc 2	75	80	250	4.9

TYPE AL-260 RELIEF VALVE  
リリ - フ弁

Approval	K. Yoshino
Check	T. Mori
Drawing	T. Nagasaka
Drawing No.	Y-1020-19D1
Date	21 OCT. 2004

**Yoshitake**  
INC.