


BJ-1,UB-11

- Belloys
- Sleeve
- Ball
- Single type
- Double type
- PTEE
- Copper pipe

■Features

- 1. Capable of absorbing every type of displacement all together, such as expansion, compression, rotation and twist.
- 2. Suitable to the place where piping space is limited.
- 3. Outstanding heat, oil, corrosion and wear resistance by original packing.
- 4. Able to make the anchor and guide smaller, also lessen them.
- 5. It is strong enough to withstand water hammer, impact, etc.
- 6. Complies with SHASE-S007 Mechanical Type Displacement Absorption Joints.(BJ-1,UB-11)



BJ-1



UB-11


■Specifications

Model		BJ-1	UB-11
Application		Steam, Air, Cold and hot water, Oil, Other non-dangerous fluids	
Maximum pressure		1.0MPa	
Maximum temperature		220℃	
Maximum displacement angle		20°	
Material	Body	Cast carbon steel	
	Ball	Carbon steel (HCr plating)	
	Packing	PTFE	
Connection		JIS 10K RF flanged	

■Dimensions (mm) and Weights (kg)


· BJ-1

Nominal size	L	L ₁	φ Do	Displacement angle θ	Weights
50A	190	110	160	20°	11
65A	220	130	175	20°	14.5
80A	235	130	195	20°	17
100A	270	150	232	20°	26
125A	310	170	270	20°	38
150A	370	190	310	20°	56
200A	430	220	380	20°	84
250A	480	240	460	20°	135



BJ-1

UB-11



Nominal size	L	L ₁	φDo	Displacement angle θ	Weights
50A	190	110	160	20°	12
65A	220	130	175	20°	17
80A	235	130	195	20°	18
100A	270	150	232	20°	30
125A	310	170	275	20°	45
200A	430	220	380	20°	90