

BSV-10S, 10ST Bellows Valve

Advancing the Hydrogen and Decarbonized Society
Introducing Our New Stainless Steel Bellows Valve



Stainless Steel Wette Parts


SUS316 & PTFE Wetted
Parts for Corrosive Fluid
Applications

PTFE Gasket


PTFE-Based Bonnet
Gasket for Hydrogen Leak
Prevention

Selectable Valve Seat Options

Two Seat Options Available
Metal Seat / Soft Seat (PTFE)



Metal Seat



Soft Seat (PTFE)

Suitable for Various Fluids Used in Hydrogen Production Processes
(Please contact us regarding operating conditions.)

YOSHITAKE


■Features

01.

Constant Handle Height Design

02.

Built-in Handle Lock Function



03.

Easy Valve Position Identification with "O" (Open) and "S" (Shut) Indicators

04.

Double-Seal Design for Leakage Prevention

05.


The bellows features a double-layer construction made of titanium-stabilized stainless steel, providing high strength and long service life.

■Specifications

Model		BSV-10S	BSV-10ST
Applicable Fluids		Steam, air, water, oil, other non-dangerous fluids and hydrogen ※1	
Maximum Operating Pressure		1.4MPa	
Maximum Operating Temperature		300℃	183℃
Materials	Body	Stainless Steel (Equivalent to SCS14A)	
	Bonnet	Stainless Steel (Equivalent to SCS14A)	
	Spindle	SUS316	
	Valve	SUS316	SUS316+PTFE
	Bellows	Stainless Steel (Equivalent to SUS316Ti)	
Connection		JIS 10K RF	

*1 For fluids not listed above, please contact us.

Size	(mm)								
	15A	20A	25A	32A	40A	50A	65A	80A	100A
L	108	117	127	140	165	203	216	241	292
H	189	189.5	193	198.5	239	240	256	274.5	355
D	125	125	125	125	180	180	200	200	250



For safe use of this product, please read the instruction manual before use.

Images shown in this catalog are for illustrative purposes only. Specifications and contents are subject to change without notice. Unauthorized reproduction of this catalog is prohibited.
Copyright(C) Yoshitake Inc. All Rights Reserved.



Yoshitake Inc.
Engineering Division

955-5 Miyamae, Iruka-Shinden, Komaki, Aichi 485-0084,
Japan TEL: +81-568-75-7551 FAX: +81-568-75-7563

valvesgo.com