

FS-II-P

Kawaki

Plain	Flap	Ball	Spinner
Stainless	Mica plate	Protective wire mesh	With protective cover
Scale description			

■Features

1. To prevent danger, a protective cover is attached to a glass window as standard.
2. Flow scale is also available (Option).



■Specifications

Application		Cold and hot water, Oil			
Maximum working pressure		0.7 MPa			
Max. temperature		80°C			
Material	Body	Ductile cast iron		Stainless steel	
	Glass	Hardened glass			
	Ball	Brass		Stainless steel	
Nominal size		10-50A	10-150A	10-40A	10-150A
Connection		JIS Rc screwed	JIS 10K FF flanged	JIS Rc screwed	JIS 10K FF flanged



■Dimensions (mm) and Weights (kg)

· Screwed type

Nominal size	L	H	S	P	Weight
10A	100	74	40	71	0.9
15A	100	74	40	71	1.0
20A	110	92	46	78	1.4
25A	120	94	52	84	1.8
32A	150	132	70	110	4.0
40A	150	132	70	110	4.0
50A	160	142	70	110	7.5

· Flanged type

Nominal size	C	D	H	S	P	L	Weight
10A	65	90	80	40	80	160	3.0
15A	70	95	80	40	80	160	3.0
20A	75	100	100	46	88	180	3.9
25A	90	125	102	52	96	180	5.4
32A	100	135	140	75	120	180	8.0
40A	105	140	140	75	120	180	8.0
50A	120	155	150	80	128	220	11.0
65A	140	175	200	120	180	270	19.0
80A	150	185	200	120	180	270	21.0
100A	175	210	230	160	240	320	33.0
125A	210	250	270	180	260	380	43.0
150A	240	280	300	200	300	420	69.0



Please fill in the usage conditions on the specification sheet on P. 7-12 when ordering.