

GD-9N

Direct type	Pilot type	Piston	Diaphragm
Bellows	Internal sensing	External sensing	Stainless steel
With handle	Built-in strainer	Low pressure	Remote
Valve leakage 0	Nylon		




GD-9N

■Features

1. Compact and lightweight.
2. Easy to adjust wide pressure range by handle.
3. The valve can be fitted with a pressure gauge to measure the outlet pressure.

■Specifications

Model		GD-9N	
Nominal size		25A	8A, 10A, 15A, 20A
Application		Air, Other non-dangerous fluids	
Inlet pressure		0.1-1.0 MPa	
Reduced pressure		0.05-0.85 MPa	0.05-0.7 MPa
Application temperature		5-60°C	
Material	Body	Aluminum die casting	
	Valve	NBR	
	Diaphragm	NBR	
Relief pressure		Set pressure + 0.05 MPa	
Connection		JIS Rc screwed	
Structure		Relief type	
Valve seat leakage		No leakage	








GD-9N

- The product cannot be used for toxic and flammable gases.
- Available with dedicated brackets.
- Available with 6 types pressure gauge.
 8A, 10A- Outer diameter ϕ 37.5-Max. 1.0 MPa or 0.4 MPa or 0.2 MPa
 15A, 20A, 25A- Outer diameter ϕ 42.5-Max. 1.0 MPa or 0.4 MPa or 0.2 MPa

■Dimensions (mm) and Weights (kg)

Nominal size	d	L	H	H ₁	Pressure gauge connection port	Weight
8A	Rc 1/4	53	93.9	23.5	Rc 1/8	0.19
10A	Rc 3/8	53	110.5	27	Rc 1/8	0.34
15A	Rc 1/2	70	133.5	33.5	Rc 1/8	0.58
20A	Rc 3/4	75	135	33.5	Rc 1/8	0.6
25A	Rc 1	95	175.6	46	Rc 1/8	1.22

Flow Characteristic Chart for each Nominal Sizes [Air: Inlet pressure 0.7MPa]



* No constraint in minimum adjustable flow rate.

Pressure Characteristic Chart for each Nominal Sizes [Air: Inlet pressure 0.7MPa, Reduced pressure 0.2MPa, Flow rate 20L/min (Standard condition)]

