

GLV-10F,20F

- 10K
- 16K
- 20K
- Bronze
- Ductile

■Specification

Model		GLV-10F	GLV-20F
Application		Steam, Air, cold and hot water, oil, other non-dangerous fluid	
Nominal Size		15A-50A	
Maximum pressure		1.4 MPa *1	2.8 MPa *1
Maximum temperature		300°C *1	300°C *1
Material	Body	Ductile cast iron	
	Bonnet	Ductile cast iron	
	Valve	SUS403	SUS304+Stellite
Connection		JIS 10KFF	JIS 20KRF

* The relation between pressure and temperature depend on P.2-3 JIS B 2051, pressure-temperature standard.
* Valve is closed at the time of shipment from the factory.

■Dimensions (mm) and Weights (kg)

· GLV-10F

Nominal Size	d	D1	L	H	I	Weights (kg)
15A	15	83	108	126	6	2.1
20A	20	105	117	135	7	2.6
25A	25	112	127	150	8	4.1
32A	32	132	140	162	9	5.6
40A	40	132	165	183	11	6.8
50A	50	132	203	186	13	9.1

· GLV-20F

Nominal Size	d	D1	L	H	I	Weights (kg)
15A	15	83	110	126	6	2.2
20A	20	105	120	135	7	2.8
25A	25	112	130	150	8	4.2
32A	32	132	160	162	9	5.8
40A	40	132	180	183	11	6.9
50A	50	180	230	186	13	9.8

