

KBLV-2SF

Features


1. Body of the ball valve is made of stainless steel.
2. Full bore type ball valve.
3. KA type actuator use NAMUR dimensions.
4. Double-acting actuator.

Specifications

Model	KBLV-2SF
Nominal size	15 - 100A
Application fluid	Steam, air, water, oil and other non-dangerous fluids
Connection	JIS 10K RF flanged ASME Class 150 flanged EN PN16 flanged
Maximum pressure	According to the pressure-temperature rating
Maximum temperature	
Valve material	Stainless steel
Seat material	PTFE
Operating fluid	Air, nitrogen gas
Operating pressure	0.4 - 0.8MPa
Ambient temperature	-20 to 80°C
Operation	Double action, 90°



Pressure and Temperature Rating



Dimensions (mm) and Weight (kg)

Nominal size	L		H	Weight		
	JIS 10K ANSI 150lb	EN PN16		JIS 10K	ANSI 150lb	EN PN16
15A	108	130	161	3.1	2.8	3.3
20A	117	150	166	3.5	3.1	4
25A	127	160	197	5.5	4.5	6
32A	140	180.3	218	7.1	6	8.1
40A	165	200	241	9	8.4	10
50A	178	230	261	11.8	11.7	13.4
65A	190	290	300	17.8	17.7	20.1
80A	203	310	333	24.7	25	27.6
100A	229	350	369	33.5	37.7	38

