




Size	d	H	L	Flange BSEN PN16				Weight (kg)
				D	C	g	n-h	
15A	15	56	130	95	65	46	4-14	2.1
20A	20	56	150	105	75	56	4-14	2.7
25A	25	67	160	115	85	65	4-14	3.8
32A	32	76	180	140	100	76	4-19	5.5
40A	40	89	200	150	110	84	4-19	7.4
50A	50	96	230	165	125	99	4-19	9.5
65A	65	104	290	185	145	118	4-19	15.0
80A	80	124	310	200	160	132	8-19	20.0
100A	100	161	350	220	180	156	8-19	29.0
125A	125	174	400	250	210	184	8-19	41.0
150A	150	197	480	285	240	211	8-23	66.0
200A	200	248	600	340	295	266	12-23	111.0
250A	250	295	730	405	355	319	12-28	196.0

8	Gasket	Graphite+CrNi	ガスケット	Graphite+CrNi	Graphite+CrNi	1
7	Hexagon Bolt	Steel	六角ボルト	Steel	Steel	1set
6	Valve	Stainless Steel	弁体	X20Cr13 1.4021	SUS420J1	1
5	Spring	Stainless Steel	スプリング	X17CrNi16-2 1.4057	SUS431	1
4	Stem	Stainless Steel	ステム	X20Cr13 1.4021	SUS420J1	1
3	Bonnet	Cast Iron	ボンネット	EN-GJL-250 JL1040	FC250	1
2	Valve Seat	Stainless Steel	弁座	X20Cr13 1.4021	SUS420J1	1
1	Body	Cast Iron	弁箱	EN-GJL-250 JL1040	FC250	1
No.	Name of Parts	Material	部品名	材質	J I S相当材質	Q. TY

Specification	
Fluid	
Press.	MPa
Temp.	℃

TYPE SCV-4EN CHECK VALVE 逆止弁	
Approval	T. Shinjo
Check	N. Yabutani
Drawing	Y. Wakamatsu
Drawing No.	Y-1229-0846-1B
Date	12 JUL. 2017
Yoshitake INC.	