

YBF-1E,2E

Bellocs

Sleeve

Ball

Single type

Double type

PTEE

Copper pipe



YBF-1E



YBF-2E

■Features

- 1. Flexible joint for general piping (to absorb misalignment)
- 2. Stainless steel wetted parts provide excellent corrosion resistance.

■Specifications

Model		YBF-1E	YBF-2E	
Application		Steam, Air, Cold and hot water, Oil, Other non-dangerous fluids		
Maximum pressure		1.0 MPa	15A-200A 250A	1.0 MPa 0.5 MPa
Maximum temperature		220°C		
Material	Connection	SS400		
	Braid	Stainless steel (SUS 304)		
	Bellows	Stainless steel (SUS 304)		
Connection		JIS Rc screwed (union joint)	JIS 10K FF flanged (loose flanges on both sides)	

- Available with tube made of stainless steel (SUS316L).
- Available with all stainless steel made (YBF-6E-7E).
- For vibration absorption around pump, the YBF-2EM (flanged type only) is appropriate. Contact us for details.

■Dimensions (mm)

· YBF-1E


Nominal size	L	Shortest distance between surface
15A		120
20A	300	150
25A	500	150
32A	800	170
40A	1000	180
50A		200



YBF-1E

· YBF-2E

Nominal size	L	Shortest distance between surface
15A		150
20A	300	
25A	400	
32A	500	
40A	600	
50A	700	
65A	800	
80A	1000	
100A		
125A	300-400-500	200
150A	600-700-800	
200A	1000-1200	
250A	1500-2000	250



YBF-2E