




Size	ID	OD	Flange JIS 10K				G	最高使用圧力 (MPa)
			D	C	T	n-h		
15A	13.0	19.6	95	70	12	4-15	51	1.0
20A	19.0	26.9	100	75	14	4-15	56	1.0
25A	25.3	34.0	125	90	14	4-19	67	1.0
32A	33.5	42.2	135	100	16	4-19	76	1.0
40A	39.1	49.1	140	105	16	4-19	81	1.0
50A	52.6	63.1	155	120	16	4-19	96	1.0
65A	66.0	78.6	175	140	18	4-19	116	1.0
80A	75.0	93.3	185	150	18	8-19	126	1.0
100A	101.0	123.0	210	175	18	8-19	151	1.0
125A	123.8	148.5	250	210	20	8-23	182	1.0
150A	148.8	175.5	280	240	22	8-23	212	1.0
200A	194.6	225.0	330	290	22	12-23	262	1.0
250A	243.0	267.0	400	355	24	12-25	324	0.5

(mm)

(mm)
L

4	Loose Flange	Rolled Steel	ルーズフランジ	SS400	2
3	Ring	Stainless Steel	コンセントリング	SUS304	2
2	Braid	Stainless Steel	ブレード	SUS304	1
1	Tube	Stainless Steel	チューブ	SUS304	1
No.	Name of Parts	Material	部品名	材質	Q.TY

Specification	
Fluid	
Press.	MPa
Temp.	℃

TYPE YBF-2E FLEXIBLE JOINT
フレキシブルジョイント

Approval	H. Iwamoto
Check	Y. Aoyama
Drawing	J. Takagi
Drawing No.	Y-836-3605-2C
Date	25 NOV. 2014